

O. D. CHARTS FOR PVC
SCREWED VILTER GLOBE VALVES

WALL THICKNESS

| IPS | 1 - 1-1/2 | 2 | 2-1/2 - 3 |
|-------|-----------|-----|-----------|
| 1/2 | 4.0 | 5.0 | 6.5 / 7.5 |
| 3/4 | 4.5 | 5.0 | 6.5 / 7.5 |
| 1 | 4.5 | 5.5 | 6.5 / 7.5 |
| 1-1/4 | 7.5 | 8.5 | 9.5 |
| 1-1/2 | 8.5 | 9.5 | 10.5 |
| 2 | 8.5 | 9.5 | 10.5 |

SCREWED VILTER ANGLE VALVES

WALL THICKNESS

| IPS | 1 - 1-1/2 | 2 | 2-1/2 - 3 |
|-------|-----------|-----|-----------|
| 1/2 | 4.0 | 5.0 | 6.5 / 7.5 |
| 3/4 | 4.0 | 5.0 | 6.5 / 7.5 |
| 1 | 4.5 | 5.5 | 6.5 / 7.5 |
| 1-1/4 | 7.5 | 8.5 | 9.5 |
| 1-1/2 | 8.5 | 9.5 | 10.5 |
| 2 | 8.5 | 9.5 | 10.5 |

THESE ARE STANDARD TEE SHAPED VALVES. VALVES WITH THE SAME O.D. AS ADJACENT PIPE COVERING, USE 1 TEE AND 1 CAP.
 VALVES WITH THE O.D. LARGER THAN THE ADJACENT PIPE COVERING, USE 1 TEE AND 3 CAPS.