



# Rotary Tillers D E F



D



E

F

**HORSEPOWER RANGE:** For tractors up to max 100 PTO HP.

**LINKAGE:** Cat II Adjustable clevis mounting brackets for Central or Offset mounting (up to 4" to the right of PTO).

**TRANSMISSION:** 1 3/8" 6 spline 540 RPM driveline and Dry Plate Friction Slip Clutch to a 4 speed gearbox. Power transmitted from gearbox pinion and crown wheel to rotor by jackshaft and gear side drive.

**ROTOR SPEEDS:** (169, 195, 238, 276 RPM @ 540 PTO). Alternative speeds are available for specialized applications.

**OPTIONS:** Adjustable Depth Control Wheels & Rollers, Double Flange Kit, UHMW Poly Liner, Front Discs, Tractor Track Eliminator, Spike Rotors, Raised Bed Shaper.

**DEPTH CONTROL:**

Adjustable Depth Control Skids.

**HORSEPOWER RANGE:** For tractors up to max 120 PTO HP.

**LINKAGE:** Cat II floating clevis mounting brackets. Center mount only.

**TRANSMISSION:** 1 3/8" 6 spline 540 RPM driveline and Dry Plate Friction Slip Clutch to a 4 speed gearbox. Power transmitted from gearbox pinion and crown wheel to rotor by jackshaft and gear side drive.

**ROTOR SPEEDS:** (168, 208, 240, 298 RPM @ 540 PTO). Alternative speeds are available for specialized applications.

**OPTIONS:** Double Flange Kit, UHMW Poly Liner, Front Discs, Tractor Track Eliminator, Spike Rotors, Raised Bed Shaper.

**DEPTH CONTROL:**

*Specify on order:*

- A. Adjustable Depth Control Skids
- B. Adjustable Depth Control Wheels
- C. Adjustable Depth Control Roller

**HORSEPOWER RANGE:** For tractors up to max 140 PTO HP.

**LINKAGE:** Cat II clevis mounting brackets. Center mount only.

**TRANSMISSION:** 1 3/8" 21 spline 1,000 RPM driveline and automatic torque limiter to a 3 speed (external lever change) gearbox. Power transmitted from gearbox pinion and crown wheel to rotor by jackshaft and gear side drive.

**ROTOR SPEEDS:** (156, 191, 234 RPM @ 1000 PTO). Alternative speeds (233, 287, & 350) are available for specialized applications.

**OPTIONS:** Double Flange Kit, UHMW Poly Liner, Front Discs, Tractor Track Eliminator, Spike Rotors, Raised Bed Shaper.

**DEPTH CONTROL:**

*Specify on order:*

- A. Adjustable Depth Control Skids
- B. Adjustable Depth Control Wheels
- C. Adjustable Depth Control Rollers

MODEL	TILLAGE WIDTH		MAX PTO	# OF	WEIGHT		MAX DEPTH	
	IN	(CM)	HP	BLADES	Lbs	(Kg)	IN	(CM)
D4 1600	62	(158)	100	36	1168	(540)	8	(20)
D4 1800	72	(182)	100	42	1301	(590)	8	(20)
D4 2100	81	(206)	100	48	1411	(640)	8	(20)
D4 2300	91	(231)	100	54	1543	(700)	8	(20)
D4 2500	100	(254)	100	60	1653	(750)	8	(20)
E 2500	95	(242)	120	54	*1830	*(830)	8	(20)
E 3000	113	(288)	120	66	*2050	*(930)	8	(20)
F 2500	95	(242)	140	54	*2270	*(1030)	8	(20)
F 3000	113	(288)	140	66	*2557	*(1160)	8	(20)

\*Weight is without DC Skids, Wheels, or rollers.

All Other Weights include DC Skids.

SPECIFICATIONS MAY CHANGE WITHOUT NOTICE

**FALC** - Via Proventa, 41 - 48018 FAENZA (ITALIA) - e-mail: info@falc1960.com - www.falc1960.com

**GUY MACHINERY** (815)338-0600 Phone  
 14213 W. Washington ST. (815)338-2525 Fax  
 Woodstock, IL 60098 0.5 Mile from US Hwy 14 on IL 120  
 guymachinery@yahoo.com