



CATALOG 2020

is gator tough

SAE 100R1AT DIN EN 857

Cover: Black, oil resistant- Synthetic Rubber (Bio-Oil Resistant)

Tube: Black, oil resistant, Nitrile

Reinforcement: one layer of high tensile steel wire

Temperature Range: -40° F to 260° F

MSHA Approved Flame-Resistant



Part #	Hose ID		Hose OD		Max. Oper. Pressure	Min. Burst Pressure	Min. Bend Radius		Hose Length
	mm	in.	mm	in.	PSI	PSI	mm	in.	one piece
1/4"-4	6.4	0.25	13.5	0.53	4,000	13,000	100	4.00	328 ft
3/8"-6	9.5	0.38	18	0.69	3,000	13,600	130	5.00	328 ft
1/2"-8	12.7	0.50	21	0.81	3,000	12,000	180	7.00	328 ft
5/8"-10	15.9	0.63	23.8	0.94	2,000	7,540	203.2	8.00	154 ft.
3/4"-12	19.1	0.75	28	1.09	2,000	8,000	240	9.50	154 ft
1"-16	25.4	1.00	36	1.41	1,500	6,000	300	12.00	154 ft
1-1/4"-20	31.8	1.25	43	1.71	1,000	4,000	420	16.50	154 ft
1-1/2"-24	38.1	1.50	51	2.00	750	3,000	500	20.00	154 ft
2"-32	50.8	2.00	64	2.54	575	2,400	630	25.00	154 ft

SAE 100R2AT DIN EN 8 2SN

Cover: Black, oil and abrasion resistant- Neoprene

Tube: Black, oil resistant, Nitrile (BTR)

Temperature Range: -40° F to 260° F

Reinforcement two braids of high tensile steel wire

MSHA Approved Flame-Resistant



Part #	Hose ID		Hose OD		Max. Oper. Pressure	Min. Burst Pressure	Min. Bend Radius		Hose Length
	mm	in.	mm	in.	PSI	PSI	mm	in.	one piece
1/4"-4	6.5	0.25	15.2	0.59	6,500	26,000	101.6	4.00	328 ft
3/8"-6	9.5	0.38	19	0.75	5,800	23,200	127	5.00	328 ft
1/2"-8	12.7	0.50	22	0.875	5,000	20,000	177.8	7.00	328 ft
5/8"-10	15.9	0.63	25	1.00	4,000	16,000	203.2	8.00	154 ft
3/4"-12	19.1	0.75	29	1.16	3,125	12,500	241.3	9.50	328 ft
1"-16	25.4	1.00	38	1.50	3,000	12,000	304.8	12.00	154 ft
1-1/4"-20	31.8	1.25	48	1.88	2,250	10,000	419.1	16.50	154 ft
1-1/2"-24	38.1	1.50	55	2.16	2,000	8,000	508	20.00	154 ft
2"-32	50.8	2.00	68	2.66	1,500	6,000	635	25.00	154 ft



CATALOG 2020

is gator tough

SAE 100R16AT

Meets or exceeds SAE 16 types S, EN857 25C, ISO 11237-1 Type 25C

Cover: Black, oil and abrasion resistant- Neoprene

Tube: Black, oil resistant, Nitrile (BTR)

Temperature Range: -40° F to 260° F

Reinforcement two braids of high tensile steel wire

MSHA Approved Flame-Resistant



Part #	Hose ID		Hose OD		Max. Oper. Pressure	Min. Burst Pressure	Min. Bend Radius		Hose Length
	mm	in.	mm	in.	PSI	PSI	mm	in	one piece
1/4"-4	6.4	0.25	13.5	0.53	6,500	26,000	50.8	2.00	328 ft
3/8"-6	9.5	0.38	18	0.69	5,000	20,000	63.5	2.50	328 ft
1/2"-8	12.7	0.50	21	0.82	5,000	20,000	88.9	3.50	328 ft
5/8"-10	15.9	0.63	24	0.94	4,000	16,000	101.6	4.00	154 ft.
3/4"-12	19.1	0.75	28	1.103	3,120	12,480	120.7	4.75	154 ft
1"-16	25.4	1.00	36	1.415	3,000	12,000	152.4	6.00	154 ft

GATOR SUPERFLEX 3000 EN 857

Cover: Black, oil and abrasion resistant- Neoprene

Tube: Black, oil resistant, Nitrile (BTR)

Reinforcement: Two braids of high tensile steel wire

Temperature Range: -40° F to 212° F

MSHA Approved Flame-Resistant



Part #	Hose ID		Hose OD		Max. Oper. Pressure	Min. Burst Pressure	Min. Bend Radius		Hose Length
	mm	in.	mm	in.	PSI	PSI	mm	in	one piece
2"-32	50.8	2	66.7	2.63	3,000	12,000	430	16.93	154 ft.



CATALOG 2020

is gator tough

SAE 100R12 DIN EN 857

Cover: Black, oil and abrasion resistant- Neoprene
 Tube: Black, oil resistant, Nitrile
 Reinforcement four spiral layers of high tensile steel wire
 Temperature Range: -40° F to 212° F

MSHA Approved Flame-Resistant



Part #	Hose ID		Hose OD		Max Oper. Pressure	Min. Burst Pressure	Min. Bend Radius		Hose Length
	mm	in.	mm	in.	PSI	PSI	mm	in	one piece
1/2"-8	12.7	0.50	23.4	0.92	6000	24000	90	3.50	328 ft
3/4"-12	19.1	0.75	31	1.20	6000	24000	120	4.75	154 ft
1"-16	25.4	1.00	38	1.48	6000	24000	150	6.00	154 ft
1-1/4"-20	31.8	1.25	47	1.83	5000	24000	210	8.25	154 ft
1-1/2"-24	38.1	1.50	55	2.18	4000	16000	250	10.00	154 ft
2"-32	50.8	2.00	68	2.69	5000	22500	320	12.50	154 ft

4 SH DIN EN 857

Cover: Black, oil and abrasion resistant- Synthetic
 Tube: Black, oil resistant, Synthetic
 Reinforcement: four spiral layers of high tensile steel wire
 Temperature Range: -40° F to 212° F

MSHA Approved Flame-Resistant



Part #	Hose ID		Hose OD		Max. Oper. Pressure	Min. Burst Pressure	Min. Bend Radius		Hose Length
	mm	in.	mm	in.	PSI	PSI	mm	in	one piece
5/8"-10	15.9	0.63	28.2	1.11	6,000	24,000	100	4.00	154 ft
3/4"-12	19.1	0.75	33	1.27	6,090	24,360	280	11.00	154 ft
1"-16	25.4	1.00	38	1.5	6,000	24,000	340	13.38	154 ft
1-1/4"-20	31.8	1.25	42	1.79	5,000	20,000	460	18.11	154 ft
1-1/2"-24	38.1	1.50	54	2.11	5,000	20,000	560	22.05	154 ft
2"-32	50.8	2.00	68	2.68	3,625	14,500	700	27.56	154 ft



CATALOG 2020

is gator tough

PUSH ON HOSE

Cover: Black Neoprene
 Tube: Nitrile (Bio-Oil Resistant)
 Reinforcement: One Fiber braid
 Temperature Range -40° to 212° F



Part #	Hose ID		Hose OD		Max. Oper. Pressure	Min. Burst Pressure	Min. Bend Radius		Hose Length
	mm	in.	mm	in.	PSI	PSI	mm	in	one piece
1/4"-4	6.4	0.25	12.7	0.5	400	1,600	76.2	3.00	328 ft
3/8"-6	9.5	0.38	17	0.65	400	1,600	76.2	3.00	328 ft
1/2"-8	12.7	0.50	19.1	0.75	400	1,600	127	5.00	328 ft
5/8"-10	15.9	0.63	22.2	0.88	300	1,200	152.4	6.00	154 ft
3/4"-12	19.1	0.75	26	1.03	300	1,200	177.8	7	154 ft
1"-16	25.4	1.00	37	1.44	250	1,000	184.2	7.25	154 ft

Pressure Washer Hose

4,000 PSI -One Braid of High tensile steel wire
 Temperature- 40° to 212° F
 Tube-synthetic rubber

Black-Blue-Grey



Part #	Hose ID	OD	W.P.	Spool Size
Black	3/8"	0.68	4,000	300 ft.
Blue/Grey	3/8"	0.68	4,000	300 ft.

6,000 PSI -Two Braid of High tensile steel wire
 Temperature- 40° to 212° F

Tube-synthetic rubber

Black-Blue

Part #	Hose ID	OD	W.P.	Spool Size
Black	3/8"	0.71	6,000	300 ft.
Blue	3/8"	0.71	6,000	300 ft.



CATALOG 2020

is gator tough

Pressure Washer Assemblies - 4,000 PSI

Part #	Hose ID	Length	Color
384000X25	3/8"	25 ft.	Black
384000X50	3/8"	50 ft.	Black
384000X100	3/8"	100 ft.	Black
384000X25B or G	3/8"	25 ft.	Blue/Grey
384000X50B or G	3/8"	50 ft.	Blue/Grey
384000X100B or G	3/8"	100 ft.	Blue/Grey



Pressure Washer Assemblies - 6,000 PSI



Part #	Hose ID	Length	Color
386000X25	3/8"	25 ft.	Black
386000X50	3/8"	50 ft.	Black
386000X100	3/8"	100 ft.	Black
386000X25B	3/8"	25 ft.	Blue
386000X50B	3/8"	50 ft.	Blue
386000X100B	3/8"	100 ft.	Blue

Custom lengths are available upon request

1

1

1

2

1

1

