



Spears Racing
15253 S.Inheritance Way
Manteca Ca, 92336 USA

INTSTALLATION PROCESS:
SP28-250/300 SB Superbike Kit
99-02 Suzuki SV650S RACE
USE ONLY!

Step 1:

Identify the key components that complete our Superbike kit:
You should have 1lines (front kit), 1 Single banjo bolt and 2 lower adapters. There are also a total of 3 washers.
We strongly suggest having a professional mechanic install these brake lines, all other installations VOID
warranty. Inspect your brake system after every race.

Step 2:

Cover the complete front end of the bike so that if any brake fluid does spill the paint will not be damaged,
brake fluid will spill, there is no question!!

Step 3:

Uninstall stock hoses; be aware of how the stock system was routed in case you need to re-install it.

Step 4:

Install the Spears adapters onto the calipers. These adapters thread to the caliper with one washer. Torque level
is 12 to 13 ft pounds. (See picture A1)

Step 5:

Install right line to the calipers; t

These lines will travel from the master cylinder to the calipers; a single banjo bolt (see picture A2) is included
to run single line down. The positioning sequence on the master cylinder is as follows:

Master cylinder, washer, 12-degree banjo, washer, and single banjo hex.. Single banjo bolt torque level is 12 FT
Pounds. (See picture A3 for positioning)

Make sure that the 90-degree fittings on the caliper are positioned parallel to the fork (see picture A4). Thread
banjo end into the adapter, and torque the end to 6 ½ Ft pounds. Brake lines must be zip-tied to fork legs (see
picture A5).

Before you proceed to the next step, please check for clearance of the lines. Compress the front end to make
sure that the lines are not binding with anything. When the front end is fully extended or fully compressed,
double check that the lines are traveling correctly and clear from any obstructions.

Step 6:

Bleed brake system according to owner's manual, and build appropriate pressure. Finishing with DOT 4-brake
fluid is recommended.



Spears Racing

15253 S. Inheritance Way,
Manteca, Ca 95336 USA

Step 7:

Once the bleeding has been done, please check brake fluid level on master cylinder.

Close brake fluid reservoir, and zip tie the brake lever to the throttle for at least 2 hours to ensure no leaks or other possible issues. If the lines are not leaking and all looks OK, you may now ride with the new system.

Make sure that the rider is aware that the overall feel has dramatically changed. We suggest taking it easy to get used to the new brake lever feel and pressure.

We also always suggest checking the brake system after every race or in the event of a crash. Brake lines must be checked **very** carefully! If there are any signs of damage or stress to the lines, the complete brake system must be replaced. If you have any problems please call us at 209-923-4684.

Pictures:



← A1 (male end that goes at caliper)



← A2 (Single banjo bolt)



Spears Racing
15253 S. Inheritance Way
Manteca Ca, 95336 USA



← A3 (master cylinder)



← A4 (right caliper)