

## Modern American line

Technical Information		Retail Price	Weight	Footprint		Firebox		Wood Length	Load per Firing	Heat Output per Firing
				Width	Depth	W	D			
		USD	lb	in.	in.	in.	in.	in.	lb	Btu
<b>Small Models</b>										
TU1000/50 Grafia	4' height, base vent, Grafia texture	\$5,990	2,200	33.1	18.9	12.2	9.6	10	18	114,000
TU1000T/50 Grafia	5' height, top vent, Grafia texture	\$7,290	2,800	33.1	18.9	12.2	9.6	10	22	139,000
TU1000/92	5' height, base vent	\$6,990	2,700	33.1	18.9	12.2	9.6	10	22	134,000
TU1000T/92	5' height, top vent	\$6,990	2,700	33.1	18.9	12.2	9.6	10	22	134,000
<b>Mid-Sized Models</b>										
TU2200/92	5' height, base vent	\$8,290	3,900	40.2	23.6	15.7	14.4	14	31	200,000
TU2200T/92	5' height, top vent	\$8,290	4,000	40.2	23.6	15.7	14.4	14	32	196,000
TU2200/50 Grafia	5' height, base vent, Grafia texture	\$8,990	3,900	40.2	23.6	15.7	14.4	14	31	200,000
TU2200T/50 Grafia	5' height, top vent, Grafia texture	\$8,990	3,900	36.6	29.5	14.4	12.0	12	31	191,000
TLU2000/92	5' 5" height, 15.4" x 18.3" bakeoven, base vent	\$10,990	4,300	36.6	29.5	14.4	12.0	12	34	218,000
TLU2000/94	5' 5" height, 15.4" x 18.3" rear-facing bakeoven, base vent	\$10,990	4,300	36.6	29.5	14.4	12.0	12	34	218,000
TLU2000/50 Grafia	5' 5" height, 15.4" x 18.3" bakeoven, base vent, Grafia texture	\$11,490	4,300	36.6	29.5	14.4	12.0	12	34	218,000
<b>Large Models</b>										
TTU2700/8	6' height, top vent	\$10,990	5,700	40.2	29.5	15.7	19.7	16	46	266,000
TLU2450/92	5' 6" height, 17.7" x 21.9" bakeoven, base vent	\$14,990	5,700	42.5	35.4	15.7	14.4	14	46	269,000
<b>Optional Features (selection)</b>										
TU22Bench	Soapstone two-sided bench for TU2200 (adds 2 3/8" to height)	\$1,265	550	68.5	27.8					
M10L	Tulikivi Classic soapstone tiles, per square foot	\$17	5	11.8	11.8					
5123	Electric elements 2 kW	870	6							

- /92 models have square doors, corners & lids and straight mantels under & above the firebox door
- /50 models have square doors & lids and 45-degree mitered corners (no corner posts) • /8 models have square doors, corners & lids
- Retail Price: delivery and on-site assembling are not included. Heat shields, hearth tiles, benches & other accessories are available as optional features
- Weight: Tulikivi heaters are high thermal mass appliances and require appropriate structural support. Being a naturally occurring material, soapstone can vary in weight
- Load per Firing : recommended load is 0.8% of the heater's weight. At least 10 hours between firings
- Warranty: 5 years. Tulikivi heaters must be assembled on site by a Tulikivi installer. They are UL/ULC safety tested & listed and don't require EPA certification
- Chimney: 20' minimum height from floor for models with bakeovens, 15' otherwise. Recommended flue dia.: 6" or 7" for small models, 7" or 8" otherwise
- Clearances to combustibles: 20" to back, 14" to sides, 10" to top and 48" to front. Those can be reduced to 3" with a Tulikivi specified heat shield
- Floor protection: 3/8" min. thickness of non-combustible material, extending 8" from sides, 8" from back (unless a heat shield is used) and 16" from front of the heater

