

Material Safety Data Sheet

No-Burn[®] PLUS XD

I. PRODUCT IDENTIFICATION

DISTRIBUTOR NO-BURN[®], INC. 1392 HIGH STREET SUITE 211 WADSWORTH, OHIO 44281

PHONE NUMBERS 330-336-1500 or 800-989-8577

PRODUCT CLASS Fire Retardant Paint

SHIPPING NAMES No-Burn[®] Plus XD

PIN # Not Applicable

NFPCA-HMIS RATINGS

| HEALTH: | 1 |
|---------------|---|
| FLAMMABILITY: | 1 |
| REACTIVITY: | 0 |

II. HAZARDOUS INGREDIENTS

 COMPONENT
 CAS. NO.
 LD50 SPEC
 LC50 SPEC
 %WT/WT

 -Triamino-s-trianzine 108-78-01
 N/Av
 N/Ap
 <10%</td>

 -Other Materials
 Not Regulated >42%

-Trade Secret per CFR 1910.1200

III. PHYSICAL DATA

| SPECIFIC GRAVITY | 1.25 | % VOLATILE BY VOL | 45% |
|--------------------------|--------|-------------------|-----|
| BOILING POINT | 212F | EVAPORATION RATE | N/A |
| рН | 7-8 | VAPOR PRESSURE | N/A |
| PHYSICAL STATS | LIQUID | VAPOR DENSITY | N/A |
| FREEZING POINT | 32F | ODOUR THRESHOLD | N/A |
| COEF. OF WATER/OIL DISTR | N/A | | |

APPEARANCE OPAQUE, SLIGHT FREE-FLOWING LIQUID

IV. FIRE AND EXPLOSION INFORMATION

FLASH POINT N/Av AUTOIGN TEMP N/Ap LEL/UEL (%) N/Ap

EXTINGUISHING MEDIA Carbon Dioxide, Dry Chemical, Alcohol Foam **CONDITIONS OF FLAMMABILTY** Dried solid residue is slightly combustible

SENSITIVITY TO MECHANICAL IMPACT N/Ap SENSITIVITY TO STATIC DISCHARGE N/Ap

SPECIAL FIRE FIGHTING HAZARDS Wear positive-pressure SCBA

V. REACTIVITY

INSTABILITY STABLE UNDER NORMAL CONDITIONS

CONDITIONS OF REACTIVITY NO SPECIAL REACTIVITY

INCOMPATIBILITY STRONG OXIDIZERS

VI. HEALTH HAZARD INFORMATION

EYES/SKIN: Causes irritation. Repeated exposure may cause allergic dermatitis.

INHALATION: Short-term exposure may cause irritation of nose, throat and lungs.

INGESTION: Possible stomach irritation and nausea. No other harmful effects anticipated.

FIRST AID

- **INHALATION:** Remove person to fresh air. If necessary, give artificial respiration or CPR.
- **SKIN CONTACT:** Wash skin with soap and water. Launder clothing before reuse.
- **EYE CONTACT:** Immediately flush with gentle stream of tepid water for 15 minutes. Get medical attention if necessary.
- **INGESTION:** Do not induce vomiting. Keep warm and at rest. Give 2-3 glasses of water or milk. Get medical attention if necessary.

VII. SPECIAL PROTECTION INFORMATION

EYE/FACE PROTECTION: Wear goggles to avoid overspray and splashing. Eye and face protection should be in accordance with OSHA 29 CFR 1910.133.

RESPIRATORY PROTECTION: If sprayed, wear a mask approved by NIOSH/MSH for organic vapors with dust/mist pre-filter. If used in a confined area, a full-face, positive-pressure airline respirator is recommended.

VIII. DISPOSAL/PREVENTATIVE INFORMATION

PRECAUTIONS TO BE TAKEN DURING HANDLING AND STORAGE

Avoid breathing vapors, avoid prolonged skin contact Store in cool, dry location away from light and strong frost Storage Temperature Maximum: 90°F Minimum: 40°F

ENGINEERING CONTROLS Use local exhaust ventilation if sprayed inside. Otherwise, general ventilation is adequate.

WASTE DISPOSAL Plastic pails are recyclable. Rinse well before recycling or disposal. Contact local authorities for further information.

IX. DOCUMENT INFORMATION

PREPARED BY Keith Kastendieck, Safety Compliance Director