



**SEWER SERVICE NOTES**

1. SERVICE PIPE TO HAVE 5' TO 6' OF COVER AT PROPERTY LINE OR AT END OF SERVICE PIPE.
2. USE 4" PIPE FOR RESIDENTIAL SERVICE LINE, USE 6" PIPE FOR COMMERCIAL SERVICE LINE, UNLESS NOTED OTHERWISE ON THE PLANS.
3. LOTS WITHOUT UTILITY EASEMENTS SHALL HAVE SERVICE PIPE INSTALLED TO PROPERTY LINE. LOTS WITH UTILITY EASEMENT SHALL HAVE SERVICE PIPE INSTALLED THROUGH EASEMENT, UNLESS NOTED OTHERWISE ON PLANS.
4. FOR DEEP SEWER MAINS, THE WYE AND 1/8 BEND SHALL BE ROTATED TOWARD THE VERTICAL POSITION AS REQUIRED TO OBTAIN 5-6 FEET COVER OVER SERVICE PIPE AT PROPERTY LINE OR AT END OF SERVICE PIPE.
5. END OF SERVICE PIPE TO BE PLUGGED AND MARKED AS NOTED.
6. WHERE CURBS ARE PROPOSED, CONTRACTOR IS TO MARK TOP OF CURB WITH "S" AT ALL SERVICE LOCATIONS AFTER CURBS ARE INSTALLED.

**SEWER SERVICE INSTALLATION DETAIL-MANHOLE RISER**

(OR APPROVED EQUAL)  
N.T.S.

NOTE: AT MANHOLE COPPER WIRE IS TO FOLLOW MANHOLE SHAFT UP TO 1ST ADJUSTMENT RING. BEFORE ADJUSTMENT RING IS PLACED, BEND WIRE TO INSIDE OF MANHOLE—LEAVE ABOUT 6" HANGING.