



CONTROL CIRCUIT WIRE: 16 AWG SEW 200°C
LOAD CIRCUIT WIRE: 10 AWG SEW 200°C

3E-75113 R5
SX-3 & SX-5 (208-240V)

ITM	DESCRIPTION	PART NO.	QTY	
*1A	TERMINAL BLOCK (BLK), 7.5/10kW	4-22TB	4	
*1B	TERMINAL BLOCK END (BLK), 7.5/10kW	4-22ES	1	
*1A	TERMINAL BLOCK (WHT), 12/15kW	4-33TB	4	
*1B	TERMINAL BLOCK END(WHT), 12/15kW	4-33ES	1	
2	SWITCH, ON/OFF/DELIME	9124-1	1	
3	THERMOSTAT, HIGH LIMIT SAFETY	9128-1	1	
4	LEVEL CONTROL, 10K OHM	4038-3	1	
5	PROBE, LOW LEVEL CUT-OFF	3738-3	1	
6	PROBE, LOW LEVEL	3738-2	1	
7	PROBE, HIGH LEVEL	4-LLP2	1	
8	READY PILOT, GREEN	4-PL04-1	1	
9	THERMOSTAT, OPERATING	9126-1	1	
10	DOOR SWITCH	9-3213	1	
11	RELAY, DPDT	9-3174	1	
12	TIMER	4-T209-1	1	
13	BUZZER	4742-1	1	
14	COOKING PILOT, RED	4-PL07-1	1	
*15	COOLING SOLENOID VALVE, 12/15kW	3-1175	1	
*15	COOLING SOLENOID VALVE, 7.5/10kW	5162-2	1	
16	FILL SOLENOID VALVE	5162-2	1	
17	BLOW-DOWN VALVE	3-S543-1	1	
18	CONTACTOR, 208V-240V	4916-1	1	
*19	ELEMENT ASSEMBLY	SEE BELOW	1	
Volts	kW	Amperes		Part No.
208	7.5	1 Phase	3 Phase	8-5051
	10	48.1	27.8	8-5050
	12	57.7	33.3	2349-1208
	15	72.2	41.6	8-5053
220	7.5	34.1	19.7	8-5220
	10	45.5	26.3	8-5056
	12	54.5	31.5	2349-1220
240	15	68.2	39.4	8-5054
	7.5	31.3	18.1	8-5240
	10	41.7	24.1	8-5051
	12	50.0	28.9	2349-1240
15	62.5	36.2	8-5055	
20	FUSE, 2A, 250V	9092-2	2	
21	FUSE HOLDER	9068-1	2	
22	PRESSURE SWITCH, 5PSI	5445-1	1	
23	RELAY, SPDT	9-3175	1	
*24	CONTINUOUS COOKING SWITCH, OPTIONAL	9096-1	1	
*25	LOAD COMPENSATE SWITCH, OPTIONAL	3-TS01	1	

* SELECT AS REQUIRED FOR VOLTAGE, KW OR MODEL.