



Made in Colorado, for Colorado's Climate!

0700 series Colorado Pro

CONTRACTOR FINISHES INTERIOR

Old Western Paint Co., Inc.

2001 W. Barberry Pl.
Denver, CO 80204
Phone: 303-825-5147
Fax: 303-825-2437
www.oldwesternpaint.com

Colorado Pro 700

Interior Contractor Primers
0710 Sandable Primer/Sealer

Description

Colorado Pro 700 Sandable Primer/Sealer 0710 is a professional quality primer and sealer that offers outstanding coverage and is easy to apply. It provides a smooth, tight surface which may be sanded for maximum gloss development and uniformity in the top-coat. It is recommended for previously painted surfaces and new construction, including gypsum board, drywall, woodwork, and cement block. This high-quality product is an excellent choice for professionals and do-it-yourselfers who want a high-hiding, easy-to-use primer.

Application and Substrate Information

Mix or stir thoroughly before using. Paint should be applied using appropriate brush, roller, or through airless spray equipment (2,000 psi, 0.015" – 0.021" tip). A second coat may be applied at a minimum of 3-4 hours after applying the first coat as drying conditions allow.

Recommended for properly prepared gypsum board, drywall, woodwork, and most previously painted interior surfaces. See General Surface Preparation for further details.

For best results, temperatures (air, surface and material temperatures) should be between 50°F – 90°F (10°-32°C) before applying.

Product Data

Gloss/Sheen (85°)	< 10
VOC Content (g/L)	< 30
Viscosity (Krebs Units)	102 (± 3)
Density (lb/gal)	11.0
Weight Solids	49 %
Volume Solids	32 %
Coverage (1.5 dry film)	325 ft ² *

*Theoretical value; may vary based on substrate porosity/application method

Features and Benefits

- ✓ Formulated and made in Colorado
- ✓ Excellent enamel hold-out
- ✓ Little to no spatter when rolled
- ✓ Good sandability
- ✓ High-hide to help cover previously painted surfaces
- ✓ May be tinted with up to 6 oz. of colorant per gallon to approximate top-coat color

Thinning

Thinning is not required, though a small amount of water can be added if desired. Thinned paint is more prone to in-can settling and biological contamination if not used immediately and/or stored over long periods of time.

Dry Time

Will dry to touch in one hour or less; may be recoated after four hours. Typically sandable after 4-8 hours, depending on drying conditions. Dry time may be affected by poor ventilation, low temperatures, amount of colorant and/or high humidity areas.

Clean-up

Clean all tools and equipment with warm, soapy water.

Environmental/Health Considerations

Formulated without lead, mercury, and other heavy metals. Does not contain ethylene glycol. No reportable amount of crystalline silica.



0700 series
Colorado Pro
CONTRACTOR FINISHES INTERIOR

Old Western Paint Co., Inc.

2001 W. Barberry Pl.
Denver, CO 80204
Phone: 303-825-5147
Fax: 303-825-2437
www.oldwesternpaint.com

Made in Colorado, for Colorado's Climate!

General Surface Preparation

All foreign material, including loose or peeling paint, dirt, grease, oil, wax, chalk, mildew, rust, dust, curing agents, etc., must be removed prior to use. Failing to do so may compromise proper adhesion and overall performance. Caulk all cracks and open seams. Putty all nail holes. An appropriate primer should be used when coating bare or porous substrates. A stain blocking primer is recommended over areas where stains would 'bleed through' to the surface. Glossy surfaces should be dulled prior to coating, and rough or patched surfaces should be sanded.

Specific Substrate Recommendations

Siding: Not recommended for exterior application.

Concrete/Masonry Block: May be used over previously painted block or concrete. Not recommended for new concrete.

Metal: May be used over previously painted metal substrates. Not recommended for direct to metal application.

Drywall/Gypsum Board: Nails and screws should be countersunk and properly covered using putty or drywall mud, then sanded to be flush with the rest of the surface.

Wood: Unpainted wood should be sanded smooth and wiped. May be sanded after fully cured. Not recommended for tannin containing woods such as redwood or cedar.

Available in 1-gallon and 5-gallon containers. Actual volume amounts of paint are indicated on the label. Volume is adjusted to account for the addition of colorants.

Intended Use

To be used in a manner consistent with latex wall paints and finishes. Do not take internally. Keep out of reach of children and pets. Not recommended for floors or where water can puddle. Keep from freezing.

WARNING: If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC AND MAY CAUSE SERIOUS ILLNESS IF YOU ARE EXPOSED, ESPECIALLY FOR CHILDREN OR THOSE WHO ARE PREGNANT. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to minimize lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. For further information, contact the U.S.E.P.A. National Lead Information Hotline at 1-800-424-LEAD or visit www.epa.gov/lead.

Disclaimer

All information and data appearing in this document are provided in good faith and are believed to be reliable and accurate to the best of our knowledge at the date of publication. None of the provided information is to be considered a warranty or quality specification or all-inclusive and is given only as a guidance. It is the user's responsibility to determine the intended utilization of the product. No guarantee, expressed or implied, is made by Old Western Paint Co., Inc. And the user assumes all risk and responsibility.