




Outside The Box

Cam Cover Installation Instructions


For Takegawa 4 Valve Head for the Honda Grom/Msx 125

Note: the OEM Cover and head are shown. Installation on the Takegawa head is the same.




Remove the two bolts holding in the OEM timing gear cover.

After removing the two bolts, remove the OEM timing gear cover.



*****ATTENTION*****
Remove the green tape securing the O-ring prior to installing the OTB Cover. Verify the O-ring is seated in the groove properly.

Firmly press your new OTB cover in place and screw in the top bolt. Hand tighten it to hold it in place. Then, do the same for the bottom bolt. Use the 2 bolts provided.



Screw in the top bolt by hand until it is snug, then screw in the bottom bolt the same way. Use a wrench to tighten the two bolts. This assures your new cover goes in straight and will not leak. The new cover should be tight against the motor housing when you are done.




Outside The Box

Cam Cover Installation Instructions


For Takegawa 4 Valve Head for the Honda Grom/Msx 125

Note: the OEM Cover and head are shown. Installation on the Takegawa head is the same.




Remove the two bolts holding in the OEM timing gear cover.

After removing the two bolts, remove the OEM timing gear cover.



*****ATTENTION*****
Remove the green tape securing the O-ring prior to installing the OTB Cover. Verify the O-ring is seated in the groove properly.

Firmly press your new OTB cover in place and screw in the top bolt. Hand tighten it to hold it in place. Then, do the same for the bottom bolt. Use the 2 bolts provided.



Screw in the top bolt by hand until it is snug, then screw in the bottom bolt the same way. Use a wrench to tighten the two bolts. This assures your new cover goes in straight and will not leak. The new cover should be tight against the motor housing when you are done.




Outside The Box

Cam Cover Installation Instructions


For Takegawa 4 Valve Head for the Honda Grom/Msx 125

Note: the OEM Cover and head are shown. Installation on the Takegawa head is the same.




Remove the two bolts holding in the OEM timing gear cover.

After removing the two bolts, remove the OEM timing gear cover.



*****ATTENTION*****
Remove the green tape securing the O-ring prior to installing the OTB Cover. Verify the O-ring is seated in the groove properly.

Firmly press your new OTB cover in place and screw in the top bolt. Hand tighten it to hold it in place. Then, do the same for the bottom bolt. Use the 2 bolts provided.



Screw in the top bolt by hand until it is snug, then screw in the bottom bolt the same way. Use a wrench to tighten the two bolts. This assures your new cover goes in straight and will not leak. The new cover should be tight against the motor housing when you are done.