



**ISA Delhi Section**

*Setting the Standard for Automation™*

## Energy And Emission : Monitoring And Control

Presented by : Piyush Tewari & Monali Fegade  
Emerson  
16<sup>th</sup> December 2023, New Delhi, India

**ISA-D: “Fertiliser , Food and Pharma Symposium-2023”**

*Copyright 2023. ISA. All rights reserved. [www.isadelhi.org](http://www.isadelhi.org)*

# Our Vision & Approach To Solve Industry's Challenges From Floor to Cloud™

---



**Increase Energy Efficiency & Reduce Waste**



**Improve Productivity, Speed, & Agility**



**Create Safer, More Reliable Operations**



**Gather Insights & Empower Workforce**


# Why Compressed Air?

## Challenges With Pneumatic Machines and Systems




### Air Leakages

Compressed Air Generated Goes To Waste Due To Leaks And Suboptimization Of Machines



### Inefficient Usage Of Air “Standby Loss”

Machines often consume compressed air even when not producing product & generating revenue




### Maintenance Intensity & Costs

On Average,  
**76%**  
Of Business Still Manually Test For Compressed Air Leaks Across Their Facility Costing an Average of  
**\$46K**  
per machine due to service, equipment & training investments<sup>1</sup>

1. Source: Hanover Research n=719

# PACEdge and Movicon Software Suites



# Jumpstart Your Energy Savings Journey

Emerson Discrete Automation, Compressed Air Manager is a ready-to-go hardware & analytics package that jumpstarts your path towards maximizing energy utilizations, reducing waste and energy costs.



## Compressed Air Manager Ready-To-Go Hardware & Software Solution

### Improve Energy Efficiency & Reduce Energy Costs



- Benchmark Air Consumption Trends
- Deep Dive Into Machine or Plant Consumption
- Visualize CO2 Impact & Energy Costs

### Empower Your Workforce



- Create Thresholds
- Quickly Identify Energy Reduction Opportunities
- Prioritize & Improve Maintenance Procedures

### Scale Within Your Network




- Edge-Enabled Technology
- Industry Standard Communication Across Sensors & Hardware e.g., OPC-UA

### Ready-To-Go Solution



- Auto-Configuration of Sensors
- Preconfigured Software & Hardware
- Reduce Config Timelines & Barrier Of Adoption

# Compressed Air Manager Solutions



## Compressed Air Manager

- ✓ Productized – Lowers Technology Adoption Barrier
- ✓ Focused Use-Case to **Start Small, Scale Fast & Prove ROI**
- ✓ Simplified update manager for future versions 1.0.X
- ✓ App-style GUI for control of all functions
- ✓ For Sensors: Add, commission, edit, delete **It's that easy**
- ✓ OPC UA as connector - Industry 4.0 ready

# Compressed Air Manager Features

## Part Number for Each World Area Created

### Compressed Air Manager



Software embedded in Edge Hardware / Enclosure



- PoE
- I/O
- Edge HW & SW
- Power Control
- Certifications

Up To x10  
Aventics AF2  
Air Flow  
Sensors



### Analytics & Monitoring Features



- Track Air Consumption Trends & Stats
- Identify Areas of Waste / Underutilization
- CO2 Emissions Impact & Associated Costs



- Analytics Integrated Within Emerson Edge HW
- **PACEdge** Software with pre-built UI

### Hardware Features



Bill of Materials Adjusted For Local / Regional Needs.




#### Cabinet Hardware Features:

- Edge Hardware **PACSystems RXi2** w/ SW
- I/O and Switch Connecting Up To x10 AF2
- Power Control Supply - **SolaHD**




#### Air Flow Sensor Features:

- Connect Up To x10 **Aventics AF2** Flow Sensors
- Ethernet-Based (OPC UA / MQTT)
- Captures Air Flow, Volume, Temperature



# Software Features




## Dashboard – Air Consumption View

- Visualization of overall airflow, pressure and temperature
- Calculation of statistics for max, min and mean
- Calculation of KPIs like volume, CO2 emission and cost
- Statistics based on selected time ranges

Name	IP Address	Description	Location	Status	Edit/Device
CH_PT_SACH_M_CNC_184C02_1465_01				OK	[Edit] [Device]
Sensit				OK	[Edit] [Device]
AF_53	192.168.0.53	description	location 26	OK	[Edit] [Device]
AF_54	192.168.0.54	description	location 26	OK	[Edit] [Device]
AF_52	192.168.0.52	testAF2	location1	OK	[Edit] [Device]

## Device Manager

- Add, commission, edit, delete of AF2 sensors
- Automatic parameterization of AF2
- Overview of the sensor in Device Manager



## Dashboard – Single Sensor View

- Visualization of airflow and pressure
- Calculation of statistics like max, min, mean for flow, pressure and temperature
- Calculation of KPIs like volume, CO2 emission, cost and IDLE time
- Statistics based on selected time ranges

BUNDLE	STATUS	EXECUTED DATE
Bundle 1	Completed	2023-07-01
Bundle 2	Completed	2023-07-02
Bundle 3	Completed	2023-07-03
Bundle 4	Failed	2023-07-04

## Settings – Restart & Update View

- Installation of Update Packages through browser window
- Extension of CAM software with new features or improvements

- Dashboard
- Air Consumption**
- Single Sensor
- Setting
- Device Manager
- About

Search or jump to... ctrl+k


Sign in

Home > Dashboards > Overall Air Consumption Timescale V1.0.0-RC

Last 24 hours

Select Device: All | Locations: All | Flow Rate Unit: m<sup>3</sup>/h | Pressure Unit: bar | Temperature Unit: °C | Volume Unit: m<sup>3</sup> | Weight Unit: kg | Costs / m<sup>3</sup>: 0.02

Energy Factor (kWh / m<sup>3</sup>): 0.06 | CO2 Factor (kg / kWh): 0.4 | Currency: €



Time Range Overall Consumption

Volume [m <sup>3</sup> ]	CO2 [kg]	Costs [€]
<b>1034</b>	<b>25</b>	<b>20.69</b>

Time Range Overall Consumption Last 24 hours

Volume [m <sup>3</sup> ]	CO2 [kg]	Costs [€]
<b>1034</b>	<b>25</b>	<b>20.69</b>

Time Range Overall Consumption Last 7 days

Volume [m <sup>3</sup> ]	CO2 [kg]	Costs [€]
<b>5441</b>	<b>131</b>	<b>108.82</b>

- Dashboard
- Air Consumption
- Single Sensor**
- Setting
- Device Manager
- About

Search or jump to... ctrl+k

Sign in

Home > Dashboards > TimeScale v1.0.0-RC1

Last 6 hours

Select Device: AF\_52 | 
 Flow Rate Unit: m<sup>3</sup>/h | 
 Pressure Unit: bar | 
 Temperature Unit: °C | 
 Volume Unit: m<sup>3</sup> | 
 Weight Unit: kg | 
 Costs / m<sup>3</sup>: 0.02  
 Energy Factor (kWh / m<sup>3</sup>): 0.06 | 
 CO2 Factor (kg / kWh): 0.4 | 
 Currency: €

Dashboard - A Untitled



Settings

Air flow ranges			
Name	Start	End	Unit

Application / Device Info

DeviceName: AF\_52  
 DeviceId: 8ffc43c-4f1f-4f72-9ed1-24986b63517f



Current Values

Flow [m <sup>3</sup> /h]	Pressure [bar]	Temperature [°C]
<b>14.7</b>	<b>6.0</b>	<b>20.5</b>

Flow [m <sup>3</sup> /...]	Pressure [...]	Temperat...
Max: <b>21.1</b>	Max: <b>6.2</b>	Max: <b>21.7</b>
Mean: <b>15.7</b>	Mean: <b>6</b>	Mean: <b>20.2</b>
Min: <b>10.1</b>	Min: <b>5.7</b>	Min: <b>18.7</b>

Idle Time

**0.0%**

Time Range Overall Consumption

Panel plugin not found: Unable to load

---

**Emission  
Monitoring & Control  
Why & How**

# Tank Farms Cover a Lot of Real Estate and Present Considerable Risks to Personnel, the Environment, and Equipment If Not Properly Maintained

## Fire hazard

-  12% of Tier 1 and 2 Safety Incidents Involve Storage Tanks<sup>1</sup>
-  Refineries and Terminals Accounted for 74% of Tank Accidents<sup>2</sup>
-  1/3 of Tank Accidents Are Caused by Personnel Error or Equipment Failure<sup>2</sup>
-  Fire and Explosions Account for 85% of Tank Accidents<sup>2</sup>
-  77% of Bulk Petroleum Storage Tank Terminal Locations Are Within 1 Mile of Communities with > 300K Residents<sup>3</sup>

Sources:

1. AFPM Reporting
2. Journal of Loss Prevention in the Process Industries, A Study of Storage Tank Accidents, Chang & Lin
3. US Chemical Safety and Hazard Investigation Board

## Product Loss

**\$5.5M**

Approximate Value of Crude Oil lost annually

Source: NYMEX Spot Prices August 2021


## Environmental

VOC control regulations (GB 37822-2019) enforced in China in July 2020. Korea and Thailand have followed suit

Source: Internal study


**These Risks Affect Various Stakeholders and Have Explicit and Implicit Costs**

# Emerson's integrated tank top portfolio ensures complete safety, tank integrity & emission control



Our PVRV's 10% overpressure technology, low leakage rate and high flow make them the preferred choice

## 10% overpressure tech saves OPEX



### Industry wide lowest leakage

API 2000 7<sup>th</sup> edition  
 permissible leakage : **0.5 to 20 SCFH at 75%** of set pressure

Our leakage rate : **<0.1 SCFH at 90%** of set pressure

### Key distinguishing factors

- High flow capacity helps **reducing CAPEX** due to downsizing
- PPS coating for sticky and corrosive fluids
- Steam jacket for freezing atm.


### Remote monitoring option



- Real time actionable intelligence
- Pallet position indicator
- Asset management tag

# Emerson's flame arrestors are designed for unstable detonation & endurance burning

## Designed for overdriven case



### International certifications



### Wide range

- 1" to 40" size
- IIA, IIB3, IIC, IIB gas group
- Short time burn, Endurance burn rating
- Special material options

### Remote monitoring option




- Real time actionable intelligence
- Differential pressure transmitter
- Temperature transmitter
- Asset management tag



# Engage with Emerson to understand your tank healthiness

## Schedule a Tank Walkdown




## Tank University session

- Detailed course covering end-to-end theoretical and practical aspects of tank pressure management and safety products
- Interact and deliberate process industry trends and drivers with other industry players
- Avail our technical consulting services to review your installations



# Global footprint of tank products manufacturing

---



## North America

Site: Tulsa, USA  
Brand : Enardo & Varec

## Europe

Site: Manchester, UK  
Brand : AMAL, AG


## Asia

Sites: Chengdu, China & Chennai, India  
Brand : Enardo, AG & Varec  
Products : Deflagration & Detonation FA, PVRV, EPRV, Combo unit

Help us help you in your safety journey

---

# Thank-you



Check out our brochures, white papers, success stories and a lot more.

