

Standard Features

Easy-to-Use Graphical Display of the Process Remote Connectivity and Support Recipe Control with Scheduler Customizable Security Access Temperature Control:

- Auto-Tune PID
- Extruder Preheat
- Soak Feature
- Broken Probe Alarm
- Open Heater Alarm
- Shorted Solid-State Relay Alarm
- High-Low Temperature Alarm (Indicated by Text Color and Flag)

Protective Features

- Cold Zone Start Inhibit
- Runaway Heat Warning and Shutdown
- High Pressure Shutdown

Data Collection (stored in a .CSV file format)


- Process Data
- Alarm Log
- Maintenance Log
- Trending Screen













SPECIFICATIONS

sign

PRICE DELIVERY QUALITY

Base Design

Voltage Input: 480 VAC, 3-Phase

Total Heat Zones: BASE CONFIGURATION: 480V Single Phase

5) Barrel Zones (30A) with cooling 4) Other Zones (30A) heat only

6) Die Zones (30A) heat only


Melt Pressure: Reading Input with Calibration

Melt Temperature: Reading

Additional Starters: 2 (Oil and Water Pumps)

Die Plugs: 6 Hubbell Receptacles with Disconnects

Primary Nip: 3 Hp Yaskawa AC Drive with Encoder Feedback
Touch Screen: 15" Color Touch-Screen Mounted on the Door



Part Number: PDQMono-15-00-15-5-A-6X-3-0

Options

5-10HP Primary Drive
Secondary Drive up to 10HP

Arc-Flash (Required with 480V/240V systems)

Swing Arm

Tower Lights/Buzzer
2 Additional Die Plugs
All 240V Zones / 240V Die Zones
480 V Three Phase Barrel

\$40,271

Base Design

Voltage Input: 480 VAC, 3-Phase

Total Heat Zones: BASE CONFIGURATION: 480V Single Phase

5) Barrel Zones (30A) with cooling

2) Other Zones (30A) heat only

8) Die Zones (30A) heat only

Melt Pressure: Reading Input with Calibration

Melt Temperature: Reading

Starters: 2 (Oil and Water Pumps)

Die Plugs: 8 Hubbell Receptacles with Disconnects

Puller Drive: 10 Hp Yaskawa AC Drive with Encoder Feedback

Touch Screen: 15" Color Touch-Screen Mounted on the Door



Part Number: PDQPipe-15-00-15-5-A-8X-10

Options

15HP or 20HP Puller Drive

Arc-Flash

(Required with 480V/240V systems)

Swing Arm

Tower Lights/Buzzer
2 Additional Die Plugs
All 240V Zones / 240V Die Zones
480 V Three Phase Barrel

\$41,978

CIFICATIONS

ase Design

Voltage Input: 480 VAC, 3-Phase

Total Heat Zones: BASE CONFIGURATION: 480V Single Phase

5) Barrel Zones (30A) with cooling

4) Other Zones (30A) heat only

6) Die Zones (30A) heat only

Reading Input with Calibration Melt Pressure:


Melt Temperature: Reading

Starters: 2 (Oil and Water Pumps)

Die Plugs: 4 Hubbell Receptacles with Disconnects

10 Hp Yaskawa AC Drive with Encoder Feedback Capstan Drive; Touch Screen:

15" Color Touch-Screen Mounted on the Door



Part Number: PDQWire-15-00-15-5-A-4X-10

Options

15HP or 20HP Capstan Drive

Arc-Flash

(Required with 480V/240V systems)

Swing Arm

Tower Lights/Buzzer

Additional Die Plugs All 240V Zones / 240V Die Zones 480 V Three Phase Barrel Lasermike input signal

\$40,736









Base Design

Voltage Input: 480 VAC, 3-Phase **Total Heat Zones:** BASE CONFIGURATION:

480V Three Phase

5) Barrel Zones (30A) with cooling

480V Single Phase

1) Other Zone (30A)

4) Die Zones

Melt Pressure: Reading Input with Calibration

Melt Temperature: Reading

Starters: 2 (Oil and Water Pumps)

4 Hubbell Receptacles with Disconnects Die Plugs: Auger Drive: 3 Hp AC Drive with Encoder Feedback

Touch Screen: 15" Color Touch-Screen Mounted on the Door Part Number: PDQComp-10-05-05-5-A-4X-03-00 Part Number: PDQPell-10-05-05-5-A-4X-03-00

\$38,658

Options

5HP Drive Upgrade

Arc-Flash

(Required with 480V/240V systems)

Tower Lights/Buzzer

2nd Feeder Drive

All 240V Zones / 240V Die Zones All 480V Single Phase System

STANDARDIZATION





(972) 906-7445 Give Us a Call!

www.integratedcontroltech.com