



**MODEL FTS7202**

*Shown with optional  
Snow Extreme Package,  
white vinyl sidewalls & ceiling liner*

**Snowmobile**

**TRAILERS**

# FASTTRAC



8.5'



74" Wide

## Mountain Tested and Trail Ready

The Wells Cargo FastTrac Snowmobile Trailer (FTS) merges economy and performance. The Deck-Over (sleds arranged side-by-side). Each style offers its own unique features. With its 6' long V-Front nose and low profile design improves fuel economy.



## 2-SLED MODELS



MODEL FTS85202



BY UNIVERSAL TRAILER

## 4-SLED MODELS

### STANDARD FEATURES — 8.5' WIDE MODELS

- 6' Long V-Front
- 74" Front Ramp Door with Spring Assist (*Roadside*)
- Ski Guide
- 91" Rear Ramp Door with Spring Assist
- Beavertail (*18' & 20' models = 32", All other models = 48"*)
- 16" High Performance Engineered Ramp Extension
- 32" Pre-Framed Side Door with Flush Lock & Dead Bolt
- Fold Out Steel Step
- 12v Dome Light (1)
- 24" Starbright Stoneguard
- 3-Piece A-Frame
- 2<sup>5/16</sup>" Ball Coupler Hitch (10,000 lb.)
- Top Wind Tongue Jack (2000 lb.) with Sand Pad
- Safety Chains & Breakaway Kit
- Entire Chassis Undercoated
- 24" Visqueen Corrosion Liner
- One-Piece Aluminum Roof
  - .030 Prefinished Aluminum Exterior Skin
  - LED Tail Lights & Clearance Lights
  - 24" OC Floor Crossmembers
  - 16" OC Vertical Wall Hat Posts
  - 16" OC Hat Section Roof Bows
- 3/4" High Performance Engineered Floor & Ramp Decking
  - 12" Kickplate (3/8" Plywood)
  - 3.6mm Luan Interior Sidewall Liner
  - 1000 lb. Recessed Floor Mounted Tie-Downs (4 or 6)
  - 3-Year Limited Warranty



### MODEL FTS85282

and versatility into one streamlined value-packed line-up. The FTS comes in two styles – the 7' wide In-Line (sleds arranged end-to-end) and the 8.5' wide Deck-Over. The Deck-Over features the widest front ramp door opening in the industry — **a full 74" of flat usable space**. The 7' wide In-Line offers superior handling and delivers superior handling. Both offer everything you need to safely and securely transport your snowmobiles (or ATV's) for many years to come.

MODEL	FTS85182	FTS85202	FTS85222	FTS85242	FTS85262	FTS85282	FTS85224	FTS85244	FTS85264	FTS85284	FTS85304
<b>Body Length:</b>	18'0"	20'0"	22'0"	24'0"	26'0"	28'0"	22'0"	24'0"	26'0"	28'0"	30'0"
<b>Body Width:</b>	8.5"	8.5"	8.5"	8.5"	8.5"	8.5"	8.5"	8.5"	8.5"	8.5"	8.5"
<b>Overall Length:</b>	20'4"	22'4"	24'4"	26'4"	28'4"	30'4"	24'4"	26'4"	28'4"	30'4"	32'4"
<b>Overall Width:</b>	8.5"	8.5"	8.5"	8.5"	8.5"	8.5"	8.5"	8.5"	8.5"	8.5"	8.5"
<b>Overall Height:</b>	110"	110"	110"	110"	110"	110"	111"	111"	111"	111"	111"
<b>Interior Length:</b>	17'4"	19'4"	21'4"	23'4"	25'4"	27'4"	21'4"	23'4"	25'4"	27'4"	29'4"
<b>Interior Width:</b>	99"	99"	99"	99"	99"	99"	99"	99"	99"	99"	99"
<b>Interior Height:</b>	78"	78"	78"	78"	78"	78"	78"	78"	78"	78"	78"
<b>Platform Height</b>	29"	29"	29"	29"	29"	29"	30"	30"	30"	30"	30"
<b>Spring Axle Quantity:</b>	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem
<b>Brakes:</b>	Electric Drum	Electric Drum	Electric Drum	Electric Drum	Electric Drum	Electric Drum	Electric Drum	Electric Drum	Electric Drum	Electric Drum	Electric Drum
<b>Radial Tires Size/Load Range:</b>	14"/C	14"/C	14"/C	14"/C	14"/C	14"/C	15"/D	15"/D	15"/D	15"/D	15"/D
<b>Hitch To Top of Ball:</b>	19"	19"	19"	19"	19"	19"	20"	20"	20"	20"	20"
<b>Hitch Weight: (% of Curb Weight):</b>	10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%
<b>Curb (lb.):</b>	3140	3320	3500	3680	3860	4040	3700	3880	4060	4240	4420
<b>GVWR (lb.):</b>	7000	7000	7000	7000	7000	7000	10000	10000	10000	10000	10000
<b>Avg. Payload (lb.):</b>	3860	3680	3500	3320	3140	2960	6300	6120	5940	5760	5580
<b>Rear Ramp Door (W x H):</b>	91" x 76"	91" x 76"	91" x 76"	91" x 76"	91" x 76"	91" x 76"	91" x 76"	91" x 76"	91" x 76"	91" x 76"	91" x 76"
<b>Front Ramp Door: (W x H):</b>	74" x 73"	74" x 73"	74" x 73"	74" x 73"	74" x 73"	74" x 73"	74" x 73"	74" x 73"	74" x 73"	74" x 73"	74" x 73"
<b>Side Entry Door (W x H):</b>	32" x 72"	32" x 72"	32" x 72"	32" x 72"	32" x 72"	32" x 72"	32" x 72"	32" x 72"	32" x 72"	32" x 72"	32" x 72"
<b>Tube Frame:</b>	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"
<b>12v End Connector:</b>	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way

Standard Features, Specifications & Dimensions subject to change without notice.



< Snap this with your smart phone for more information.



BY UNIVERSAL TRAILER

## 2-SLED MODELS

### STANDARD FEATURES — 7' WIDE MODELS

- 6' Long V-Front
- 68" Front Ramp Door with Spring Assist (Roadside)
- Ski Guide
- 75" Rear Ramp Door with Spring Assist
- Beavertail (18' & 20' models = 32", All other models = 48")
- 16" High Performance Engineered Ramp Extension
- 32" Pre-Framed Side Door with Flush Lock & Dead Bolt
- 12v Dome Light (1)
- 24" Starbright Stoneguard
- 3-Piece A-Frame
- 2 3/16" Ball Coupler Hitch (10,000 lb.)
- Top Wind Tongue Jack (2000 lb.) w/ Sand Pad
- Safety Chains & Breakaway Kit
- Entire Chassis Undercoated
- 24" Visqueen Corrosion Liner
- Aluminum Fenders
- One-Piece Aluminum Roof
- .030 Prefinished Aluminum Exterior Skin
- LED Tail Lights & Clearance Lights
- 24" OC Floor Crossmembers
- 16" OC Vertical Wall Hat Posts
- 16" OC Hat Section Roof Bows
- 3/4" High Performance Engineered Floor & Ramp Decking
- 1000 lb. Recessed Floor Mounted Tie-Downs (3)
- 3.6mm Lauan Interior Sidewall Liner
- 12" Kickplate (3/8" Plywood)
- 2-Year Limited Warranty



**MODEL FTS7202**

Shown with optional Snow Extreme Package, white vinyl sidewalls & ceiling liner

### SNOW EXTREME PACKAGE:

- 5000 lb. Drop Leg A-Frame Jack
- ABS Chrome Center Caps
- 6" ATP Exterior Sidewall Trim
- Chrome Rear Accents
- 12" ATP Kick Plate
- 24" V-Front Wall Scuff Guard
- 14" x 14" Access Door
- Traction Blocks (Front & Rear Ramps)
- Sidewall Vents
- Loading Lights (1 Front & 2 Rear)
- 12v Wall Switch for Loading Lights



MODEL	FTS7182	FTS7202	FTS7222	FTS7242	FTS7262	FTS7282	FTS7302
<b>Body Length:</b>	18'0"	20'0"	22'0"	24'0"	26'0"	28'0"	30'0"
<b>Body Width:</b>	7'0"	7'0"	7'0"	7'0"	7'0"	7'0"	7'0"
<b>Overall Length:</b>	21'0"	23'0"	25'0"	27'0"	29'0"	31'0"	33'0"
<b>Overall Width:</b>	102"	102"	102"	102"	102"	102"	102"
<b>Overall Height:</b>	100"	100"	100"	100"	100"	100"	100"
<b>Interior Length:</b>	17'3"	19'3"	21'3"	23'3"	25'3"	27'3"	29'3"
<b>Interior Width:</b>	80"	80"	80"	80"	80"	80"	80"
<b>Interior Height:</b>	78"	78"	78"	78"	78"	78"	78"
<b>Platform Height:</b>	20"	20"	20"	20"	20"	20"	20"
<b>Spring Axle Quantity:</b>	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem
<b>Brakes:</b>	Electric Drum	Electric Drum	Electric Drum	Electric Drum	Electric Drum	Electric Drum	Electric Drum
<b>Radial Tires Size/Load Range:</b>	15"/C	15"/C	15"/C	15"/C	15"/C	15"/C	15"/C
<b>Hitch To Top of Ball:</b>	19"	19"	19"	19"	19"	19"	19"
<b>Hitch Weight: (% of Curb Weight):</b>	10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%	10% - 15%
<b>Curb (lb.):</b>	2925	3145	3365	3585	3805	4025	4245
<b>GVWR (lb.):</b>	7000	7000	7000	7000	7000	7000	7000
<b>Avg. Payload (lb.):</b>	4075	3855	3635	3415	3195	2975	2755
<b>Rear Ramp Door (W x H):</b>	75" x 76"	75" x 76"	75" x 76"	75" x 76"	75" x 76"	75" x 76"	75" x 76"
<b>Front Ramp Door: (W x H):</b>	68" x 73"	68" x 73"	68" x 73"	68" x 73"	68" x 73"	68" x 73"	68" x 73"
<b>Side Entry Door (W x H):</b>	32" x 72"	32" x 72"	32" x 72"	32" x 72"	32" x 72"	32" x 72"	32" x 72"
<b>Tube Frame</b>	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"	2" x 6"
<b>12v End Connector</b>	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way