

H-CRPT-4 Commercial Restroom Plumbing Trainer

Purpose

The **Hampden H-CRPT-4** Commercial Restroom Plumbing Trainer demonstrates the setup and use of a toilet and urinal.

Components

- 3'- 8" X 8'- 0" platform dimensions – Aluminum frame and floor
- 16" center wall centered at 4' – 4' high with aluminum diamond plate face facing clear lexan panel face of wall
- Wall hung flushometer WC back to back on center wall
- Power outlet next to WC
- Urinal 0.25 gal flush – electronic (battery) flushometer back to back on center wall
- Water – cold and hot connections on right side of floor platform (for water hook up)
- 4 heavy duty wheels all 4 rotating, two locking

Fixtures

- WC – Kohler Kingston K-4325 1.28gpf Wall Hung Water Closet: JR Smith Fig. 0210Y No-Hub w/2" vent Vertical WC Carrier
- Kohler Exposed Wave Flushometer Valve – 1.28gpf K-10673
- Urinal - Sloan WEUS-1002.1201-0.25 Solis Optima Plus Systems Solar Powered High Efficiency Urinal Flushometer and Urinal

Piping

- Water supply – copper tube
- Waste – cast iron no hub

All Hampden units are available for operation at any voltage or frequency

Hampden[®]
ENGINEERING CORPORATION