



TILE BOND™ Roof Tile Adhesive

Certified Applicator or Instructor Application (Circle one)

Name: _____ Phone: (____) _____

Company Name : _____ Date: (____) _____

Address: _____ City: _____ State: _____

Email: _____ ZIP: _____

Question 1: How long does the container need to be shaken or rolled before using?

- A) Not required B) 15 minutes C) 15 to 20 seconds

Question 2: True or False? TILE BOND™ Roof Tile Adhesive is only approved by Florida Building Code.

- A) True. It does not have Miami-Dade approval
 B) False. TILE BOND™ Roof Tile Adhesive has FBC, Miami-Dade and Texas DOI and UL Evaluation Report

Question 3: True or False? On low/flat tiles, you should check at least one tile/square for proper adhesive coverage on the tile service.

- A) True B) False

Question 4: What is the optimal application temperature for TILE BOND™ Roof Tile Adhesive?

- A) 32°F B) Between 70°F to 90°F C) Between -10°F to 20°F

Question 5: For flat and medium profile tiles what is the appropriate bead size?

- A) 1×1×8 B) 2×1×4 C) full coverage

Question 6: How long do you have to set the tiles after TILE BOND™ Roof Tile Adhesive is dispensed?

- A) 4 minutes B) 10 minutes C) 15 minutes

Question 7: What is the shelf-life of TILE BOND™ Roof Tile Adhesive?

- A) 15 minutes B) 2 years C) 12 months

Question 8: What is a key component on the nozzle that keeps it from leaking?

- A) the small O-ring at base of nozzle B) there is none it is one piece C) a “do hickey” at the front tip of the nozzle

Question 9: How should a partially used TILE BOND™ kit be stored?

- A) Just throw it away, it can't be re-used B) Shut the valve and let the foam harden in the nozzle C) Remove the hose and clean it out

Question 10: How do you re-start a partially used kit?

- A) Open the valve and pull the trigger.
 B) Remove the nozzle, push the plug of cured foam out, and re-attach the nozzle making sure the o ring is still in place. Shake the can 15-20 seconds – open the valve a quarter to one full turn and continue.
 C) Throw the kit away, it can't be restarted.

A TILE BOND™ Roof Tile Adhesive Certification Card will be issued upon successful completion of the following requirements:

1. I have reviewed the following; Presentation, Operating Instructions, Anchor fastening Tables, Product Information Sheet, and Sell Sheet.
2. I have received hands-on training by a Certified TILE BOND™ Instructor and am familiar with the safe operation of the kit and appropriate adhesive placement.

I have completed the above requirements and agree to follow these for each TILE BOND™ roof tile application. I understand that my certification to install or my status as a TILE BOND™ Certified Applicator can be revoked at the discretion of Dow Building Solutions for not abiding by these requirements. If a municipal building official rejects a TILE BOND™ installation due to my negligence, this will be cause for a certification review and may be reason for my certification to be revoked. Recertification required every three years.

Instructor to; complete training, collect completed applications, and trainee photos, and send to:
 Program Administrator: FUSITEC@dow.com

Program Administrator will mail completed certification cards in 7-10 business days.
 Sales and Technical Information
 866-583 BLUE (2583)