

## Material Safety Data Sheet

### Section 1: PRODUCT AND COMPANY INFORMATION

**Product Name(s):** QPR®  
**Product Identifiers:** QPR®, Quality Pavement Repair®, QPR® High Performance Pavement Repair.  
**Manufacturer:** Lafarge North America Inc.  
 12950 Worldgate Drive, Suite 500  
 Herndon, VA 20170  
**Information Telephone Number:** 703-480-3600 (9am to 5pm EST)  
**Emergency Telephone Number:** 1-800-451-8346 (3E Hotline)  
**Product Use:** QPR® is a cold patch used for repairing asphalt pavement, driveways and parking lots.

### Section 2: COMPOSITION/INFORMATION ON INGREDIENTS

Component	Percent (By Weight)	CAS Number	OSHA PEL -TWA (mg/m <sup>3</sup> )	ACGIH TLV-TWA (mg/m <sup>3</sup> )	LD <sub>50</sub> (rat, oral)	LC <sub>50</sub>
Aggregate	90-95	Various	NA	NA	NA	NA
Asphalt Cement (as Fume)	< 5	8052-42-4	NA	0.5	NA	NA
#2 Fuel Oil (as Vapor & Aerosol)	< 2	68476-30-2	2000	100	12g/kg	NA
Crystalline Silica (as Quartz)	varies	14808-60-7	[(10) / (%SiO <sub>2</sub> +2)] (R); [(30) / (%SiO <sub>2</sub> +2)] (T)	0.05 (R)	NA	NA

### Section 3: HAZARD IDENTIFICATION

<b>WARNING</b>		
	<p>Toxic - Harmful by inhalation. (Contains crystalline silica)</p> <p>Irritant: Causes eye, skin and inhalation irritation</p> <p>Use proper engineering controls, work practices, and personal protective equipment.</p> <p>Read MSDS for details.</p>	 Eye Protection  Gloves

**Emergency Overview:** QPR® is a black colored granular solid that has a petroleum odor. Prolonged or repeated skin contact can cause drying of the skin which may produce irritation or dermatitis. If heated, hot product will cause severe thermal burns. When heated, this product will release toxic hydrogen sulfide (H<sub>2</sub>S) vapors.

**Potential Health Effects:**

**Eye Contact:** Airborne dust may cause immediate or delayed irritation or inflammation. Eye contact with amounts of QPR® can cause moderate eye irritation, redness, and itching. Eye exposures require immediate first aid to prevent damage to the eye. If heated, hot product will cause severe thermal burns.

**Skin Contact:** QPR® may cause dry skin, discomfort, irritation, and dermatitis. Repeated contact may cause skin irritation from abrasion and asphalt cement. If heated, hot product will cause severe thermal burns.

**Section 3: HAZARD IDENTIFICATION (continued)**

---

- Inhalation (acute):** When heated, QPR® may release irritating fumes or vapors such as smoke, carbon dioxide, carbon monoxide, unburned hydrocarbons. Hydrogen sulfide and other sulfur-containing gases can evolve from this product at elevated temperatures. Exposure to fumes or vapors may cause irritation of the nose and throat, and symptoms such as headache, dizziness, loss of coordination, and drowsiness. Cutting, crushing or grinding hardened asphalt will release dust. Breathing dust may cause nose, throat or lung irritation, including choking, depending on the degree of exposure.
- Inhalation (chronic):** Risk of injury depends on duration and level of exposure.
- Silicosis:** This product contains trace amounts of crystalline silica. Cutting, crushing or grinding hardened asphalt or other crystalline silica-bearing materials will release respirable crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a seriously disabling and fatal lung disease.
- Carcinogenicity:** QPR® is not listed as a carcinogen by IARC or NTP; however, QPR® contains trace amounts of crystalline silica that is classified by IARC and NTP as known human carcinogen.
- Ingestion:** Do not chew or ingest QPR®. Ingestion may result in nausea, vomiting, diarrhea and restlessness. Chewing asphalt has caused gastrointestinal effects. Stomach obstructions have been reported in individuals who have chewed and swallowed asphalt.
- Medical Conditions Aggravated by Exposure:** Individuals with preexisting skin conditions can be aggravated by exposure.

**Section 4: FIRST AID MEASURES**

---

- Eye Contact:** For contact with QPR®, rinse eyes thoroughly with water for at least 15 minutes. Seek medical attention. For contact with hot material, flush with large amounts of water for at least 15 minutes. Immediately call a physician.
- Skin Contact:** Wash with cool water and a pH neutral soap or a mild skin detergent. Do not use solvents or thinners to remove material from skin. Seek medical attention for rash, irritation, and dermatitis.
- For contact with hot material, immerse or flush skin with cold water for at least 15 minutes. Call a physician. Do not attempt to remove solidified material, since removal may cause further tissue injury.
- Inhalation:** Move person to fresh air. Seek medical attention for discomfort or if coughing or other symptoms do not subside.
- Ingestion:** Do not induce vomiting. If conscious, have person drink plenty of water. Seek medical attention or contact poison control center immediately.

---

**Section 5: FIREFIGHTING MEASURES**


---

<b>Flashpoint &amp; Method:</b>	NA	<b>Firefighting Equipment:</b>	A SCBA is recommended to limit exposures to combustion products when fighting any fire.
<b>General Hazard:</b>	Combustible solid. Avoid breathing fumes.	<b>Combustion Products:</b>	Toxic gases produced in fire, such as CO, CO <sub>2</sub> , H <sub>2</sub> S.
<b>Extinguishing Media:</b>	Use extinguishing media appropriate for surrounding fire.	<b>Auto-Ignition Temperature:</b>	NA
<b>Upper/Lower Flammable Limit:</b>	NA		

---

**Section 6: ACCIDENTAL RELEASE MEASURES**


---

**General:** Use a shovel to scrape up material and place material into suitable containers for recovery or disposal. Do not wash QPR® down sewage and drainage systems or into bodies of water (e.g. streams). Wear appropriate protective equipment as described in Section 8.

**Waste Disposal Method:** Dispose of QPR® according to Federal, State, Provincial and Local regulations.

---

**Section 7: HANDLING AND STORAGE**


---

**General:** Keep bagged QPR® sealed until used. Stack bagged material in a secure manner to prevent falling. Bagged QPR® is heavy and poses risks such as sprains and strains to the back, arms, shoulders and legs during lifting and mixing. Handle with care and use appropriate control measures. Do not stand on stockpiles of QPR®, they may be unstable.

**Usage:** QPR® should not be heated above 70°F (21°C) when utilizing a hot box. Cutting, crushing or grinding hardened asphalt or other crystalline silica-bearing materials will release respirable crystalline silica. Use all appropriate measures of dust control or suppression, and Personal Protective Equipment (PPE) described in Section 8 below.

Avoid contact with skin, eyes and clothing. Use additional precautions when handling hot material. Do not breathe fumes or vapor from heated material. Do not allow hot material to contact skin. Use all appropriate Personal Protective Equipment (PPE) described in Section 8 below.

**Storage:** Store in properly closed containers that are appropriately labeled and in a cool well-ventilated area. Do not expose to heat, open flames, strong oxidizers or other source of ignition.

**Storage Temperature:** Store away from heat, all ignition sources and open flames.

**Clothing:** Remove and launder clothing that is soiled with QPR®. Thoroughly wash hands and exposed skin after exposure to QPR®.

---

**Section 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION**


---

**Engineering Controls:** Under ordinary conditions, engineering controls are not required. Use local exhaust or general dilution ventilation when using at elevated temperatures or during activities that generate fumes, to maintain levels below exposure limits.

**Personal Protective Equipment (PPE):**

Respiratory Protection:	Under ordinary conditions no respiratory protection is required. Wear a NIOSH approved respirator that is properly fitted and is in good condition when exposed to dust or fumes above exposure limits.
-------------------------	---

---

**Section 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION (continued)**

---

- Eye Protection: Wear ANSI approved glasses, safety goggles, or face shield when handling QPR<sup>®</sup> to prevent contact with eyes.
- Skin Protection: Wear leather or cloth work gloves to prevent skin contact and insulated gloves when handling hot material. Thoroughly wash hands and other exposed skin after exposure to QPR<sup>®</sup>.
- Foot Protection: Wear ANSI approved hard-toed safety boots when handling QPR<sup>®</sup>.

---

**Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

---

<b>Physical State:</b>	Granular solid.	<b>Evaporation Rate:</b>	NA.
<b>Appearance:</b>	Black solid.	<b>pH (in water):</b>	NA.
<b>Odor:</b>	Slight petroleum odor.	<b>Boiling Point:</b>	563 - 1301° F (295 - 705° C).
<b>Vapor Pressure:</b>	NA.	<b>Freezing Point:</b>	NA.
<b>Vapor Density:</b>	NA.	<b>Viscosity:</b>	NA.
<b>Specific Gravity:</b>	2.6-2.8	<b>Solubility in Water:</b>	Insoluble

---

**Section 10: STABILITY AND REACTIVITY**

---

- Stability:** Stable. Avoid contact with incompatible materials, excessive heat, sources of ignition and open flame.
- Incompatibility:** QPR<sup>®</sup> is incompatible with strong acids or bases, and oxidizing agents such as nitrates, chlorates and peroxides.
- Hazardous Polymerization:** None.
- Hazardous Decomposition:** When heated may liberate hydrogen sulfide and various hydrocarbons.

---

**Section 11 and 12: TOXICOLOGICAL AND ECOLOGICAL INFORMATION**

---

For questions regarding toxicological and ecological information refer to contact information in Section 1.

---

**Section 13: DISPOSAL CONSIDERATIONS**

---

Dispose of waste and containers in compliance with applicable Federal, State, Provincial and Local regulations.

---

**Section 14: TRANSPORT INFORMATION**

---

This product is not classified as a Hazardous Material under U.S. DOT or Canadian TDG regulations.

---

**Section 15: REGULATORY INFORMATION**

---

- OSHA/MSHA Hazard Communication:** This product is considered by OSHA/MSHA to be a hazardous chemical and should be included in the employer's hazard communication program.
- CERCLA/SUPERFUND:** This product is not listed as a CERCLA hazardous substance.
- EPCRA SARA Title III:** This product has been reviewed according to the EPA Hazard Categories promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 and is considered to be an acute health hazard (irritation).
- EPRCA SARA Section 313:** This product contains none of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

**Section 15: REGULATORY INFORMATION (continued)**

- RCRA:** If discarded in its purchased form, this product would not be a hazardous waste either by listing or characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste.
- TSCA:** This product and/or its components are listed on the Toxic Substances Control Act (TSCA) inventory.
- California Proposition 65:** Crystalline silica (airborne particulates of respirable size) is a substance known by the State of California to cause cancer.
- WHMIS/DSL:** Products containing crystalline silica are classified as D2A and are subject to WHMIS requirements.



**Section 16: OTHER INFORMATION**

**Abbreviations:**

>	Greater than	NA	Not Applicable
<	Less than	NFPA	National Fire Protection Association
ACGIH	American Conference of Governmental Industrial Hygienists	NIOSH	National Institute for Occupational Safety and Health
CAS No	Chemical Abstract Service number		
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act	NTP	National Toxicology Program
		OSHA	Occupational Safety and Health Administration
CFR	Code for Federal Regulations	PEL	Permissible Exposure Limit
CL	Ceiling Limit	pH	Negative log of hydrogen ion
DOT	U.S. Department of Transportation	PPE	Personal Protective Equipment
EST	Eastern Standard Time	R	Respirable Particulate
HEPA	High-Efficiency Particulate Air	RCRA	Resource Conservation and Recovery Act
HMIS	Hazardous Materials Identification System	SARA	Superfund Amendments and Reauthorization Act
IARC	International Agency for Research on Cancer	T	Total Particulate
		TDG	Transportation of Dangerous Goods
LC <sub>50</sub>	Lethal Concentration	TLV	Threshold Limit Value
LD <sub>50</sub>	Lethal Dose	TWA	Time Weighted Average (8 hour)
mg/m <sup>3</sup>	Milligrams per cubic meter	WHMIS	Workplace Hazardous Materials Information System
MSHA	Mine Safety and Health Administration		

This MSDS (Sections 1-16) was revised on April 20, 2005.

An electronic version of this MSDS is available at: [www.lafarge-na.com](http://www.lafarge-na.com) under the Products section.

Lafarge North America Inc. (LNA) believes the information contained herein is accurate; however, LNA makes no guarantees with respect to such accuracy and assumes no liability in connection with the use of the information contained herein which is not intended to be and should not be construed as legal advice or as insuring compliance with any federal, state or local laws or regulations. Any party using this product should review all such laws, rules, or regulations prior to use, including but not limited to US and Canada Federal, Provincial and State regulations.

NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OTHERWISE.