

16 Inch (Reverse Rim)		Low Disk								Hi Disk									
		4-100								4-100									
Diameter	Width	Offset Option																	
16	5.5J	45	42	39						36	34	32	29						
16	6.0J	45	42	39	36	33				43	37	31	26	23					
16	6.5J	45	42	39	36	33	30			44	38	32	26	23	20				
16	7.0J	45	42	39	36	33	30	27	24	44	38	32	26	20	14				
16	8.0J	44	38	32	26	20	14	11		45	39	33	27	21	15	9	3	1	

\* 16" 815F offset is preset. Range option is not available.

! Not TPMS Compatible (Adapter is required for TPMS support).

17 Inch (Reverse Rim)		Low Disk										Hi Disk																			
		4-100										4-100																			
Diameter	Width	Offset Option																													
17	5.5J	45	42	39																36	34	32	29								
17	6.0J	45	42	39	36	33														43	37	31	26	23							
17	6.5J	45	42	39	36	33	30													44	38	32	26	23	20						
17	7.0J	45	42	39	36	33	30	27	24											44	38	32	26	20	14						
17	7.5J	45	42	39	36	33	30	27	24	21	18									44	38	32	26	20	14	8					
17	8.0J	44	38	32	26	20	14	11												45	39	33	27	21	15	9	3	1			
17	8.5J	44	38	32	26	20	14	8	5											45	39	33	27	21	15	9	2	-5			
17	9.0J	44	38	32	26	20	14	8	2	-1										45	39	33	27	21	13	9	3	-4	-11		

\* 16" 815F offset is preset. Range option is not available.

! Not TPMS Compatible (Adapter is required for TPMS support).

18 Inch (Reverse Rim)		Super Low Disk				Low Disk			
		5-114.3				5-100, 5-112, 5-114.3			
Diameter	Width	Offset Range							
18	7.5J	49 ~ 31				42 ~ 24			
18	8.0J	56 ~ 26				49 ~ 19			
18	8.5J	56 ~ 19				49 ~ 12			
18	9.0J	56 ~ 19				49 ~ 12			
18	9.5J	56 ~ 19				49 ~ 12			
18	10.0J	56 ~ 25				49 ~ 18			

! Not TPMS Compatible (Adapter is required for TPMS support).

19 Inch (Normal Rim)		Super Low Disk				Low Disk			
		5-114.3				5-100, 5-112, 5-114.3			
Diameter	Width	Offset Range							
19	8.0J	33 ~ 21				26 ~ 14			
19	8.5J	39 ~ 12				32 ~ 7			
19	9.0J	45 ~ 20				38 ~ 13			
19	9.5J	51 ~ 15				45 ~ 8			
19	10.0J	51 ~ 21				45 ~ 14			
19	10.5J	51 ~ 20				45 ~ 13			
19	11.0J	51 ~ 21				45 ~ 14			

! Not TPMS Compatible (Adapter is required for TPMS support).

19 Inch (Reverse Rim)		Super Low Disk				Low Disk				Hi Disk			
		5-114.3				5-100, 5-112, 5-114.3, 5-120				5-114.3			
Diameter	Width	Offset Range											
19	7.5J	49 ~ 39				42 ~ 32				27 ~ 17			
19	8.0J	56 ~ 34				49 ~ 27				34 ~ 12			
19	8.5J	56 ~ 27				49 ~ 20				40 ~ 5			
19	9.0J	56 ~ 19				49 ~ 12				46 ~ -3			
19	9.5J	56 ~ 19				49 ~ 12				46 ~ -3			
19	10.0J	56 ~ 25				49 ~ 18				46 ~ 3			
19	10.5J	56 ~ 21				49 ~ 14				46 ~ -1			

20 Inch (Normal Rim)		Super Low Disk	Low Disk	Hi Disk
		5-114.3	5-100, 5-112, 5-114.3, 5-120	5-114.3
Diameter	Width	Offset Range		
20	8.5J	37 ~ 21	30 ~ 14	15 ~ -1
20	9.0J	43 ~ 14	36 ~ 7	21 ~ -8
20	9.5J	50 ~ 9	43 ~ 2	28 ~ -14
20	10.0J	50 ~ 2	49 ~ -5	34 ~ -20

! Not TPMS Compatible (Adapter is required for TPMS support).

20 Inch (Reverse Rim)		Super Low Disk	Low Disk	Hi Disk
		5-114.3	5-112, 5-114.3, 5-120	5-112, 5-114.3, 5-120
Diameter	Width	Offset Range		
20	8.0J	56 ~ 34	49 ~ 27	34 ~ 12
20	8.5J	56 ~ 27	49 ~ 20	40 ~ 5
20	9.0J	56 ~ 19	49 ~ 12	46 ~ -3
20	9.5J	56 ~ 19	49 ~ 12	46 ~ -3
20	10.0J	56 ~ 25	49 ~ 18	46 ~ 3
20	10.5J	56 ~ 21	49 ~ 14	46 ~ -1

21 Inch (Normal Rim)		Super Low Disk	Low Disk	Hi Disk
		5-114.3	5-112, 5-114.3, 5-120	5-112, 5-114.3, 5-120
Diameter	Width	Offset Range		
21	9.0J	46 ~ 22	39 ~ 15	24 ~ -7
21	9.5J	46 ~ 16	46 ~ 9	31 ~ -7
21	10.0J	46 ~ 16	46 ~ 9	37 ~ -7
21	10.5J	46 ~ 22	46 ~ 15	43 ~ -1

! Not TPMS Compatible (Adapter is required for TPMS support).

#### COLOR OPTION:

- 16"/17" - Bright Silver / Glossy Black
- 18" - Bright Silver / Glossy Black
- 19" - Bright Silver / Glossy Black
- 20" Normal Rim - Bright Silver / Glossy Black
- 20" Reverse and 21" - SBC / Bright Silver / Glossy Black

#### RIM COLOR OPTION:

- Standard finish is Anodized Polished
- With additional cost. Gloss Black (Painted) is available



#### RIVET COLOR OPTION:

- Standard rivet color is Chrome.
- With additional cost. Classical (Black) rivets is available.



\* Hub bore size: 5-100 = 65mm / 5-112 = 66.5mm / 5-114.3 = 73mm / 5x120 = 72.5mm

\* You must specify that you would like to have TPMS support on your 19, 20 or 21 inch 815F upon ordering.

If it is not specified, we will build the wheel without TPMS support.

\* If the wheel cannot be made TPMS compatible from the Weds factory. Optional TPMS adapter can be used and is sold separately

\* Unlisted vehicle bolt pattern might be available. Please contact us for details.

\* Any questions regarding disk type. Please contact us for support.

\* All specifications are subject to change without prior notice.