

MATERIAL SAFETY DATA SHEET Page 1 of 3

Product Name: FOOTPRINT RECYCLED INT/EXT LATEX PAINTS-All Colors HMIS CODES: H F R P
Product Code: RRRP 000A
THIS PRODUCT CONSISTS PRIMARILY OF POST-CONSUMER RECYCLABLE LATEX PAINTS.

----- SECTION I – MANUFACTURER IDENTIFICATION -----

MANUFACTURER’S Name: OLD WESTERN PAINT CO., INC.
ADDRESS: 2001 WEST BARBERRY PLACE
DENVER, CO 80204
EMERGENCY PHONE: CHEM-TEL 800-255-3924 DATE PRINTED: 01/01/15
INFORMATION PHONE: 303-825-5147 NAME OF PREPARER: PD

----- SECTION II HAZARDOUS INGREDIENTS/SARA III INFORMATION -----

REPORTABLE COMPONENTS	Cas Number	ACGIH-TLV		OSHA-PEL		Est. Weight Percent
		8-Hour TWA	8-Hour TWA	8-Hour TWA	8-Hour TWA	
limestone	1317-65-3	10 mg/m3	5 mg/m3	5 mg/m3	0-10	0-10
clay	1332-58-7	2 mg/m3	5 mg/m3	5 mg/m3	0-10	0-10
titanium dioxide	13463-67-7	10 mg/m3	10 mg/m3	10 mg/m3	0-20	0-20
quartz	14808-60-7	.05 mg/m3	0.1 mg/m3	0.1 mg/m3	0-20	0-20
aluminum hydroxide	21645-51-2	10 mg/m3	5 mg/m3	5 mg/m3	0-10	0-10
vinyl acrylic latex	proprietary	not est.	not est.	not est.	0-30	0-30
acrylic resin	Sup. Conf.	not est.	not est.	not est.	0-30	0-30
feldspar-type minerals	37244-96-5	5 mg/m3	not est.	not est.	0-20	0-20
amorphous silica	7631-96-9	10 mg/m3	6 mg/m3	6 mg/m3	0-5	0-5

No known Toxic chemical (s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.

----- SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS -----

BOILING RANGE: N/A SPECIFIC GRAVITY (H2O=1): 1.32
VAPOR DENSITY: Heavier than air EVAPORATION RATE: Slower than ether
SOLUBILITY IN WATER: Dispersible
APPEARANCE AND ODOR: Colors with slight odor
COATING VOC: >150g/L

----- SECTION IV – FIRE AND EXPOSION HAZARD DATA -----

FLASH POINT: NA METHOD USED: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME – N/A LOWER: N/A UPPER:N/A
EXTINGUISHING MEDIA: Foam, CO2, Dry Chemical, Water Fog

SPECIAL FIREFIGHTING PROCEDURES
Normal fire fighting procedures may be used.
UNUSUAL FIRE AND EXPOSION HAZARDS
No special hazards known.

----- SECTION V – REACTIVITY DATA -----

STABILITY: STABLE
CONDITIONS TO AVOID:
Avoid poor ventilation. Store in dry area. Avoid freezing.

INCOMPATIBILITY (MATERIALS TO AVOID): None known.
HAZARDOUS DECOMPOSITION OR BY PRODUCTS: N/A
HAZARDOUS POLYMERIZATION: N/A

----- SECTION VI – HEALTH HAZARD DATA -----

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

None known.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Direct contact with eyes can cause irritation. Prolonged or repeated contact of undiluted product with skin may cause irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

May cause irritation.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPSURE

May cause irritation and nausea.

CARCINOGENICITY: Not carcinogenic. NTP CARCINOGEN: No IARC MONOGRAPHS: No
OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

If skin or eye irritation persists, consult physician.

EMERGENCY AND FIRST AID PROCEDURES

Remove patient to fresh air. Eye contact; flush eyes with clean water for 15 minutes. Skin contact-remove saturated clothing, and wash skin thoroughly. If symptoms persist, seek medical attention.

----- SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE -----

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike, absorb and dispose. Wash area with water, not washing into public sewers. Remove saturated clothing and wash affected skin areas with soap and water.

WASTE DISPOSAL METHOD

Place waste and any unusable material in an appropriate container and dispose of in accordance with local, State and Federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep out of reach of children. Do not take internally. Keep from freezing. Use adequate ventilation.

TRANSPORTATION: Not regulated as a DOT hazardous material. Do not transfer product to any other unlabeled container. Store closed container at 40-80°F.

OTHER PRECAUTIONS

Do not take internally. Avoid prolonged contact with skin, breathing spray mist, or heated vapors.

----- SECTION VIII – CONTROL MEASURES -----

RESPIRATORY PROTECTION

Should be worn to avoid breathing spray mist or heated vapors.

VENTILATION

Local exhaust and general ventilation recommended to rid mist or vapors.

PROTECTIVE GLOVES

Required for prolonged or repeated contact. Use plastic or rubber gloves.

EYE PROTECTION

Use chemical safety glasses or goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Wear protective clothing to avoid prolonged contact with skin.

WORK/HYGENIC PRACTICES

Contaminated clothing should be removed. Avoid prolonged contact with skin and breathing heated vapors. Remove and wash contaminated clothing before reuse. Wash hands before eating or using the wash room.

----- SECTION IX – DISCLAIMER -----

The information contained herein is based on data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of the product described herein.

KEEP OUT OF REACH OF CHILDREN

Please read container's complete label before using.