



Key Features

- Operates in extreme environments
- Simple installation - between wall studs
- Advanced electronic control system
- Liquid bottle probe
- Humidity control
- Energy saving mode
- Fully ductable
- 55°F temperature differential



Features

The Extreme Series offers 3-speed fans to truly put full control in your hands. With the system set in the Low setting, you can maintain a 55°F cellar at an ultra quiet 51 decibels for the 5000ti and 57 decibels for the 8000ti. This fully featured line also includes WhisperKOOL's most advanced controller to keep all of the cellar vitals in check. Utilizing a series of monitoring probes inside the unit, the controller is able to ensure efficient high performance and long cooling unit life. Acceptable for mounting through exterior walls and can operate in a 110°F exhaust environments. Maintain 55°F and 50-70% relative humidity in a cellars up to 1000 cu. Ft. (5000ti) or 2000 cu. Ft. (8000ti) in size.

Specifications

Model	5000ti	8000ti
Cellar Size	1000 cu. ft.	2000 cu. ft.
dBa	Low: 52 Med: 58 High: 66	Low: 57 Med: 59 High: 60
Dimensions	14.25"W x 15.75"H x 28"D	14.25"W x 22.5"H x 27.5"D
Weight	96lbs	110lbs
AMPS (starting/running)	32/9	36/10
Installation	Through-the-Wall, partially ducted, fully ducted	
Thermostat	Digital Control Display	
Temp. Delta	55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)	
Outside Venting	Can be done if the outside temperature does not exceed 110°F, the external grille cover is highly recommended.	
Ducting Options	Unit can be fully ducted.	
Warranty	2 year parts and labor / 5 year compressor	
Compliance	ETL Listed	

Optional Accessories

Ducting Plenum, Exterior Grille