



**OLD WESTERN PAINT CO., INC.**  
2001 West Barberry Place  
Denver, Colorado 80204

PHONE: 303-825-5147  
FAX: 303-825-2437  
TOLL FREE 1-888-POLY VAR  
(765-9827)  
WWW.oldwesternpaint.com  
WWW.polyvar.com

## PRODUCT INFORMATION

### EXTERIOR LATEX HOUSE PAINT **1082 408 BLACK**

**TYPE:** Modified Vinyl Acrylic Resin

**DESCRIPTION:** *EXTERIOR LATEX HOUSE PAINT* is an excellent breather-type paint with a low sheen that helps hide surface defects. May be used on exterior masonry surfaces or any primed wood or metal. It is extremely easy to apply and dries in approximately two hours to a durable blister resistant film.

**CLEAN UP:** Clean water

**APPLICATION:**

Brush, Roller, Spray- Surface should be clean and free from dust, dirt, grease and peeling paint. Glossy surfaces must be dulled by sanding or applying liquid sanding solution. All water stains should be primed with stain killer before painting. All nails should be caulked or primed with exterior oil base primer before painting. New wood, redwood, cedar and peeling surfaces should be primed with proper stain killing primer before applying finish coat. Do not apply below 50<sup>0</sup> F or above 95<sup>0</sup> F. Must be applied to dry surface. KEEP FROM FREEZING, store at room temperature.

**SPREADING RATE:** 350-450 square feet per gallon, subject to surface porosity, texture and application method.

**DRYING TIME:** Dries in 2 hours (dust free), recoat 4 hours. Drying time may be affected by excessive humidity, low temperature, failure of air movement and thickness of finish.

**ANALYSIS:**

<b>PIGMENT</b>	<b>29.57%</b>
<b>VEHICLE</b>	<b>70.43%</b>
<b>TOTAL</b>	<b>100.00%</b>

<b>PIGMENT</b>	
Colored Oxide Pigment	25.47%
Selected Extenders	74.53%
<b>Total</b>	<b>100.00%</b>

<b>VEHICLE</b>	
Modified Vinyl Acrylic Resin	37.49%
Volatile, Surfactants	62.51%
<b>Total</b>	<b>100.00%</b>

**VOC content does not exceed 250 grams/liter,  
2.1 lbs./gallon**

**NOTE:** If used as directed, including proper application and surface preparation in accordance with label directions, this product is warranted to be free from defect when used for its intended application for a period of one year from the date of purchase. This limited warranty does not apply if the product is mixed with any other ingredient. Buyer assumes all risks of handling. Buyer's sole and exclusive remedy with respect to any defective product is replacement of product or refund of the purchase price, at Manufacturer's sole option and only after receipt of proof of purchase. THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND DESIGN. IN NO EVENT SHALL MANUFACTURER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LABOR COST. Some states do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

**-PAGE 4.10-**

*"Quality where it Counts"*