



Touch Probe TC51



# TC51 | Touch Probe | Tactile workpiece measuring system with infrared transmission

## Unique – high dynanmic touch probe for fast pulling measurements

- Mass production
- · Measuring tasks requiring superior precision
- Extremely fast measurements
- Thermal compensation of the machine tool
- · Pulling measurement of grooves, recesses and outside width
- · Spindle orientation is required

#### Your benefit:

- Measuring speed up to 5 m/min
- Highest acceleration
- Superior precision
- No-wear, optoelectronic measuring mechanism
- Highest process reliability
- Use of two measuring systems with one IR receiver
- Extended battery life
- · Precise measurement even with coolant
- Proven and robust design




### **DUO-Mode**

Sequential use of two measuring systems with one infrared receiver.


## Technical data

Protection class	IP68
Approach directions	XY*, ±Z
Measuring force in XY   Z	1,5 N**   4 N
Max. deflection XY $\mid$ +Z $/$ -Z	15°*   3 mm / 7 mm
Trigger point XY	0,5 mm / 0,8 mm / 1,2 mm / 1,5 mm ***
Trigger point Z	0,8 mm
Max. acceleration	100 m/s <sup>2</sup>
Repeatability	0,3 μm 2σ
Max. probing speed	5 m/min
Mass	920 g
Signal transmission   Range	Infrared   ±60° in Z, 360° in X/Y
Battery (2 pieces)	Saft Lithium LS 14500 (AA, 3,6 V) 2600 mAh
Tool holder	BTH 50 (HSK, SK, BT, VDI,)
Storage/Operating temperature	-20 °C +70 °C   +5 °C +50 °C






TC51 – extremely fast and precise



TC51 – ideal for mass production



Modern and precise measuring mechanism with optoelectronic signal generation



Blum worldwide Service & Support

More than 40 subsidiaries and service offices.

www.blum-novotest.com

#### Blum-Novotest Ltd.

33 Townfields Lichfield, Staffordshire WS13 8AA, United Kingdom

Phone: +44 1543 257111 Fax: +44 1543 251746 E-Mail: info@blum-novotest.co.uk Blum LMT, Inc.

4144 Olympic Boulevard Erlanger, KY 41018 USA

Phone: +1 (859) 344 6789 Fax: +1 (859) 344 6799 E-Mail: solutions@blumlmt.com

<sup>\*\*\*</sup> Stylus L= 50 mm / 100 mm / 150 mm / 200 mm