



Specifications*

Energy Per Blow, Adjustable

Pump Setting 1	50 %	20.5 kNm	15,000 ft.lbs.
Pump Setting 2	66 %	27.7 kNm	19,690 ft.lbs.
Pump Setting 3	83 %	33.6 kNm	24,760 ft.lbs.
Pump Setting 4	100 %	40.5 kNm	29,840 ft.lbs.

Frequency	37 - 52 blows/min	
Related Piston Stroke	3.2 - 1.6 m	10.5 - 5.3 ft.

Maximum batter w/o upper cyl. ext.	1:2	-
with upper cylinder extension	n/a	-
Fuel consumption at full load	4.5 L/hr.	1.20 gal./hr.
Oil consumption	0.5 L/hr.	0.13 gal./hr.

Approx. Weights

Hammer	2600 kg	5,730 lbs.
Piston	1280 kg	2,820 lbs.
Hammer with standard guiding	3220 kg	7,100 lbs.

Capacities

Fuel Tank	24 L	6.3 gal.
Oil Tank	6.5 L	1.7 gal.

Dimensions

A	- Length	5580 mm	18.3 ft.
LH	- Length, standard	5850 mm	19.2 ft.
B	- Center to trip	356 mm	14.0 in.
B1	- Center to trip with cylinder	508 mm	20.0 in.
C	- Center to pump guard	381 mm	15.0 in.
D	- Width of hammer	482 mm	19.0 in.
D1	- Width of trip	622 mm	24.5 in.
W	- Minimum lead width	534 mm	21.0 in.

*Technical data are subject to change without prior notice
 Operating energy based on piston stroke - values are approximate.
 Hydraulic start optional.