

GRADE 2 SINGLE CYLINDER DEADBOLT WITH TURN

BHMA
ANSI A156.5
GRADE 2



D241



A12639 001 00



C646A626

- Accepts all small format interchangeable style cores (SFIC) and conventional cylinders
- Deadbolt thrown or retracted by key or by turn
- Bolt automatically deadlocks when fully thrown, 1" projection
- Door thickness: 1-3/8" to 1-3/4"
- Backset: 2-3/8" - 2-3/4"
- 1-1/8" x 2-1/4" faceplate
- Non-handed
- ANSI/BHMA standard: A156.5, 2001, Grade 2
- UL listed, A label, 3 hours

MFG #	DESCRIPTION	EZ #
D241BD626	Single Cylinder I/C Deadbolt Less Core	091331
A12639 001 00	6 Pin Spring Cover For I/C Core 100/pk	003753
C646A626	I/C A Keyway 6PIN Uncombined	035507

THUMBTURN INDICATOR LOCK



D271



A30155 000 00

- Deadbolt lock used to provide privacy
- When locked from inside the room, deadbolt locks the door, and a visual "In Use" sign appears
- When bolt is retracted, message reads "Vacant"
- Emergency key opens lock from the outside when required
- Finish: Satin chrome

MFG #	DESCRIPTION	EZ #
D271 626	Thumbturn Indicator Lock	035400
A30155 000 00	Emergency Release Tool	062590

