

2024

BUMPER SWAP

MINI VAN/MINI TRUCKS/SUV

4/6 cylinder only

GENERAL RULES:

1. Must be registered before inspection.
2. Anything deemed excessive will be at official's discretion.
3. If the rules do not say you can do it, don't.

BODY

Doors:

1. May be fastened shut 1 of 2 ways
 - a. You may weld (3) 4x4 tabs per vertical seam only
 - b. You may use 9 locations of 9 wire per door.
 - c. Drivers' door may be welded solid.

Tailgates/Hatches:

2. You may fasten the tailgate in 1 of 2 ways.
 - a. You may weld using (4) total 4x4 plates.
 - b. You may 9 wire in 6 locations.
3. Hatches/tail gates may be removed but you lose all 9 wire spots.

Hoods:

4. Hoods may be fastened shut in 1 of 2 ways
 - a. You may use (4) 3/8 bolts to secure the hood down.
 - i. This be accomplished going sheet metal to sheet metal or but using 2-inch angle iron no longer than 3 inches.
 - b. You may 9 wire in 6 locations.

Quarters:

5. Quarters may be creased behind the rear doors.
6. Bedsides must remain upright.

Body:

7. No extra body mounts permitted.

Windshield:

8. Windshield must have 1 form of protection.

- a. No ratchet straps.
- b. You may use 9 wire
- c. You may weld 3-inch strapping.
- d. You must have a window bar!

Rear Window:

9. No rear window bar or wire permitted.

DRIVETRAIN

Engine/Tranny:

10. Must remain stock

- a. (make to make)

11. You may not reinforce the vehicle in anyway.

12. Motor mounts must remain factory.

13. All other components must remain stock unless otherwise stated.

- b. Simplified harnesses are permitted.

14. No aftermarket coolers permitted.

15. Radiators may be looped or ran in factory location.

- c. No water boxes.

SUSPENSION

16. All components must remain stock unless otherwise stated.

17. Suspension must bounce but you are permitted spring risers.

18. No altering or reinforcing permitted.

CAGE/TANK PROTECTOR/FUEL

Cage:

19. You are permitted a 4-point cage.

- a. May be no larger than 4x4 tubing.
- b. Must remain 6 inches off any part of the floor.

- c. Gussets are permitted but must be internal of the 4-point cage.
- d. Door bars may not exceed 10 inches past the b-pillar.
 - i. Extended cab/4 door picks up follow same rule.
 - ii. Single cab trucks may not exceed outside of the cab.

Tank Protector:

- 20. You are permitted a 24"x24" tank protector mounted off of the seat bar or may be mounted directly to the floor.
- 21. Tanks may also be left underneath if tank is in front of the rear axle.

BUMPERS/FRAMES

- 22. Any factory car bumper may be used.
 - a. You may use smw bumper as a replacement.
 - b. 4x4x1/4 tube or 2x6x1/4 tube may be used but ends must remain open.
 - c. No homemade points permitted.
- 23. You may hardnose bumpers to frame using a 6x6 mounting plate flush to cap the end.
- 24. You may also mount the bumper 1 of 2 ways.
 - d. Use a 4"x6" plate on the outer most edge of the frame (tire side)
 - i. Must be welded to back of bumper.
 - e. Use the first 3" all the way around the frame. may be no further back than 3 inches from the back side of the bumper.
- 25. You are permitted (4) 4x4 fix it plates (fresh/pre-ran)

TIRES/WHEELS

- 26. Any rubber tire of choice.
- 27. No bead lips
- 28. Tires may be doubled/tubed
- 29. Rubber sidewall protectors permitted.