



New Massey Ferguson® 2635 Utility Tractor

Turbocharge your routine.



MODEL	2635
Engine	
SAE Gross Engine HP @ rated engine rpm: HP (kW)	74 (55.2) @ 2,200
PTO HP @ rated engine rpm (LIVE PTO): HP (kW)	62 (46.2) @ 2,200
PTO HP @ rated engine rpm (Independent PTO): HP (kW)	60 (44.7) @ 2,200
SIMPSON® engine model	TSJ436E
Cylinders and aspiration	4-Turbo
Total displacement: in. (liters)	220 (3.6)
Cold starting aid:	Glow Plug
Fuel tank capacity: US gal. (liters)	17.7 (65)
Clutch	
Type with live PTO	Dry Dual Disc
Diameter traction clutch: in. (mm)	12 (305)
Diameter of PTO clutch: in. (mm)	10 (254)
Type with independent PTO	Dry Single Disc
Diameter traction clutch: in. (mm)	12 (305)
Hydraulic engaged independent PTO clutch:	Wet Multi Disc
Transmission	
Type standard	8F x 2R
Type optional	8F x 8R Shuttle
Brakes & Final Drives	
Final drives with 8x2 transmission	Outboard Planetary
Final drives with 8x8 shuttle transmission	Outboard Planetary
Brakes	Inboard Wet Multi Disc
Differential lock	Foot Operated
PTO Type	
Type standard (8x2 transmission only)	Live (Dual Stage Dry Clutch)
Type optional	Independent (Electro-hydraulically engaged Multi-Disc Wet Clutch)
PTO speed @ engine RPM (6 spline shaft)	540 @ 1,790 ERPM

MODEL	2635
Hydraulics	
System type	Open Center & Modified Closed Center
Pump type	Gear & Scotch Yoke
Total flow: gpm (lpm) (steering + aux + 3-point pump)	22.8 (86)
Steering pump flow: gpm (lpm)	6.9 (26)
Auxiliary pump flow: gpm (lpm)	11.2 (42)
3-point hitch pump: gpm (lpm)	4.7 (18)
Remote valves standard:	None
Remote valves optional:	1 or 2 Rear Valves
Three-Point Hitch	
ASAE category	Category I & II Cross Drilled Ball Ends
Extendable lower links	Optional
Stabilizers	Chain Type
Lift capacity @ hitch point - horizontal position: lbs. (kg)	4,520 (2,050)
Electrical	
Battery CCA	N/A
Alternator amperage	45
Trailer outlet	Standard
Horn	Standard
Weight & Dimensions***	
Rear tire used for measurement:	16.9x28
(A) Wheelbase: in. (mm) 2/4WD	81 (2,050) / 81 (2,066)
(B) Overall length: in. (mm) 2/4WD	138 (3,510) / 139 (3,526)
(C) Min. overall width: in. (mm)	73 (1,854)
(D) Min. tread setting: in. (mm)	56 (1,420)
(E) Height top of ROPS: in. (mm)	95 (2,395)
(F) Ground clearance @ drawbar: in. (mm)	13.5 (350)
2WD platform approx. shipping weight: lbs. (kg)	5357 (2,430)
4WD platform approx. shipping weight: lbs. (kg)	5798 (2,630)

*** See the full 2600 Series brochure for illustrated views of above dimensions.



An economical 8x2 constant mesh transmission with live PTO provides a simple and reliable powertrain to handle daily chores on the farm. The optional 8x8 SynchroShuttle transmission with independent PTO gives new meaning to comfort and convenience by allowing the tractor to shift gears on the go and change direction without having to stop completely.



All 2600 Series models can be equipped with a front loader to improve performance on the job site. Several models are available, from economical to deluxe, to meet the job's requirements.



Most daily service items, such as engine oil check, can be done without opening the hood. For other maintenance, the gas assisted, single-piece steel hood opens widely for easy access.