

DISPLAY

AVAILABLE COLORS



White



Silver



Black



SHOWN IN BLACK
(POLE STAND NOT INCLUDED)

KEY FEATURES

- 47" Pro Series True Outdoor All-Weather LED Television for permanent outdoor installation
- Ultra-Bright (700 NIT) 47" full HD, 1080p LED screen for improved outdoor viewing
- Direct Sunlight-Readable
- High temperature Enhanced Solar Tolerance (EST) technology prevents isotropic backout
- Exterior designed to protect internal components from rain, snow, dust, insects, humidity, and salt air.
- Powder-coated rust-proof aluminum exterior for strength and durability.
- Multi-fan airflow system keeps the unit cool and dry in temperatures up to 122 degrees F.
- Ability to operate in cold weather (-40 degrees F).
- Ambient Light Sensor provides automatic dimming of backlight for night time viewing.
- Front tempered anti-reflective glass window provides added protection to LED screen, and safeguards against vandalism & abuse.
- RS232 serial control with discrete on, off, and input control.
- Rear IR receiver (located in the cable-entry compartment).
- Innovative water-tight Cable Entry System seals out moisture and allows for easy hook-ups.
- Optional media player compartment door to house a digital media player, Pro:Idiom set top box, or fan-less PC's.
- Weatherproof detachable 20W speaker module (included), remote control, and control buttons.
- Side control button lock-out prevents unauthorized users from changing the programming.
- Includes warranty and manual
- Landscape installation only. (For Portrait installation see DS-4717P)

<p>SCREEN</p>	<p>SCREEN 47-inch Diagonal Color Active Matrix TFT LED</p> <p>RESOLUTION 1920 x 1080 Full-HD 1080p</p> <p>ASPECT RATIO 16:9</p> <p>CONTRAST RATIO 1300:1</p> <p>FRAME RATE 120 Hz</p> <p>VIEWING ANGLE 178° x 178°</p> <p>RESPONSE TIME 12 milliseconds</p> <p>TV FORMATS 1080p, 1080i, 720p, 720i, 480p, 480i</p>
<p>CONNECTIONS</p>	<p>RF Antenna/CATV (ATSC/QAM/NTSC) x1</p> <p>HDMI HDMI™ Input x2</p> <p>VIDEO COMPOSITE S-Video x1 and Composite Video x1, L/R Audio Inputs x1</p> <p>VIDEO COMPONENT YPbPr plus Stereo Audio x2</p> <p>PC 15-pin D-sub VGA plus Stereo Audio</p> <p>CONTROL SET RS232 Serial, Discrete IR Control, Concealed IR Window</p> <p>AUDIO OUT Digital SPDIF Audio(fixed) Analog 1/8" headphone jack (variable)</p> <p>SPEAKERS 20 WATT detachable speaker module(included)</p> <p>INPUT POWER 100-240 VAC, 50-60 Hz 2.8 A Max</p>
<p>TEMPERATURE TOLERANCES</p>	<p>OPERATING TEMP -24° to 122° F. (-31° to 50°C.)</p> <p>NON-OP. TEMP -24° to 140° F. (-31° to 60°C.)</p> <p>(OFF MODE WITH POWER APPLIED) The non-operating temperature feature requires power to be applied.</p>
<p>PHYSICAL SPECS</p>	<p>ACCESSORIES INCLUDED Weatherproof remote control</p> <p>EXTERIOR Powder-coated aluminum.</p> <p>EXTERIOR COLORS Black, Silver, White</p> <p>TV DIMENSIONS 44.72" W x 27.16" H (29.33" H with speakers) x 6.51" D</p> <p>TV WEIGHT 85.0 lbs.(88.0 lbs with speaker)</p> <p>SHIPPING DIMENSIONS 52" W x 42" H x 13" D</p> <p>SHIPPING WEIGHT 109.0 lbs.</p> <p>RESIDENTIAL WARRANTY Two-year parts and labor.</p> <p>COMMERCIAL WARRANTY Two-year parts and labor.</p>