Printing date 09/25/2014

9270

Revised On 09/25/2014

1 Identification of the substance and manufacturer

Trade name:

MRO CUMMINS BEIGE

Product code: Product category Manufacturer/Supplier: 0006201447

PC9a Paints and coatings. Seymour of Sycamore

917 Crosby Avenue

Sycamore, IL 60178 Phone: 815-895-9101 www.seymourpaint.com

Emergency telephone number:

CHEMTEL 1-800-255-3924, 813-248-0585 *if located outside the U.S.*

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas

H280 Contains gas under pressure; may explode if heated.

Carc. 2

H351 Suspected of causing cancer.

STOT RE 2

H373 May cause damage to organs through prolonged or repeated exposure.

H319 Causes serious eve irritation.

Eye Irrit. 2A **GHS Hazard pictograms**





GHS02 GHS04 GHS07 GHS08

Signal word

Hazard statements

Precautionary statements

Danger

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

Suspected of causing cancer.

May cause damage to organs through prolonged or repeated exposure. If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.
Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Wash hands thoroughly after handling.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

Do not breathe dust/fume/gas/mist/vapours/spray.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

If eve irritation persists: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention. Get medical advice/attention if you feel unwell.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

This product is a mixture of the substances listed below with nonhazardous additions.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Dangerous components: 67-64-1 Acetone 17.98% 74-98-6 propane 15.82% 106-97-8 n-butane 9.29% 1317-65-3 Calcium Carbonate 8.63% 108-10-1 methyl isobutyl ketone 7.42% 2807-30-9 Glycol Ether ÉP 4.94% 13463-67-7 titanium dioxide 4.29% 110-19-0 isobutyl acetate 3.17% 107-87-9 Methyl Propyl Ketone 2.54% 108-65-6 PM acetate 2.11%

4 First-aid measures

Chemical Description:

After inhalation: After skin contact: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After eye contact: After swallowing:

Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

(Contd. on page 2)

(Contd. of page 1)

Printing date 09/25/2014 Revised On 09/25/2014

Trade name: MRO CUMMINS BEIGE

Most important symptoms and

effects:

Indication of any immediate medical

attention needed:

Dizziness

5 Fire-fighting measures

Extinguishing agents:

Special hazards:

firefighters:

Protective equipment for

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

No further relevant information available.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Methods and material for containment and cleaning up: Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm REL (USA) Long-term value: 590 mg/m3, 250 ppm

TLV (USA)

Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm

REL (USA) Long-term value: 1800 mg/m3, 1000 ppm

TLV (USA) refer to Appendix F

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m3, 800 ppm

TLV (USA) Short-term value: 2370 mg/m3, 1000 ppm

108-10-1 methyl isobutyl ketone

PEL (USA) Long-term value: 410 mg/m³, 100 ppm

REL (USA)

Short-term value: 300 mg/m³, 75 ppm Long-term value: 205 mg/m³, 50 ppm Short-term value: 307 mg/m³, 75 ppm Long-term value: 82 mg/m³, 20 ppm

TLV (USA)

110-19-0 isobutyl acetate

PEL (USA) Long-term value: 700 mg/m³, 150 ppm

Long-term value: 700 mg/m³, 150 ppm REL (USA)

TLV (USA) Long-term value: 713 mg/m3, 150 ppm

107-87-9 Methyl Propyl Ketone

Long-term value: 700 mg/m³, 200 ppm PEL (USA) REL (USA) Long-term value: 530 mg/m3, 150 ppm

TLV (USA) Short-term value: 529 mg/m3, 150 ppm

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 3)

(Contd. of page 2)

Printing date 09/25/2014 Revised On 09/25/2014

Trade name: MRO CUMMINS BEIGE

108-10-1 methyl isobutyl ketone

BEI (USA) 1 mg/L

Medium: urine Time: end of shift Parameter: MIBK

Hygienic protection:

Keep away from foodstuffs and animal feed. Wash hands after use.

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn.

If you suspect overexposure conditions exist, please consult an authority on chemical hygeine. Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Odor:

Aerosol. Aromatic

Odor threshold:

Hand protection:

Not determined. Not determined.

pH-value: Melting point/Melting range

Undetermined. -44 °C (-47 °F)

Boiling point: Flash point:

-19 °C (-2 °F) Extremely flammable.

Flammability (solid, gas): Decomposition temperature:

Not determined.

Auto igniting:

Product is not self-igniting.

Danger of explosion:

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: Upper Explosion Limit:

1.7 Vol % 10.9 Vol %

Not determined.

Vapor pressure: Relative Density:

Between 0.77 and 0.85 (Water equals 1.00)

Vapour density Evaporation rate

Not determined. Not applicable. Partition coefficient: n-octonal/water: Not determined.

Solubility: Viscosity:

Not determined. Not determined.

VOC content: VOC content (less exempt solvents):

494.7 g/l / 4.13 lb/gl

MIR Value:

47.0 % 1.06

Solids content:

35.1 %

10 Stability and reactivity

Reactivity:

Stable at normal temperatures.

Conditions to avoid:

Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability:

Not fully evaluated.

Possibility of hazardous reactions:

No dangerous reactions known. No further relevant information available.

Incompatible materials: Hazardous decomposition:

No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat) 108-10-1 methyl isobutyl ketone

Oral LD50 LD50 Dermal

2100 mg/kg (rat)

16000 mg/kg (rab) Inhalative LC50/4 h 8.3-16.6 mg/l (rat)

13463-67-7 titanium dioxide

Oral LD50 >20000 mg/kg (rat) Dermal LD50 >10000 mg/kg (rbt) Inhalative LC50/4 h >6.82 mg/l (rat)

(Contd. on page 4)

Printing date 09/25/2014 Revised On 09/25/2014

Trade name: MRO CUMMINS BEIGE

(Contd. of page 3)

110-19-0 isobutyl acetate

LD50 Oral 4763 mg/kg (rbt)

108-65-6 PM acetate

LD50 8500 mg/kg (rat) Oral

Inhalative LC50/4 h 35.7 mg/l (rat)

Information on toxicological effects: No data available.

Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

108-10-1 methyl isobutyl ketone 2B 13463-67-7 titanium dioxide 2B

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity:

Hazardous for water, do not empty into drains.

Persistence and degradability:

The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential: Mobility in soil:

No further relevant information available. No further relevant information available. No further relevant information available.

13 Disposal considerations

Other adverse effects:

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950

DOT Aerosols, flammable ADR 1950 Aerosols

Transport hazard class(es):

Class 2.1 Marine pollutant: No

Special precautions for user: Warning: Gases

EMS Number: F-D,S-Ù

Packaging Group: UN "Model Regulation":

UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-10-1 methyl isobutyl ketone

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

108-10-1 methyl isobutyl ketone

13463-67-7 titanium dioxide 100-41-4 ethyl benzene

EPA:

67-64-1 Acetone

108-10-1 methyl isobutyl ketone

110-19-0 isobutyl acetate

USDA (United States Department of

Agriculture):

Category 21: This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of this product to be safe for use in official meat and poultry establishments, and to perform well under a daily regimen of thorough cleaning, cyclical temperature change, and wet conditions. This product may be used where there is a possibility of incidental food contact.

16 Other information

Contact: Regulatory Affairs