# SAMSUNG DM-D LARGE-SIZE COMMERCIAL LED LCD DISPLAYS

ENSURE MAXIMUM UPTIME



# PUT A CLEAR AND COMPELLING MESSAGE FORWARD WITH 24/7 CONTINUOUS OPERATION

Samsung makes it easy to create a strong impression. The DM65D, DM75D and DMD82D commercial displays offer reliable 24/7 uptime and contain many features and benefits to effectively communicate in the busiest environments. With enhanced SoC (system-on-chip) performance and internal media player functionality, users can display content without the need of an external PC and can control messaging through either a RS232 or LAN connection. Samsung MagicInfo software simplifies content creation and programming. Each unit comes with a built-in quad-core processor to manage graphics-heavy content. Samsung's high-resolution HD graphics ensure messages are sharp and clear.

CONTACT US:

Hospitality TV Sales: 888-866-9981 ProTVSolutions.com



### **KEY FEATURES**



### Large Signage with Reliable 24/7 Operation

Large-size displays feature innovative Samsung cooling technologies, for highly reliable 24/7 continuous operation. For added peace of mind, they come with a 3-year onsite commercial warranty.



#### Built-In Wi-Fi

In addition to HDMI, USB and D-Sub (analog) connectivity, the built-in Wi-Fi lets you easily share or mirror content from a tablet or other mobile device.



# Enhanced System-on-Chip Performance with Quad-Core CPU

Powered by a System-on-Chip semiconductor and quad-core CPU, Samsung's Smart Signage Platform reduces TCO for digital signage deployments, providing savings in hardware, installation and operating costs.

#### Easy Content Control

The Samsung SMART Signage platform eliminates the need for an external media player. With Samsung MagicInfo<sup>™</sup> content management software, selecting and scheduling software is simple to control with either a RS232 or LAN connection.



#### Super-Slim 2.3" Chassis

The stylishly thin chassis helps simplify installation while meeting ADA compliance requirements.

#### LED Technology

DM-D Series LED displays feature 1920 x 1080 Full HD resolution and up to 5000:1 contrast ratio for sharp, detail-rich images and crisp, easily legible type. LED gives you the advantage of large signage, with reduced power consumption and heat output.

Add an optional IR touch overlay accessory to enable up to 10

Optional Touch Overlay (65" and 75" only)



# simultaneous touch points. New Industrial Design

A sleek, stylish new look features our new hidden logo tag, for a clean, sophisticated installation.

## Samsung DM-D Large-Size Commercial LED LCD Displays





ANNUAL SALES REPORT



Conditions Features Special Tuner	orizontal/Vertical) 3-to-Ci) RGB Video Audio RGB Audio Audio ion (Typical/Max) tion (Standby)	65"           60Hz Slim D-LED BLU           1920 x 1080 (16:9)           450 nits           4000:1           178°/178°           Landscape / Portrait           6.5ms           VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2           HDMI, Component/Composite           Stereo Mini Jack           DisplayPort 1.2 (Loop-out)           Stereo Mini Jack           DisplayPort 1.2 (Loop-out)           Stereo Mini Jack           DisplayPort 1.2 (Loop-out)           Stereo Mini Jack           RS232C (in/Out) Thru Stereo Jack, RJ45           IR, Ambient Light           AC 100 - 240 V~ (+/- 10 %), 50/60 Hz           105W / 264W           < 0.5W           0°C~40°C           10-80%           Slim & Light LFD with Built-in Magichrío Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (b USB), Auto Source Switching & Recovery, RS232C/RJ45           MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDCP Support), Built In MagicInfo Player S2, Firmware Update by Network, LFD New Home Screen, PC-less VideoWall, Predefined	75"           60Hz Slim D-LED BLU           1920 x 1080 (16:9)           450 nits           5000:1           178°/178°           Landscape / Portrait           8ms           VGA (0-Sub 15 Pin), DVI-D, DisplayPort 1.2           HDMI, Component/Composite           Stereo Mini Jack           DisplayPort 1.2 (Lop-out)           Stereo Mini Jack           RS232C (In/Out) Thru Stereo Jack, RJ45           IR, Ambient Light           AC 100 - 240 V~ (±/-10 %), 50/60 Hz           147W / 308W           < 0.5W           0°C~40°C           10~80%           Slim & Light LFD with Built-in MagicInfo Player S2           Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot           Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module           Embedded, SD Card Slot           Magic Clone (to USB), Auto Source Switching & Recovery, RS232CRJ45           MDC, Pug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital           Daisy Chain (HOCP Support), Built Housian Player Play Play Built Magicher Player S2	82* 120Hz Edge-lit LED 1920 x 1080 (16:9) 500 nits 5000:1 178°/178° Landscape / Portrait 8ms VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2 HDMI (3), Component/Composite Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (In/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V = (4/- 10 %), 50/60 Hz 138W / 363W < 0.5W 0°C-40°C 10-80% Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Displa Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Stot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 Mo2, Piug and Play, PIP/PPP, Image Rotation, Button Lock, DP 1.2 Digital
Resolution Brightness Contrast Ratio Viewing Angle (H Orientation Response Time (C Dutput External Control External Control External Control External Control External Sensor Power Consumpl Power Consumpl Power Consumpl Power Consumpl Features Features Special	orizontal/Vertical) S-to-G) RGB Video Audio RGB Audio tion (Typical/Max) tion (Typical/Max) tion (Standby) srature Hardware	1920 x 1080 (16:9)           450 nits           4000:1           178*/178°           Landscape / Portrait           6.5ms           VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2           HDMI, Component/Composite           Stereo Mini Jack           DisplayPort 1.2 (Loop-out)           Stereo Mini Jack           RS232C (In/Out) Thru Stereo Jack, RJ45           IR, Ambient Light           AC 100 - 240 V~ (+/- 10 %), 50/60 Hz           105W / 264W           < 0.5W	1920 x 1080 (16:9)           450 nits           5000:1           178°/178°           Landscape / Portrait           8ms           VGA (D-Stu 15 Pin), DVI-D, DisplayPort 1.2           HDMI, Component/Composite           Stereo Mini Jack           RS232C (In/Out) Thru Stereo Jack, RJ45           IR, Ambient Light           AC 100 - 240 V~ (±/- 10 %), 50/60 Hz           147W / 308W           < 0.5W	1920 x 1080 (16:9)           500 nits           5000:1           178°/178°           Landscape / Portrait           8ms           VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2           HDMI (3), Component/Composite           Stereo Mini Jack           DisplayPort 1.2 (Loop-out)           Stereo Mini Jack           RS322C (m/Out) Thru Stereo Jack, RJ45           IR, Ambient Light           AC 100 - 240 V~ (+/- 10 %), 50/60 Hz           138W / 363W           < 0.5W
Power Consumpt Finvironmental Conditional Features Tuner Tuner	S-to-Ci)  RGB Video Audio RGB Audio RGB Audio (Typical/Max) tion (Standby) rature Hardware	450 nits 4000:1 178°/178° Landscape / Portrait 6.5ms VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2 HDML, Component/Composite Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (In/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 105W / 264W < 0.5W 0°C-40°C 10-80% Sim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WIFI Module Embedded, SD Card Slot Magic Clone (to US8), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDCP Support), Built In MagicInfo Player S2, Firmware	450 nits 5000:1 178°/178° Landscape / Portrait 8ms VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2 HDM, Component/Composite Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (In/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 147W / 308W < 0.5W 0°C~40°C 10-80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videovall (15 x 15), Pivot Display, Clock Rattery (80 hrs. Clock Keeping), Built in Speaker, WFI Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232CRJ45 MDC, Plug and Play, PIP/PPB, Image Rotation, Button Lock, DP 1.2 Digital	500 nits 5000.1 178°/178° Landscape / Portrait 8ms VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2 HDMI (3), Component/Composite Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (In/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 138W / 363W < 0.5W 0°C~40°C 10~80% Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Displa Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Stot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45
Contrast Ratio Viewing Angle (H Orientation Response Time (C Output External Control External Sensor Power Power Consumpl Power Consumpl Power Consumpl Power Consumpl Freatures Features Special	S-to-Ci)  RGB Video Audio RGB Audio RGB Audio (Typical/Max) tion (Standby) rature Hardware	4000:1 178°/178° Landscape / Portrait 6.5ms VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2 HDMI, Component/Composite Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (in/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V- (+/- 10 %), 50/60 Hz 105W / 264W < 0.5W 0°C-40°C 10-80% Slim & Light LFD with Built-in MagicInto Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WFI Module Embedded, SD card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDOP Suppor), Built in MagicInfo Player S2. Firmware	5000:1 178°/178° Landscape / Portrait 8ms VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2 HDM, Component/Composite Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (In/Out) Thru Stereo Jack, RJ45 II, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 147W / 308W < 0.5W 0°C~40°C 10~80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232CR/45 MDC, Plug and Play, PIP/PRP, Image Rotation, Button Lock, DP 1.2 Diglab	5000:1 178°/178° Landscape / Portrait 8ms VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2 HDMI (3), Component/Composite Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (in/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V- (+/- 10 %), 50/60 Hz 138W / 363W < 0.5W 0°C-40°C 10-80% Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Displa Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Stot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45
Viewing Angle (H Orientation Response Time (C Response Time (C Output External Control External Sensor Power Power Consumpl Power Con	S-to-Ci)  RGB Video Audio RGB Audio RGB Audio (Typical/Max) tion (Standby) rature Hardware	178°/178° Landscape / Portrait 6.5ms VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2 HDMI, Component/Composite Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (In/Uut) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 105W / 264W < 0.5W 0°C~40°C 10-80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Or (15 x 15), Pivot Display, Subtray (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot MDc, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Diasy Chain (HDC) Support), Built in MagicInfo Player S2, Firmware	178°/178°           Landscape / Portrait           8ms         VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2           HDMI, Component/Composite         Stereo Mini Jack           DisplayPort 1.2 (Loop-out)         Stereo Mini Jack           RS232C (In/Out) Thru Stereo Jack, RJ45         IB, Ambient Light           AC 100 - 240 V~ (+/- 10 %), 50/60 Hz         147W / 308W           < 0.5W	178°/178°           Landscape / Portrait           8ms           VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2           HDMI (3), Component/Composite           Stereo Mini Jack           DisplayPort 1.2 (Loop-out)           Stereo Mini Jack           RS232C (m/Out) Thru Stereo Jack, RJ45           IR, Ambient Light           AC 100 - 240 V~ (+/- 10 %), 50/60 Hz           138W / 363W           < 0.5W
Connectivity Connectivity Connectivity Connectivity Comparison Power Power Supply Power Consumpt	S-to-Ci)  RGB Video Audio RGB Audio RGB Audio (Typical/Max) tion (Standby) rature Hardware	Landscape / Portrait 6.5ms VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2 HDM, Component/Composite Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS2322 (In/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 105W / 264W < 0.5W 0°C~40°C 10-80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WIFI Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232/CRJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Diasy Chain (HDC) Support), Built In MagicInfo Player S2, Firmware	Landscape / Portrait 8ms VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2 HDM, Component/Composite Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (tr/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 147W / 308W < 0.5W 0°C-40°C 10-80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Rattery (80 hrs. Clock Keeping), Built in Speaker, WFI Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PRP, Image Rotation, Button Lock, DP 1.2 Digital	Landscape / Portrait 8ms VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2 HDMI (3), Component/Composite Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (In/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 138W / 363W < 0.5W 0°C~40°C 10~80% Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Displa Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Stot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45
Connectivity Connectivity Connectivity Competitive Conditions Features Conditions Features Conditions Conditio	RGB       Video       Audio       RGB       Audio       ion (Typical/Max)       ion (Standby)       yrature       Hardware	6.5ms VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2 HDML, Component/Composite Stereo Mini Jack DisplayPort 1.2 (Lopo-out) Stereo Mini Jack RS232C (In/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V- (+/- 10 %), 50/60 Hz 105W / 264W < 0.5W 0°C-40°C 10-80% Slim & Light LFD with Built-in MagicInto Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 Ins Clock Keeping), Built In Speaker, WiFI Module Embedded, SD Card Slot MDc, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDCP Support), Built In MagicInto Player S2, Firnware	8ms         VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2           HDM, Component/Composite         Stereo Mini Jack           DisplayPort 1.2 (Loop-out)         Stereo Mini Jack           R, Ambient Light         R           AC 100 - 240 V~ (+/- 10 %), 50/60 Hz         147W / 308W           < 0.5W	8ms         VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2           VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2           HDMI (3), Component/Composite           Stereo Mini Jack           DisplayPort 1.2 (Loop-out)           Stereo Mini Jack           RS232C (in/Out) Thru Stereo Jack, RJ45           IR, Ambient Light           AC 100 - 240 V~ (+/- 10 %), 50/60 Hz           138W / 363W           < 0.5W
Connectivity Input Output External Control External Sensor Power Power Consumpl Power Consumpl Power Consumpl Power Consumpl Frvironmental Conditions Features Special Tuner	RGB       Video       Audio       RGB       Audio       ion (Typical/Max)       ion (Standby)       yrature       Hardware	VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2 HDMI, Component/Composite Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (In/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 105W / 264W < 0.5W 0°C~40°C 10-80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDC) Support), Built in MagicInfo Player S2, Firmware	VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2 HDM, Component/Composite Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (In/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 147W / 308W < 0.5W 0°C~40°C 10–80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital	VGA (D-Sub 15 Pin), DVI-D, DisplayPort 1.2 HDMI (3), Component/Composite Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS2326 (I/VU)T Inru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 138W / 363W < 0.5W 0°C~40°C 10~80% Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Displa Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFI Module Embedded, SD Card Stot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45
Input Output External Control External Sensor Power Power Consumpt Power Consumpt Power Consumpt Freatures Special Tuner	Video Audio RGB Audio I I I I I I I I I I I I I I I I I I I	HDMI, Component/Composite         Stereo Mini Jack         DisplayPort 12 (Loop-out)         Stereo Mini Jack         RS232C (In/Out) Thru Stereo Jack, RJ45         IR, Ambient Light         AC 100 - 240 V~ (+/- 10 %), 50/60 Hz         105W / 264W         < 0.5W	HDM, Component/Čomposite Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (In/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 147W / 308W < 0.5W 0°C~40°C 10~80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs. Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PRP, Image Rotation, Button Lock, DP 1.2 Digital	HDMI (3), Component/Composite Stereo Mini Jack DisplayPort 12 (Loop-out) Stereo Mini Jack RS232C (In/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V ← (+/ - 10 %), 50/60 Hz 138W / 363W < 0.5W 0°C~40°C 10~80% Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Disple Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Stot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45
Power Consumpt     Power Co	Audio RGB Audio Itypical/Max) tion (Typical/Max) tion (Standby) reature Hardware	Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (In/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V- (+/- 10 %), 50/60 Hz 105W / 264W < 0.5W 0°C-40°C 10-80% Slim & Light LFD with Built-in MagicInto Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFI Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDCP Support), Built in MagicInto Player S2, Firmware	Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (in/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 147W / 308W < 0.5W 0°C~40°C 10–80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital	Stereo Mini Jack DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (in/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 138W / 363W < 0.5W 0°C~40°C 10-80% Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Displa Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Stot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45
External Control External Sensor Power Supply Power Consumpl Power Consumpl Power Consumpl Power Consumpl Power Consumpl Humidity Features Special Tuner	RGB       Audio       iion (Typical/Max)       iion (Standby)       arature       Hardware	DisplayPort 1.2 (Loop-out) Stereo Mini Jack RS232C (In/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V- (+/- 10 %), 50/60 Hz 105W / 264W < 0.5W 0°C-40°C 10-80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDC) Support), Built in MagicInfo Player S2, Firmware	DisplayPort 1.2 (Loop-out)           Stereo Mini Jack           RS232C (In/Out) Thru Stereo Jack, RJ45           IB, Ambient Light           AC 100 - 240 V~ (+/- 10 %), 50/60 Hz           147W / 308W           < 0.5W	DisplayPort 1.2 (Loop-out)           Stereo Mini Jack           RS2326 (I/Vul) Thru Stereo Jack, RJ45           IR, Ambient Light           AC 100 - 240 V~ (+/- 10 %), 50/60 Hz           138W / 363W           < 0.5W
External Control External Sensor Power Supply Power Consumpl Power Consumpl Power Consumpl Power Consumpl Power Consumpl Humidity Features Special Tuner	Audio ion (Typical/Max) ion (Typical/Max) ion (Standby) erature Hardware	Stereo Mini Jack         RS232C (In/Out) Thru Stereo Jack, RJ45         IR, Ambient Light         AC 100 - 240 V~ (+/- 10 %), 50/60 Hz         105W / 264W         < 0.5W	Stereo Mini Jack           RS232C (m/Out) Thru Stereo Jack, RJ45           IB, Ambient Light           AC 100 - 240 V~ (+/- 10 %), 50/60 Hz           147W / 308W           < 0.5W	Stereo Mini Jack RS232C (In/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V - (+/- 10 %), 50/60 Hz 138W / 363W < 0.5W 0°C-40°C 10-80% Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Disple Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45
External Control External Sensor Power Supply Power Consumpl Power Consumpl Power Consumpl Power Consumpl Power Consumpl Humidity Features Special Tuner	ion (Typical/Max) tion (Standby) rature Hardware	RS232C (In/Out) Thru Stereo Jack, RJ45 IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 105W / 264W < 0.5W 0°C~40°C 10~80% Silm & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFI Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDCP Support), Built in MagicInfo Player S2, Firmware	RS232C (In/Out) Thru Stereo Jack, RJ45           IR, Ambient Light           AC 100 - 240 V~ (+/- 10 %), 50/60 Hz           147W / 308W           < 0.5W	RS232C (In/Out) Thru Stereo Jack, RJ45           IR, Ambient Light           AC 100 - 240 V~ (+/- 10 %), 50/60 Hz           138W / 363W           < 0.5W
External Sensor           Power         Power Supply           Power Consumpl         Power Consumpl           invironmental Conditions         Operating Tempe Humidity           Features         Special           Tuner         Tuner	rature Hardware	IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 105W / 264W < 0.5W 0°C~40°C 10~80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDC) Support), Built In MagicInfo Player S2, Firmware	IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 147W / 308W < 0.5W 0°C~40°C 10-80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFI Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital	IR, Ambient Light AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 138W / 363W 0°C~40°C 10~80% Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Displic Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45
Power Supply Power Consumpt Power Consumpt Power Consumpt Conditions Features Special	rature Hardware	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 105W / 264W < 0.5W 0°C-40°C 10-80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDC) Support), Built In MagicInfo Player S2, Firmware	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 147W / 308W < 0.5W 0°C~40°C 10~80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz 138W / 363W < 0.5W 0°C~40°C 10~80% Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Disple Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45
Power Consumpt Power Consumpt Operating Tempe Humidity Features Special	rature Hardware	105W / 264W < 0.5W 0°C-40°C 10-80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDC) Support), Built in MagicInfo Player S2, Firmware	147W / 308W < 0.5W 0°C~40°C 10~80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital	138W / 363W < 0.5W 0°C~40°C 10~80% Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Displ Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45
Power Consumpl nvironmental Condition Features Special Tuner	rature Hardware	< 0.5W 0°C~40°C 10~80% Slim & Light LFD with Built-in Magichrlo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDC) Support), Built In Magichrlo Player S2, Firmware	< 0.5W 0°C-40°C 10-80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital	< 0.5W 0°C-40°C 10-80% Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Displa Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45
invironmental Conditions Features Special Tuner	Hardware	0°C~40°C 10~80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDC) Support), Built In MagicInfo Player S2, Firmware	0°C~40°C 10-80% Slim & Light LFD with Built-in Magichrio Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, Wiri Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital	0°C~40°C 10~80% Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Displa Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS2320/RJ45
Conditions Features Features Special Tuner	Hardware	10~80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDC) Support), Built in MagicInfo Player S2, Firmware	10–80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs: Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital	10-80% Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Disple Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45
Conditions Humidity Features Special Tuner	Hardware	10~80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDC) Support), Built in MagicInfo Player S2, Firmware	10–80% Slim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs: Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital	1080% Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Displa Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45
Features Special Tuner		Sim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, S0 Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDC) Support), Built in MagicInfo Player S2, Firmware	Sim & Light LFD with Built-in MagicInfo Player S2 Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital	Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Displa Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45
Special Tuner		Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDCP Support), Built in MagicInfo Player S2, Firmware	Super Clear Coating, Temperature Sensor, Videowall (15 x 15), Pivot Display, Clock Battery (80 hrs Clock Keeping), Built in Speaker, WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital	Clock Battery (80hrs Clock Keeping), Built in Speaker (10W x 2), WiFi Module Embedded, SD Card Slot Magic Clone (to USB), Auto Source Switching & Recovery, RS232C/RJ45
Tuner	Software	MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain (HDCP Support), Built In MagicInfo Player S2, Firmware	MDC, Plug and Play, PIP/PBP, Image Rotation, Button Lock, DP 1.2 Digital	
		Template for Vertical Usage, Multi Channel, Mobile Control, Event Schedule, Backup Player, PC-less Touch, MagicPresenter	Update by Network, LFD New Home Screen, PC-less VideoWall, Predefined Template for Vertical Usage, Multi Channel, Mobile Control, Event Schedule, Backup Player, PC-less Touch, MagicPresenter	Daisy Chain (HDCP Support), Built in Magicinfo Player S2, Firmware Updat by Network, LFD New Home Screen, PC-less VideoWall, Predefined Tempi for Vertical Usage, Multi Channel, Mobile Control, Event Schedule, Backup Player, MacicPresenter
		Yes	Yes	Yes
	Platform Compliant	Yes	Yes	Yes
Internal Media Pl		Cortex-A9 1GHz Quad Core, 1.5GB DDR3, 4GB FDM, USB 2.0, Linux OS	Cortex-A9 1GHz Quad Core, 1.5GB DDR3, 4GB FDM, USB 2.0, Linux OS	Cortex-A9 1GHz Quad Core, 1.5GB DDR3, 4GB FDM, USB 2.0 (x2), Linux
	Vall Mount Interface	400 x 400mm	400 x 400mm	600 x 400mm
24/7 Operation		Yes	Yes	Yes
Dimensions Product Dimension		57.8" x 33.4" x 2.2"	66.0" x 37.8" x 2.3"	73.0" x 41.9" x 1.9" (3.5" depth incl. handles)
Packaging Dimer Bezel Width (mm		63.0" x 38.6" x 8.5" 18.0 (Top/Side) / 23.5 (Bottom)	71.3" x 42.7" x 9.8"	78.8" x 48.7" x 18.6" 20.2mm
	1)	60.5 lbs.	12.0 (Top/Side) / 17.3 (Bottom) 75.4 lbs.	106.7 lbs.
Weight Product Weight Shipping Weight		89.1 lbs.	97.5 lbs.	136.4 lbs.
Shipping Weight Service Standard Warran		3 Years On-Site (Parts / Labor / Backlight)	3 Years On-Site (Parts / Labor / Backlight)	3 Years On-Site (Parts / Labor / Backlight)
Accessories		Quick Setup Guide, Warranty Card, D-Sub Cable, Power Cord, Remote	Quick Setup Guide, Warranty Card, D-Sub Cable, Power Cord, Remote	Quick Setup Guide, Regulatory Guide, Warranty Card, D-Sub Cable, Pow
Accessories Included		Controller, Batteries, RS232C(IN) Adapter, COVER-JACK	Controller, Batteries, RS232C(IN) Adapter, COVER-JACK	Cord, Remote Controller, Batteries, RS232C(IN) Adapter, COVER-JACK
Optional Mount		WMN-4675MD	WMN-4675MD	WMN-5770D
Optional Stand		STN-L6500E	STN-L7585F	STN-L7585F
Optional Media P	Plaver	PIM-BE7, PIM-BE7P	PIM-BE7, PIM-BE7P	PIM-BF7, PIM-BF7P
Optional HDBase		PIM-HDBT	PIM-HDBT	PIM-HDBT
Optional Touch C		CY-TE65LCC	CY-TD75LDAF	N/A
Green Emission Standa		EMC	EMC	EMC
Management RoHS Compliant		Yes	Yes	Yes
Packaging Recyc		Packing Materials Recyclable	Packing Materials Recyclable	Packing Materials Recyclable
DNNECTIVITY DM65D / DM75D Aud	io In / Out	DVI In HDMI In	Antenna In IR Out	

RS232C

In / Out

IR/Ambient

Sensor In

DM82D		Anter	nna In IF
•• <b>••</b> ••		•	<b>)</b>
RS232C IR/Ambient Audio SD Card Slot USB In / Out Sensor In In / Out	USB DVI In DisplayPort In HDMI In	VGA In DisplayPort Out	AV In

VGA In DisplayPort Out

AV In

RJ45 In

## **SAMSUNG**

To help select the right Samsung Hospitality Television for your property, and for price and availability, visit ProTVSolutions.com or call 888-866-9981.



IR Out

. RJ45 In

Samsung Electronics has been named 2013 ENERGY STAR Partner of the Year in the product manufacturing category by the U.S. Environmental Protection Agency (EPA).

I DisplayPort In

USB

SD Card Slot

ENERGY STAR AVVARD 2013 PARTNER OF THE YEAR PARTNER OF THE YEAR PARTNER OF THE YEAR