# **Professional Plus**

Filter Fabric • Patio/Paver Underliner • Weed Control • Soil Separator 4 oz. Nonwoven





### WEED CONTROL FABRIC

- Stops approx. 95% of weed growth
- Lets air, water and fertilizer pass through to plant roots
- Saves you time (no more weeding)
- Permanent when covered from sunlight

### **FILTER FABRIC**

- Protects native soil and silt from clogging drainage septic systems
- Drainage protection to maintain flow and percolation
- Prolongs life of septic drain fields and drainage pipes
- Proven alternative to graded aggregate or sand filters

# **BENEFITS**

- · Maximum water flow
- Prevents soil movement in erosion control applications
- High strength to withstand heavy traffic
- · Cuts easy, installs quickly
- · Permanent when covered from sunlight

# **OTHER APPLICATIONS**

- Weed control
- Erosion control
- Paver underliner
- Landfills

### **USE UNDER OR AROUND**

- Patio Blocks & Pavers
- Decorative Stone & Bark
- Retaining Wall Filter Fabric
- Drainage and Septic Systems
- Sand
- \* Refer to page 18 for installation instructions

# DEIN

#### **Bulk Rolls**

3 X 250	/50 sq. π.	2b#^
4 x 250	1000 sq. ft.	34#*
5 x 250	1250 sq. ft.	43#*
6 x 250	1500 sq. ft.	52#*
8 x 250	2000 sq. ft.	68#*
10 x 250	2500 sq. ft.	86#*
12 x 250	3000 sq. ft.	104#*
15 x 250	3750 sq. ft.	128#*

**AVAILABLE SIZES** 

\* Roll sizes & weights may vary. For best results the use of a pre and post emergent herbicide is advised.

PROVIDES
MAXIMUM
WATER
PERMEABILITY



6398 W. 74TH ST. • BEDFORD PARK, ILLINOIS 60638 (708) 728-7180 • 1-800-992-0550 • FAX: (708) 728-0482 www.fabriscape.com • e-mail: info@fabriscape.com

# TYPICAL SPECIFICATIONS

Properties	Test Method	4 oz.
Grab Tensile (lbs)	ASTM D-4632	105
Grab Elongation (%)	ASTM D-4632	50
Puncture Strength (lbs)	ASTM D-4833	65
Mullen Burst (psi)	ASTM D-3786	210
Trapezoidal Tear (lbs)	ASTM D-4533	45
Apparent Opening Size (AOS)	ASTM D-4751	70
Permittivity (sec-1)	ASTM D-4491	2.0
Permeability (cm/sec)	ASTM D-4491	.22
Water Flow Rate (gpm/ft²)	ASTM D-4491	145
Weight (oz/yd²)	ASTM D-3776	4.0
Thickness (mils)	ASTM D-1777	55
U.V. Resistance	ASTM D-4355	70
Material	Poly	propylene

