Contender Solid Tires

Distributed By Advance Tire Inc.

1 1 1

Advance Tire Your Complete Source For Solid Tires (800) 445-6647 www.advancetires.com

Tire Sizes and Tread Patterns

CONTENDER



CONTENDER SEMI SMOOTH / SG Tires

	Tire Size	Rim <mark>Size</mark>	Tire OD	Width	Rubber Depth	Tread Depth	Weight
	1400-24	10.00 <mark>-24</mark>	53	14	14	5	895
10	17.5-25	14.5- <mark>25</mark>	53	17.5	14	7	> 1030
1 Sta	20.5-25	17.00 <mark>-25</mark>	59	20.5	17	8.5	1542
	<mark>2</mark> 3.5-25	19.5- <mark>25</mark>	64	23.5	19.5	9	2156
	<mark>26</mark> .5-25	22.00- <mark>25</mark>	68.8	26.5	21	10	3014
19 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	<mark>29</mark> .5-25	25.00- <mark>25</mark>	72	29.5	24	11	3894
N-129236	35/65-33	28.00- <mark>2</mark> 5	81	34.6	24	14	5478

Smooth Solids



Soft Ride Solid Rubber Loader Tires

No rims to buy. Tough cut resistant rubber. More wearable rubber. One or two rows of aperture holes. Ask about our rim exchange program.

TY DA LUG



Tire Size	Rim Size	Tire OD	Width	Rubb <mark>er Dep</mark> th	Tread Depth	Weight
1400-24	10.00-24	53	14	14	5	895
17.5-25	14.5-25	53	17.5	14	7	1030
20.5-25	17.00-25	58	20.5	17	8.5	1542
23.5-25	19.5-25	64	23.5	19.5	9	2156
26.5-25	22.00-25	67	26.5	21	10	3014
29.5-25	25.00-25	72	29.5	24	11	3894
35/65-33	28.00-25	81	34.6	24	14	5478
26.5-25 29.5-25	22.00-25 25.00-25	67 72	26. <mark>5</mark> 29.5	21 24	10 11	301 389

Skid Steer, Backhoe, Forklift, Wheel Excavators, Haul Trucks Tires.



Advance Tire, Inc. 1000 Rike Dr, Millstone Twp., NJ 08535 Phone (800) 445-6647 · Fax (609) 490-9776 Info@advancetires.com , www.advancetires.com