

MISCELLANEOUS

ASA STRIKES, FLUSH BOLTS, FASTENER SEXBOLT, PUSH & PULL HANDLES

ASA STRIKES



- Meets the ASA strike specification size of A115.2 of 4-7/8"H x 1-1/4"W
- Used for knob & lever sets in commercial applications

MFG #	TYPE	FINISH	EZ #
ASA C15	Standard	Brushed Nickel	035224
ASAC3	Standard	Polished Brass	082308
ASAC15T	Adjustable Lip	Brushed Nickel	083790

FLUSH BOLTS



DC840



DC860

- For keeping the inactive door of a pair of doors stationary
- DC840 supplied in pairs
- DC860 sold individually

MFG #	FOR	HEIGHT	WIDTH	THROW	EZ #
DC840 C15	Steel	6-1/4"	1'	5/8'	086322
DC860C28	Aluminum	5-1/4"	15/16"	5/8"	039421

FASTENER SEXBOLT



- Zinc plated thru-bolt for affixing door closers, exit devices and other hardware on 1-3/4" doors where a blind bolt fastener is required on exterior side
- Allen key nut interior

MFG #	EZ #
SF710ZCB	039649

PUSH & PULL PLATES



1410



H1413

1410

- Push/pull plate combination with a 9" pull mounted on a 4" x 16" push plate
- Aluminum finish

H1413

- Pull handle only

MFG #	DESCRIPTION	EZ #
1410 AL	Push Pull Handle Set	035220
H1413	9" Pull Handle Only	067805