

## The Magic is the Media

A ISO 9001:2008 - ANSI-ISO-ASQ Q9001-2008 Company

### **SECTION I**

PRODUCT NAME OR NUMBER (as it appears on label)						
Magic 10/30 Aerospace SuperStrip-A®						
MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.					
U.S. Technology Media Inc.	(330) 455-1181					
ADDRESS (Number, Street, City, and Zip Code)	DATE PREPARED/REVISED – NO.					
509 Water ST., Bolivar OH. 44612	06/06/2018					
MATERIAL DESCRIPTION, PROPER SHIPPING NAME						
Plastic Abrasive, Thermoset Polymer/Dense Particle Abra	sive					
HAZARD CLASSES (as applicable): Non-regulated						
FORMULA: N.A.						

### **SECTION II - INGREDIENTS**

(list all ingredients)

CAS REGISTRY NO.	Approx. %W	CHEMICAL NAME (S)	OSHA PEL	ACGIH TLV	Other Limits Recommended
9011-05-6	>1%	Polymerized Urea-Melamine			
9003-08-1		Formaldehyde Compound			
9004-34-6		w/Alpha Cellulose Filler and			
1318-93-0		Montmorillonite Clay			
2764-13-8	<1%	Anti-Static Agent – Cal Stat600			
5280-80-8	<1%	Pigments and Additives			
13463-67-7					
12769-96-9					
1344-28-1	>1%	Fused Aluminum Oxide			

### **SECTION III – PHYSICAL DATA**

BOILING POINT°FC	N.A.	SPECIFIC GRAVITY (H <sub>2</sub> 0=1)	2.00		
			2.06		
MELTING POINT°FC	N.A.	PERCENT VOLATILE BY VOLUME	N.A.	PERCENT SOLID	100
		(%)		BY WEIGHT (%)	
VAPOR DENSITY (AIR=1)	N.A.	EVAPORATION RATE ( =1)	N.A.		
SOLUBILITY IN WATER	N.A.	pH=	4-8		
APPEARANCE AND ODOR: Multi-colored granules with slight plastic odor				MATERIAL FORM: S	Solid

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

				LEL	UEL
FLASH POINT	°F _	C: N.A.	FLAMMABLE: N.A.	N.A.	N.A.
EXTINGUISING MEDIA: Carbon dioxide, dry chemicals or water fog.					
SPECIAL FIRE FIGHTING PROCEDURES: Do not use high-pressure water stream. Fog nozzles are preferable.					
UNUSUAL FIRE AND EXPLOSION HAZARDS: Maintain normal good housekeeping for control of dust.					

### Magic® Aerospace SuperStrip-A\*\*\* Page 1 of 2

### SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE – Conditions to Avoid:	THRESHOLD LIMIT VALUE					
Mechanical injury to eyes and/or skin can occur.	PERMISSIBLE EXPOSURE LIMIT					
Excessive dust inhalation may be harmful.						
PRIMARY ROUTES OF ENTRY: ⊠ Inhalation ⊠ Skin Contact □ Other (specify)						
<b>EMERGENCY AND FIRST AID PROCEDURES:</b> In case of eye or skin irritation, flush with plenty of water for 15						
minutes. Inhalation – remove to fresh air and contact physician if necessary.						
SECTION VI _ DEACTIVITY DATA						

#### SECTION VI – REACTIVITY DATA

	UNSTABLE		CONDI	TIONS TO AVOID:	
STABILITY	STABLE	Х			
INCOMPATIBILITY INCOMPATIBILITY	TY (materials	to av	oid): No	specific incompatibility	
HAZARDOUS DE	HAZARDOUS DECOMPOSITION or BYPRODUCTS: Smoke, carbon dioxide, carbon monoxide, formaldehyde,				
hydrogen cyanide	hydrogen cyanide at +500°F.				
	HAZARDOUS MAY OCCUR CONDITIONS TO AVOID:				
POLYMERIZATI	POLYMERIZATION MAY NOT X				
	OCCUF	<u> </u>			

### SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove open flame, sparks, hot					
surfaces and oxidizing agents. Sweep up and place waste in disposal container.					
WASTE DISPOSAL METHOD: Sanitary landfill in accordance with Federal, State, and Local regulations.					
CERCLA (Superfund) REPORTABLE QUANTITY (in lbs.): N.A.					
RCRA HAZARDOUS WASTE NO. (40 CFR 261.33): N.A.					
VOLATILE ORGANIC COMPOUND (VOC) (as packaged, minus water): N.A.					
☐ Theoretical lbs. /gal. ☐ Analytical lbs. /gal					

### **SECTION VIII - SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION (Specify Type): Where required, use NIOSH/MSHA approved respiratory					
protection in com	protection in compliance with OSHA regulations (i.e.1910.134 et. al.).				
VENTILATION	LOCAL EXHAUST (Specify Rate): W	here necessary to	SPECIAL: Explosion proof may be		
	maintain exposure levels to OSHA per	necessary if aerated or airveyed.			
MECHANICAL (General – Specify Rate): Acceptable OTHER:					
PROTECTIVE GLOVES (Specify Type): Normal EYE PROTECTION (Specify Type): Safety goggles					
OTHER PROTECTION EQUIPMENT: Respirator hood, if necessary.					

### **SECTION IX - SPECIAL PRECAUTIONS**

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in closed, properly labeled containers in a cool ventilated area. Keep away from heat, sparks, open flame and oxidizing agents. Do not transfer to unmarked containers.

# **OTHER PRECAUTIONS:**

Prepared by:

Name (print): Casey Wiliams **Title:** Quality Assurance Manager **Date Reviewed:** 06/06/2018

Magic® Aerospace SuperStrip-A\*\*\* Page 2 of 2