



COMPACT

**BEST
QUALITY
SILAGE
ON
EXPORT
LEVEL**



Silage Baling is the most superior Technology to naturally Preserve forages for more than a Year.....

Vidhata Balres are best it!



SALAGER	AVAILABLE IN	SALAGER
120 PRO	TWO VARIANTS	120 PRO+
(100 KG)		(PLC PENAL, LINK, PRINTER, 100 KG)

TOLL FREE NO.: 1800-309-3852

IMPORTANT FEATURES

INTERNAL WRAPPING UNIT

First stage internal wrapping
 Programmable no. of internal layers
 UV protected wrapping film
 520 mm film roll

OPERATOR PLATFORM

Elevated Platform for operator
 Easy Monitoring of all operation

COMPRESSION CHAMBER

Compaction rate: 650 kg/m³
 Automatic pressure control

EXTERNAL WRAPPING UNIT

Programmable no. of layers
 Automatic bale count
 Automatic bale ejection

HOPPER & CONVEYOR SYSTEM

Programmable no. of layers
 Automatic bale count
 Automatic bale ejection



TECHNICAL SPECIFICATION		
PERAMETER	SALAGER 120 PRO	SALAGER 120 PRO +
Machine width	6.50 feet	
Machine Length	16.0 feet	
Machine Height	7.50 feet	
Machine total weight	3300 kg	
Hopper Capacity	600 kg	
Operation System	Digital computer with Alphanumeric Display (DC12V)	
Power source	Tractor 35 H.P PTO at 540 ROM or 20 H.P Electric Motor (3 phase)	
Compaction density	650 kg/cm ³	
Bale chamber diameter	550 mm x 500 mm	550 mm x 450 mm(HxW)
Bale Weight	92 to 100 kg	
Bales Capacity	55 to 60 bales per hour	
External Wrapping (Horizontal)	250 mm	
Internal Wrapping (Vertical)	500 mm	
Wrapping Film	25 microns	
Hydraulic Pump	20 liter (single pump)	
Hydraulic Motor	1 For External Wrapping	
Hydraulic Distributer	7 Double Action 12V Distributor	
Hydraulic oil Tank	26 litre	
Conveyor	Yes (Chain Type)	
Tyre	2 tyres	
Warning system	Alarm & Red Light	
Roller support system	Bearings, Manual Greased	
Controller power source	12 V Alternator	



BASANT PRODUCTS INDIA

C- 46 FOUNDRY NAGAR, NARAICH, HATHRAS ROAD,
 AGRA (U.P) – 282006

