

J&B PART NUMBER
IES1535

Page 1/10

Safety Data Sheet
acc. to OSHA HCS

Printing Date 07/22/2014

Revision Number 1

Revision Date 07/22/2014

1 Identification

- **Product identifier**
- **Trade name:** 1535 SUPER WEATHERSTRIP ADHESIVE (BLACK)
- **Article number:** 1535
- **Relevant identified uses of the substance or mixture.** Adhesive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
International Epoxies & Sealers
30241 Commerce Drive
San Antonio, FL 33576
Information Phone Number: 352-588-2400
- **Information department:** Regulatory.
- **Emergency telephone number:** INFOTRAC: UNITED STATES 1(800)535-5053 INTERNATIONAL 352-323-3500

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

(Contd. on page 2)

USA

Safety Data Sheet acc. to OSHA HCS

Printing Date 07/22/2014

Revision Number 1

Revision Date 07/22/2014

Trade name: 1535 SUPER WEATHERSTRIP ADHESIVE (BLACK)

(Contd. of page 1)

- **Hazard statements**

Highly flammable liquid and vapor.
 Causes skin irritation.
 Causes serious eye irritation.
 Suspected of damaging fertility or the unborn child.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.
 May be fatal if swallowed and enters airways.

- **Precautionary statements**

If medical advice is needed, have product container or label at hand.
 Keep out of reach of children.
 Read label before use.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

| | | |
|-----------------|---|---------------------|
| HEALTH | 2 | Health = *2 |
| FIRE | 3 | Fire = 3 |
| PHYSICAL HAZARD | 0 | Physical Hazard = 0 |

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

| | | |
|----------|---------------------|--------|
| 108-88-3 | toluene | 10-25% |
| 78-93-3 | methyl ethyl ketone | 5-20% |
| 67-64-1 | acetone | 5-20% |
| 110-54-3 | n-hexane | 5-20% |

4 First-aid measures

- **Description of first aid measures**

- **After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

USA

Safety Data Sheet acc. to OSHA HCS

Printing Date 07/22/2014

Revision Number 1

Revision Date 07/22/2014

Trade name: 1535 SUPER WEATHERSTRIP ADHESIVE (BLACK)

(Contd. of page 2)

- Call a doctor immediately.
- Overexposure, remove to fresh air and seek medical attention.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Seek medical treatment.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**
Water
Water and water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Protective clothing and respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste in accordance with federal state and local regulations.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling** Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location away from direct heat.
- **Information about storage in one common storage facility:** Store as flammable liquid.

(Contd. on page 4)

USA

Safety Data Sheet acc. to OSHA HCS

Printing Date 07/22/2014

Revision Number 1

Revision Date 07/22/2014

Trade name: 1535 SUPER WEATHERSTRIP ADHESIVE (BLACK)

(Contd. of page 3)

- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

| Components with limit values that require monitoring at the workplace: | |
|---|---|
| 108-88-3 toluene (10-25%) | |
| PEL | Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift |
| REL | Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm |
| TLV | Long-term value: 75 mg/m ³ , 20 ppm BEI |
| 78-93-3 methyl ethyl ketone (5-20%) | |
| PEL | Long-term value: 590 mg/m ³ , 200 ppm |
| REL | Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm |
| TLV | Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI |
| 67-64-1 acetone (5-20%) | |
| PEL | Long-term value: 2400 mg/m ³ , 1000 ppm |
| REL | Long-term value: 590 mg/m ³ , 250 ppm |
| TLV | Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m ³ , (500) NIC-250 ppm BEI |
| 110-54-3 n-hexane (5-20%) | |
| PEL | Long-term value: 1800 mg/m ³ , 500 ppm |
| REL | Long-term value: 180 mg/m ³ , 50 ppm |
| TLV | Long-term value: 176 mg/m ³ , 50 ppm Skin; BEI |

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/22/2014

Revision Number 1

Revision Date 07/22/2014

Trade name: 1535 SUPER WEATHERSTRIP ADHESIVE (BLACK)

(Contd. of page 4)

| Ingredients with biological limit values: | |
|--|---|
| 108-88-3 toluene (10-25%) | |
| BEI | 0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene |
| | 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene |
| | 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background) |
| 78-93-3 methyl ethyl ketone (5-20%) | |
| BEI | 2 mg/L Medium: urine Time: end of shift Parameter: MEK |
| 67-64-1 acetone (5-20%) | |
| BEI | 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) |
| 110-54-3 n-hexane (5-20%) | |
| BEI | 0.4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2,5-Hexanedione without hydrolysis |

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment (see listings below)**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/22/2014

Revision Number 1

Revision Date 07/22/2014

Trade name: 1535 SUPER WEATHERSTIP ADHESIVE (BLACK)

(Contd. of page 5)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses with side shields.



Tightly sealed goggles

· **Body protection:** *Protective work clothing*

9 Physical and chemical properties

| | |
|--|---|
| · Information on basic physical and chemical properties | |
| · General Information | |
| · Appearance: | |
| · Form: | <i>Liquid</i> |
| · Color: | <i>Black</i> |
| · Odor: | <i>Characteristic</i> |
| · Odour threshold: | <i>Not determined.</i> |
| · pH-value: | <i>Not determined.</i> |
| · Change in condition | |
| · Melting point: | <i>Undetermined.</i> |
| · Boiling point: | <i>55 °C (131 °F)</i> |
| · Flash point: | <i>-26 °C (-15 °F)</i> |
| · Flammability (solid, gaseous): | <i>Not applicable.</i> |
| · Ignition temperature: | <i>240 °C (464 °F)</i> |
| · Decomposition temperature: | <i>Not determined.</i> |
| · Auto igniting: | <i>Product is not selfigniting.</i> |
| · Danger of explosion: | <i>Product is not explosive. However, formation of explosive air/vapor mixtures are possible.</i> |
| · Flammable limits: | |
| · Lower: | <i>1.2 Vol %</i> |
| · Upper: | <i>13.0 Vol %</i> |
| · Vapor pressure at 20 °C (68 °F): | <i>233 hPa (175 mm Hg)</i> |
| · Specific gravity at 20 °C (68 °F): | <i>0.879 g/cm³ (7.335 lbs/gal)</i> |
| · Relative density | <i>Not determined.</i> |
| · Vapour density | <i>Not determined.</i> |
| · Evaporation rate | <i>Not determined.</i> |

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/22/2014

Revision Number 1

Revision Date 07/22/2014

| |
|---|
| Trade name: 1535 SUPER WEATHERSTRIP ADHESIVE (BLACK) |
|---|

(Contd. of page 6)

| | |
|---|---|
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 71.2 % |
| Solids content: | 28.8 % |
| · Other information | "NOTICE: This product does not comply with the requirements of Rule 1168 of California's South Coast Air Quality Management District". WEIGHT PER GALLON: 7.32 VOC: 3.88 LBS/GAL (465 G/L) 584 G/L (SCAQMD RULE 1168 METHOD) |

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** Keep away from extreme heat, sparks, open flames.
- **Possibility of hazardous reactions** Strong oxidizers, acids and bases.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
Oxides of carbon, nitrogen and hydrocarbons, hydrogen chloride (thermal degradation products).

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

| | | |
|---|----------|----------------------|
| · LD/LC50 values that are relevant for classification: | | |
| 108-88-3 toluene | | |
| Oral | LD50 | 5000 mg/kg (rat) |
| Dermal | LD50 | 12124 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 5320 mg/l (mouse) |

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitizing effect through inhalation is possible with prolonged exposure.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Carcinogenic categories**

| | | |
|---|---------|---|
| · IARC (International Agency for Research on Cancer) | | |
| 108-88-3 | toluene | 3 |

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/22/2014

Revision Number 1

Revision Date 07/22/2014

Trade name: 1535 SUPER WEATHERSTRIP ADHESIVE (BLACK)

(Contd. of page 7)

| |
|--|
| <ul style="list-style-type: none"> · NTP (National Toxicology Program) |
| <p><i>None of the ingredients is listed.</i></p> |
| <ul style="list-style-type: none"> · OSHA-Ca (Occupational Safety & Health Administration) |
| <p><i>None of the ingredients is listed.</i></p> |

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** *No further relevant information available.*
- **Persistence and degradability:** *No further relevant information available.*
- **Bioaccumulative potential:** *No further relevant information available.*
- **Mobility in soil:** *No further relevant information available.*
- **Ecotoxicological effects:**
- **Remark:** *Harmful to fish*
- **Additional ecological information:**
- **General notes:**
- Water hazard class 2 (Self-assessment): hazardous for water*
- Do not allow product to reach ground water, water course or sewage system.*
- Danger to drinking water if even small quantities leak into the ground.*
- Harmful to aquatic organisms*
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*
- **Other adverse effects:** *No further relevant information available.*

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- Must be specially treated adhering to official regulations.*
- Disposal must be made according to official regulations.*
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

14 Transport information

| | |
|---|---------------------|
| <ul style="list-style-type: none"> · UN-Number | |
| <ul style="list-style-type: none"> · DOT | UN1133 |
| <ul style="list-style-type: none"> · UN proper shipping name | |
| <ul style="list-style-type: none"> · DOT | Adhesives |
| <ul style="list-style-type: none"> · Transport hazard class(es) | |
| <ul style="list-style-type: none"> · DOT | |
| <ul style="list-style-type: none"> · Class | 3 Flammable liquids |
| <ul style="list-style-type: none"> · Packing group | |
| <ul style="list-style-type: none"> · DOT | II |

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing Date 07/22/2014

Revision Number 1

Revision Date 07/22/2014

| |
|---|
| Trade name: 1535 SUPER WEATHERSTRIP ADHESIVE (BLACK) |
|---|

(Contd. of page 8)

| | |
|--|------------------------|
| · Environmental hazards: | <i>Not applicable.</i> |
| · Special precautions for user | <i>Not applicable.</i> |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | <i>Not applicable.</i> |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

| |
|--|
| · Section 355 (extremely hazardous substances): |
| <i>None of the ingredients is listed.</i> |

| |
|--|
| · Section 313 (Specific toxic chemical listings): |
| 108-88-3 toluene |
| 110-54-3 n-hexane |

| |
|---|
| · TSCA (Toxic Substances Control Act): |
| <i>All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.</i> |

- **Proposition 65**

| |
|---|
| · Chemicals known to cause cancer: |
| <i>None of the ingredients is listed.</i> |

- **Chemicals known to cause reproductive toxicity:**

Warning: This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

| |
|--------------------|
| 108-88-3 toluene |
|--------------------|

- **(DSL) Canada Domestic Substance List**

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

- **Carcinogenicity categories**

| | | |
|--|---------------------|----|
| · EPA (Environmental Protection Agency) | | |
| 108-88-3 | toluene | II |
| 78-93-3 | methyl ethyl ketone | I |
| 67-64-1 | acetone | I |
| 110-54-3 | n-hexane | II |

- **TLV (Threshold Limit Value established by ACGIH)**

| | | |
|----------|---------|----|
| 108-88-3 | toluene | A4 |
| 67-64-1 | acetone | A4 |

- **MAK (German Maximum Workplace Concentration)**

None of the ingredients is listed.

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **National regulations:**

- **Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.**

(Contd. on page 10)

USA

Safety Data Sheet acc. to OSHA HCS

Printing Date 07/22/2014

Revision Number 1

Revision Date 07/22/2014

Trade name: 1535 SUPER WEATHERSTRIP ADHESIVE (BLACK)

(Contd. of page 9)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, IES makes no representations as to the completeness or accuracy thereof.

Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will IES or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, IES makes no representations as to the completeness or accuracy thereof.

Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will IES or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

· **Department issuing SDS:** Regulatory Department.

· **Creation Date:** 07/22/2014

· **Date of preparation / last revision** 07/22/2014 / -

· **Abbreviations and acronyms:**

DOT: US Department of Transportation

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1