





32 & M62 SERIES MAGNETIC LOCKS



32



M62

- Operating temperature: -40 to +60C
- Warranty: MagnaCare lifetime replacement warranty
- Patented instant release circuit, no residual magnetism
- UL listed
- Fully sealed electronics, tamper proof and weatherproof
- Finish: Brushed stainless steel
- Ten feet of jacketed, stranded conductor
- Automatic dual voltage, no field adjustment required

32


- Holding force: 600 lbs
- Current draw voltage: 300mA at 12VDC; 150mA at 24VDC
- Size: 8"L x 1.88H" x 1.5"D

M62

- Holding force: 1,200 lbs
- Current draw and voltage: 250mA at 12VDC; 125mA at 24VDC
- Size: 8"L x 2.9"H x 1.75D"

MFG #	HOLDING FORCE	EZ #
M32 24VDC	600 LBS	028116
M62 12/24VDC	1200 LBS	013349

2000 LBS HOLDING FORCE GATE LOCK



- 2000 lbs holding force
- Operates under pre-load up to 100 lbs
- Automatic dual voltage - no field adjustment required
- Fail secure convertible to fail safe
- Manual key override (right or left hand)
- Self-aligning receiver (+/- 1/2" horizontally) helps compensate for gate misalignment and sag
- Tamper proof cast aluminum housing
- Latch status monitor switch (SPDT)
- Heavy wall 1/2" inside diameter threaded steel coupling
- Hardened steel latch
- Surface mount
- Black krinkle powder coated finish
- Holding force: 2000 lbs
- Current draw and voltage:
 - » 12 volts initial (peak): (~1.0 second) at 870mA - reduced: 290mA
 - » Power consumption: 3.5 watts
 - » 24 volts initial (peak): (~1.0 second) at 720mA - reduced: 170mA
 - » Power consumption: 4.1 watts
- Operating temperature: -50°C to +75°C

MFG #	HOLDING FORCE	EZ #
GL1	2000 LBS	086794