


STANDARD SPECIFICATIONS:

- Series: Heavy Duty
 Body: Cast Iron, Precision Machined
 End Covers: Cast Iron, Precision Fully Machined
 Rotor: Fabricated Mild Steel, Open-Ends, 8-Vanes
 Rotor Tips: Replaceable Mild Steel
 Bearings: Sealed for Life, Mounted Outboard
 Shaft Seals: PTFE, Braided
 Clearances: Machined for Ambient
 Drive: 1 HP, 230/460/3/60, TEFC, 1800 RPM, C-Face Motor with Gearbox, Chain Driven with Taperlock Sprockets, Enclosed in a Mild Steel Safety Guard
 Speed: 22 RPM
 Paint: Sunco Blue Enamel, Guard Safety Yellow

IMPORTANT SAFETY NOTICE:

1. All dimensions are in inches, unless stated otherwise.
2. For exposed inlets and outlets, safety guards are required and available from Sunco.

GENERAL ARRANGEMENT - NOT CERTIFIED



Sunco Powder Systems, Inc.
 1863 ROCK HILL HIGHWAY - LANCASTER, SC 29720
 Phone: 704-545-5545
 www.suncovalves.com

12" ROTARY AIRLOCK VALVE, ROUND

DATE: 01/01/15
 DRAWING NO.: 20155-0012-C1-RD