



### Technical Specifications

Transmitter type:	Crystal controlled 2-stage ("B" suffix denotes 3-stage)
Calibration tolerance:	±2.5kHz
Frequency stability:	±2.5kHz, -20°C to 40°C
Pulse rate and width:	Typical on time 20ms, off time 1100ms (controlled by uC)
Pulse rate variation:	0.01%/volt, ±0.01% for temperatures -20°C to +40°C
Battery:	Lithium
Activation:	By removing magnet
Encapsulation:	Electrical resin, water-proof, specific gravity: 1.12 Coated with USP Class VI material

MODEL	BATTERY	BATTERY CAPACITY (days)		DIMENSIONS (mm)		WEIGHT (grams)	PRICE GROUP
		40 ppm	55 ppm	A	B		
	3.5V	40 ppm	55 ppm	A	B		
A2610*	10-12	73	56	11	30	6	E
A2620*	10-18	182	140	11	36	7	E
A2630*	10-25	264	202	11	43	8	E
A2650*	10-35	365	280	11	53	11	E
A2660	1/2AA	654	502	16	42	13	B
A2670	2/3AA	787	603	16	51	20	B
A2670B	2/3AA	300	222	16	51	22	B

\*Flat bottom option

Factors other than battery capacity may reduce life.

Warranty life is 50% of battery capacity.

470 First Ave. No. • Isanti, MN 55040-7123  
763.444.9267 • fax:763.444.9384 • sales@atstrack.com • www.atstrack.com