

Jazz

REFRACTION UNIT

Jazz Refraction Unit, together with its sleek design, and its unique control panel is easy to use for the process of examination and it is much more comfortable for both the patient and the doctor.



VIEWLIGHT™
POWERED BY INNOVATION

U.S. CORPORATE OFFICE
8380 NW 64TH ST
MIAMI, FL 33166
TEL: 1.305.406.3915
FAX: 1.305.938.5012
customerservice@viewlightusa.com



www.viewlightusa.com

TECHNICAL SPECIFICATIONS

● Product Class	Class 1 (Low risk)
● Protection against electric shock	Type B Class I
● Level of protection IP	IPX4 – Splash guard
● Operating Mode	Continuous operation
● Voltage	127 / 220V
● Frequency of operation	50 / 60 Hz
● Load current	2A
● Motor	CC 24V
● Fuse type	Fast fuse 0,79in – 2A
● Energy consumption	150W
● Maximum lift capacity	396.83 Lb
● Dimensions (stretcher configuration)	74.41 x 28.35 x 20.08 in (L x W x H)
● Dimensions (standard configuration)	39.37 x 28.35 x 48.42 in (L x W x H)
● Seat height maximum / minimum	27.56in / 20.01in
● Area occupied (stretcher configuration)	2108in ²
● Net weight	187.39Lb
● Gross weight	246.92Lb
● Packaging type	Wooden Case
● Package Dimensions	43.31 x 29.53 x 50.39in (L x W x H)

Jazz

REFRACTION UNIT



FEATURES

Chair

- Chair reclines electrically to 180° making procedures in a fully electric stretcher.

Stand

- Fully adjustable arm for phoropter
- Projector Arm
- Auxiliary arm for another small instrument
- Counterbalanced arm for slit lamp
- Contains receptacles for recharging instruments 3.5V diagnostic

U.S. CORPORATE OFFICE
8380 NW 64TH ST
MIAMI, FL 33166
TEL: 1.305.406.3915
FAX: 1.305.938.5012
customerservice@viewlightusa.com

VIEWLIGHT[™]
POWERED BY INNOVATION



www.viewlightusa.com