

Type Approval Certificate



This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 44 880 - 07 HH

Company BMT Co., Ltd.
21-1 Bukjeong-dong Yangsan
Gyeongsangnamdo 626-110, KOREA, REPUBLIC OF

Product Description PIPE UNIONS

Type Superlok Tube Fittings

Environmental Category None

Technical Data / TECHNICAL DATA

Range of Application Material: Stainless steel SS316
Metallic sealing with cutting ring
Temperature range [°C]: -55 up to +400
Nominal Pressure PN [bar]: refer to page 2

RANGE OF APPLICATION

The above mentioned pipe unions of type superlok are type approved as compression coupling for the use in piping systems according the Rules I-1-2 Machinery Installations, Section 11, Table 11.13 / 11.14, compression coupling, bite type, fire resistant.

LIMITATIONS

Threaded bulkhead pipe unions are not approved through watertight bulkheads.

Test Standard VI-7-8: Test Requirements for Components and Systems of Mechanical Engineering and Offshore Technology, Edition 2008.

Documents
- Test report BTR-S070430-01
- Manufacturing Inspection and Test Plan BMT-ITP-601
- Product catalogue BMT CTF-3 (05.01.06)
- GL Approval Ref.-No.: 12-050446

Remarks The selection of the pipe unions for the corresponding service and the right installation are to be in accordance with the instructions of the manufacturer.

Valid until 2017-06-13

Page 1 of 2

Type Approval Symbol



File No. ILC.05

Hamburg, 2012-05-15

Germanischer Lloyd

Hanspeter Raschle
Hanspeter Raschle
Sven Dudsus
Sven Dudsus

Type Approval Certificate



This is to certify that the undernoted product(s) has/have been tested in accordance with the relevant requirements of the GL Type Approval System.

Certificate No. 44 880 - 07 HH

TECHNICAL DATA

Tube O.D. [inches]	Nominal Pressure PN [bar]
1/8"	752,0
3/16"	703,0
1/4"	703,0
5/16"	552,0
3/8"	448,0
1/2"	462,0
5/8"	414,0
3/4"	400,0
7/8"	331,0
1"	324,0

Tube O.D. [mm]	Nominal Pressure PN [bar]
4	993,0
6	876,0
8	703,0
10	552,0
12	497,0
16	469,0
18	462,0
20	414,0
22	372,0
25	359,0

The pressure reduction factors for service temperatures above 50°C are to be observed.

Valid until 2017-06-13

Page 2 of 2

Type Approval Symbol



File No. II.C.05

Hamburg, 2012-05-15

Germanischer Lloyd

Hanspeter Raschle

Hanspeter Raschle

Sven Dudzusz

Sven Dudzusz

This certificate is issued on the basis of "Guidelines for the Performance of Type Approvals Part 1, Procedure".