



YT-RJ45 waterproof connector application type



YT-RJ45 dedicated for signals of CNLINKO provides solutions for signal transmission in harsh environments. These connectors are especially suitable for applications for Ethernet in audio, commercial, entertainment, on-site stage equipment, DMX lighting, industrial and outdoor network connection environments. The YT-RJ45 series provides cable jackets, assembled Socket Plug, straight plug, cable couplers and protection styles. The IP44/IP65 protection level is the strongest protection for the installation box.

Series product information:

Series code:	Signal type: RJ45				
Material type:	Plastic type, metal type, plastic and metal type				

Introduction:

YT series are industrial–specific signal connectors. The metal model uses a zinc alloy shell, which has high strength; the plastic model uses an engineering plastic shell, which is light in weight. The product has excellent and stable electrical performance, and is suitable for the connection of equipment installed in front of and behind the board, and can also be used for system connection outside the equipment. The operation is simple, safe and stable.

• Main body material, process and surface treatment:

Shell:	Material: Engineering Plastic/Metal treatment: chrome plating
Silell.	Production Process: Injection Molding & Die Casting & Machining Surface

Module material, process and surface treatment:

Contact:	Material: Male/Female Pin (Copper Alloy) Treatment: Gold plated over nickel						
	Production Process: Machining & Stamping Surface						
Insulator:	Material: engineering plastic Production process: injection molding						

Packaging and Storage:

The product is in a sealed bag, with a small box in the large box, and a label on the small box. The label indicates the product name, model, batch number, and number of products. Packaged products are recommended to be stored in a warehouse with an ambient temperature of $25\% \pm 3\%$, a relative humidity of $\leq 72\%$, and no acidic, alkaline and other corrosive gases in the surrounding air. Other storage environments may affect product life.

• Check the official website YT-RJ45 series area:

Scan the QR code below to check the YT-RJ45 area of CNLINKO's official website. If you have any doubts, you can contact the online customer service for more detailed product information.



QR code of YT-RJ45 series

(NLINKO,

Applications



YT-RJ45 series products are used in a certain equipment information control box

Features Overview



Excellent waterproof/dustproof performance

The protection level of YT series can reach IP65 when connected, which can provide good electrical protection performance for the equipment.



Multiple style options

Various materials and styles are available to meet the needs of different application scenarios.



Super anti-shielding ability

Precise structure, high-speed transmission, without any delay, faster, more stable and more secure transmission.



Panel Mount

External connection and installation, stable and convenient, safe and reliable.



YT-RJ45 Series Information Overview

P139

Product	Signal: RJ45						
application type:	The rated voltage of the power connection is 42V, the rated current is 1.2A, and the shield is optional.						
Cable O.D:	Signal type: RJ45: Φ5.5~Φ7.0mm						
Details page:	Product Parameter Map: P139	Dimension Drawing: P141					

Main feature:

- According to EIA568B/ISO/IEC11801 standard, it complies with D-pole/CAT3e/CAT5e, and the data transmission rate can reach 10M/s, 1000M/s, 1000M/s;
- Multi-style connection design, 1/4 quick bayonet connection (YT01), quick plug (YT10) and push-pull;
- The cable jacket has a solid die-cast outer shell and a unique double-clamped ferrule;
- Shielding system——high frequency noise immunity and electromagnetic interference protection;
- The product conforms to the IP44/IP65 protection level when connected.

137 I DYNAMIC LINKO, HIGHLIGHTS THE FUTURE

(NLINKO

→ YT-RJ45 Datasheet



		Product Series		YT-RJ45							
		Number Of Cores		RJ45					_		
	RJ45	Application Type Section							_		
	Signal	Current Rating		_					_		
		Voltage Rating		_					_		
		Cable O.D Range	φ 5.5 ~ φ 7.0mm —								
		Wire Size	26-24AWG —								
		Protection Level	IP44/IP65 (In connected state)								
		Assembly Method	1/4 quick bayonet con	nection/plug-in connection/push-	-pull connection				_		
			Circula	Metal			Circular Engi	neering Plastic	Square Engineering Plastic		Square Metal
p I u g		YT-RJ45-CPE-10-001	YT-RJ45-CI	PE-10-002 YT-RJ45-0	PE-11-001		YT-RJ45-CPE-01-001	YT-RJ45-CPE-29-001	YT-RJ45-CPE-13-001	YT-RJ45-CPE-05-001	YT-RJ45-CPE-03-001
	YT-RJ45-JSX-16-0	01	YT-RJ45-JSX-17-001	YT-RJ45-JSX-22-002	YT-RJ45-JSX-21-002		YT-RJ45-JSX-01-001	YT-RJ45-JSX-29-001	YT-RJ45-JSX-05-002	YT-RJ45-JSX-07-001	YT-RJ45-JSX-05-003
r e c e p t a c l	YT-RJ45-JSX-24-0	02	YT-RJ45-JSX-25-001	YT-RJ45-JSX-32-001	YT-RJ45-JSX-26-001(IP44)		YT-RJ45-JSX-04-002	YT-RJ45-JSX-29-004	YT-RJ45-JSX-02-001	YT-RJ45-JSX-08-001	YT-RJ45-JSX-10-001
e	YT-RJ45-JSX-18-001(-RJ45-JSX-19-001(IP44)	YT-RJ45-JSX-21-001(IP44)	YT-RJ45-JSX-22-001(IP44)		_	_	_	_	_


(NLINKO,

── YT-RJ45 Dimension Drawing (unit: mm)


Plastic Circular Connector YT-RJ45-CPE-01-001









Plastic Circular Receptacle YT-RJ45-JSX-01-001









Plastic Circular Receptacle YT-RJ45-JSX-04-002











Square Connector YT-RJ45-CPE-05-001









Square Connector YT-RJ45-CPE-13-001










Square Receptacle YT-RJ45-JSX-02-001












Square Receptacle YT-RJ45-JSX-08-001










NLINKO

── YT-RJ45 Dimension Drawing (unit: mm)


Plastic Circular Connector YT-RJ45-CPE-29-001









Plastic Circular Receptacle YT-RJ45-JSX-29-001









Plastic Circular Receptacle YT-RJ45-JSX-29-004










Metal Circularplug Connector YT-RJ45-CPE-11-001/2








Metal Circularplug Connector YT-RJ45-CPE-10-001/2










Metal Square Receptacle YT-RJ45-JSX-16-001









Metal Square Receptacle YT-RJ45-JSX-17-001



