



**OLD WESTERN PAINT CO., INC**  
**2001 West Barberrry Place**  
**Denver, Colorado 80204**

Phone: 303-825-5147/888-765-9827

Fax: 303-825-2437

[www.oldwesternpaint.com](http://www.oldwesternpaint.com)

**PRODUCT INFORMATION**

**POLY VAR POLYURETHANE**  
**QUICK DRY PRIMER/SANDING SEALER**

1270-01

**TYPE :** One packaged oil modified pure polyurethane quick dry primer/sanding sealer.

**DESCRIPTION:** A superior quality fast drying primer/sanding sealer designed specifically for hardwood floors, paneling, furniture, cabinets and woodwork. Offers maximum sealing and inter-coat adhesion when top coating with POLY VAR Gloss, Semi Gloss, Velvet or Satin Finish.

**CLEAN UP:** Mineral Spirits

**APPLICATION:**

Brush, Spray, Lambswool applicator – Stir thoroughly before using. Remove dirt, grease and waxes.

New Work - Properly prepare surface by sanding and removing all dust, wipe with tack cloth or lint free rag dampened with mineral spirits. Fill open grain woods with a wood filler compatible with polyurethanes.

Old Finishes, Not Peeling – Sand and remove sanding dust as above.

Old Finishes in Poor Condition – Remove completely by sanding and remove sanding dust as above.

Apply first coat QUICK DRY PRIMER/SANDING SEALER on bare wood. Allow 2 or more hours between succeeding coats. If screening between coats, allow to dry 12 hours, subject to excessive humidity, low temperature, failure of air movement and film thickness.

**DO NOT APPLY OVER STEARATED SANDING SEALERS. NOT RECOMMENDED FOR SEALING GARAGE FLOORS.**

**SPREADING RATE:** 550-700 square feet per gallon, subject to surface porosity, texture and application method.

**DRYING TIME:** Dries in 1 hour – first coat on bare wood (dust-free), succeeding coats up to 2 hours. Drying time may be affected by excessive humidity, low temperature, failure of air movement and thickness of finish.

**ANALYSIS:**

SOLIDS BY WEIGHT	40.00%
SOLIDS BY VOLUME	33.00%
SOLVENT TYPE	Aliphatic

GLOSS 60 DEGREE	Semi Gloss
-----------------	------------

V.O.C. content 525 grams/liter, 4.38 lbs./gallon

LIMITED WARRANTY if used as directed, including proper application and surface preparation in accordance with label directions, this product is warranted to be free from defect when used for its intended application for a period of one year from the date of purchase. This limited warranty does not apply if the product is mixed with any other ingredient. Buyer assumes all risks of handling. Buyer assumes all risks of handling. Buyer's sole and exclusive remedy with respect to any defective product is replacement of product or refund of the purchase price, at Manufacturer's sole option and only after receipt of proof of purchase. THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND DESIGN. IN NO EVENT SHALL MANUFACTUREER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LABOR COST. Some states do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.