



GasAlert MaxXT II

multi-gas detector



Go the distance, and save

GasAlertMax XT II is the smart, simple, economical way to compliance. Workers feel safe and incidents are minimized so everyone will be able to do more. That means savings realized from business continuity and productivity.

Simple operation, with SmartSample pump.

GasAlertMax XT II reliably monitors up to four hazards and combines straightforward one-button operation with our robust, motorized pump for intelligent, remote sampling, ideal for confined spaces. The GasAlertMax XT II is fully compatible with MicroDock II automated test and calibration system.



H₂S

CO

O₂

LEL

**WATER
RESISTANT**












- Minimize costs and training with one-button operation
- More accurate sampling results with SmartSample pump technology
- Compact, comfortable and field tough

BW
Technologies
by Honeywell

Wear yellow. Work safe.

Standard features of BW products:

- Continuous LCD shows real-time gas concentrations
- Compact and lightweight design makes it comfortable to wear
- Water-resistant
- Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- Full function self-test of sensor, battery status, circuit integrity and audible/visual alarms on start up
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot

GasAlertMax XT II Specifications																	
Size	5.1 x 2.8 x 2.0 in. / 13.1 x 7.0 x 5.2 cm																
Weight	11.5 oz. / 328 g																
Temperature	-4 to 122°F / -20 to 50°C																
Humidity	10 - 100% RH (non-condensing)																
Alarms	- Visual, vibrating, audible (95dB) - Low, High, STEL, TWA, OL (over limit), Low Battery, Pump																
Tests	Audible/visual alarms on activation, sensors, battery, pump and circuitry (continuous)																
Typical battery life	13 hours @ 32°F / 0°C 8 hours @ -4°F / -20°C Recharges in 6 hours																
Pump draw	Sample from up to 75 ft. / 23 m																
User options	<table border="0"> <tr> <td>Confidence beep</td> <td>Force calibration when overdue</td> </tr> <tr> <td>Safety (sensor) lock</td> <td>Sensor configuration</td> </tr> <tr> <td>Latching alarms</td> <td>Detector identification</td> </tr> <tr> <td>Safe display mode</td> <td>Low alarm acknowledge</td> </tr> <tr> <td>Calibration IR lock</td> <td>Language choices (five)</td> </tr> <tr> <td>Location selection</td> <td>Set custom start-up message</td> </tr> <tr> <td>Force block test</td> <td>Confidence interval</td> </tr> <tr> <td>Force bump test when overdue</td> <td>Datalog interval</td> </tr> </table>	Confidence beep	Force calibration when overdue	Safety (sensor) lock	Sensor configuration	Latching alarms	Detector identification	Safe display mode	Low alarm acknowledge	Calibration IR lock	Language choices (five)	Location selection	Set custom start-up message	Force block test	Confidence interval	Force bump test when overdue	Datalog interval
Confidence beep	Force calibration when overdue																
Safety (sensor) lock	Sensor configuration																
Latching alarms	Detector identification																
Safe display mode	Low alarm acknowledge																
Calibration IR lock	Language choices (five)																
Location selection	Set custom start-up message																
Force block test	Confidence interval																
Force bump test when overdue	Datalog interval																
Ratings	EMI/RFI: Complies with EMC Directive 2004/108/EC																
Ingress Protection	IP66/67																
Certifications and approvals	<table border="0"> <tr> <td></td> <td>Class I, Div. 1, Gr. A, B, C, D</td> </tr> <tr> <td>IECEX:</td> <td>Ga Ex ia IIC T4</td> </tr> <tr> <td>ATEX:</td> <td>CE  II 1 G Ga Ex ia IIC T4</td> </tr> <tr> <td></td> <td>Br Ex ia IIC T4</td> </tr> </table>		Class I, Div. 1, Gr. A, B, C, D	IECEX:	Ga Ex ia IIC T4	ATEX:	CE  II 1 G Ga Ex ia IIC T4		Br Ex ia IIC T4								
	Class I, Div. 1, Gr. A, B, C, D																
IECEX:	Ga Ex ia IIC T4																
ATEX:	CE  II 1 G Ga Ex ia IIC T4																
	Br Ex ia IIC T4																
Warranty	Full two year warranty including all sensors																

Additional GasAlertMax XT II features:

- Integrated sampling pump with reliable diaphragm technology
- Best in class block detection with semi-conductor pressure sensor
- Multi-language support in English, French, German, Spanish and Portuguese
- Conveniently manage your detector with Fleet Manager II
- Equipped with standard datalogging and event logging

Options and Accessories



MicroDock II compatible



Belt holster



Multi-unit cradle charger



Concussion-proof boot

For a complete list of accessories, please contact BW Technologies by Honeywell.

Sensor Specifications		
Gas	Measuring Range	Resolution
H₂S	0-200 ppm	1 ppm
CO	0-1000 ppm	1 ppm
O₂	0-30.0%	0.1%
Combustible gases	0-100% LEL 0-5.0% v/v	1% 0.1%

Alarm setpoints for all sensors are user adjustable. Setpoint(s) are automatically displayed during instrument start-up.



Corporate Headquarters

2840 - 2 Avenue S.E.
Calgary, AB, Canada T2A 7X9
Phone: +1.403.248.9226
Toll free: 1.800.663.4164

www.gasmonitors.com

USA 1.888.749.8878
Europe +44 (0)1295.700.300
France +33 (0) 442.98.17.70
Germany 49 (0) 2137.17.6522

info@gasmonitors.com

Middle East +971.4.887.1766
S.E. Asia +65.6580.3468
China +86.10.6786.7305
Australia +61.3.9464.2770

Latin America +55.11.3475.1873
Other Countries +1.403.248.9226

6570-0-EN
© 2010 Honeywell International Ltd. All Rights Reserved.

Locally available from

sensorsforsafety.co.uk
World Class Products

Distributed by:
Sensors for Safety Ltd
Knaresborough Technology Park
Manse Lane
Knaresborough
North Yorkshire
HG5 8LF
Tel: 01423 206360
E-Mail: sales@sensorsforsafety.co.uk
www.sensorsforsafety.co.uk

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.