

PULL STATION



For emergency release application in blue.

- Single gang mount
- Switch: 1amp @ 30VDC, N/C
- Often required by code when installing an electromagnetic lock
- Fench & English on label

| MFG # | EZ # |
|---------|--------|
| CM701BE | 086878 |

C

7 DAY TIMERS



With up to 8 flexible daily or weekly (on/off) schedules, the CX-247 can automatically activate/de-activate electric locks and magnets, automatic doors, or control lighting or energy management devices.

- Programmable 7 day timer with 8 daily or weekly schedules
- Internal memory back-up
- Easy to program/set up
- Water resistant enclosure
- Current draw: .1 mA Idle, 10 mA operating
- SPDT contacts rated 16 amps @ 30 VDC, N/O + N/C

| MFG # | VOLTAGE | DIMENSIONS | EZ # |
|----------|----------|--------------------------|--------|
| CX247 12 | 12VAC/DC | 2-3/8" x 2-3/8" x 1-1/4" | 075472 |
| CX247 24 | 24VAC/DC | 2-3/8" x 2-3/8" x 1-1/4" | 075473 |

DOOR INTERFACE RELAYS



A versatile make/break relay, the SA-1 features separate triggers and multiple operating modes, for smoke-evac or unidirectional sequencing applications.

- Momentary and extended trigger
- 3 operating modes
- Noise filtering ensures reliability
- 3 LED's for visual confirmation
- 2 SPDT contacts rated 2 amps @ 28 VDC
- 3 timers: 1/4 - 30 seconds

| MFG # | VOLTAGE | DIMENSIONS | EZ # |
|--------|--------------|--------------------|--------|
| CX-SA1 | 12-24 VAC/DC | 4" x 3-1/2" x 3/4" | 080734 |