

GEN-838H (4400W-9.6kW-60Hz-16yr) Hybrid 120V-240V	Geneforce Emergency Power System
Product Features	
Silent operation. Safe for indoors. No gas or emissions.	
No Installation; No Maintenance; No Permits required	
Arrives fully charged and ready to work.	
Automatic & one-touch start.	
System Control Panel with Graphical 128 x 64-pixel, backlit LCD displays power reserves, amp hours consumed, fault conditions, solar panel output, charging, power consumption.	
Overheat Temperature Sensor & Automatic Shutdown feature.	
Built-in voltage regulation system for sensitive electronics.	
Built-in 40A solar charge controller for solar panel charging.	
Electrical Specifications	
Output power (continuous) at 25°C	3,800 W
Output power (30 min) at 25°C	4,400 W
Output power (5 sec) at 25°C	7,000 W
Peak current	41 A
Output frequency	50 / 60 Hz selectable
Output voltage	120 / 240 Vac
Output wave form	True sine wave
Input DC voltage range	40-68 Vdc
AC connections	Single / Split phase
Charger	
Output current	45 A
Nominal output voltage	48 Vdc
Charge control	3 stages
Charge temperature compensation	Battery temperature sensor included
Input AC voltage	120 / 240 Vac split phase
Input AC voltage range line to neutral	95 - 135 Vac single phase; 170 - 270 Vac
AC input voltage requirements	240V default *phase between L (1) and L (2) must be 180° to qualify AC
AC input 1	One 30A, 250 Volt, NEMA L14-30P, 3P, 4W, locking plug with 8 ft. cord
AC output 1	Two (20A/125V) NEMA 5-20R isolated ground receptacles
AC output 2	Two (20A/125V) NEMA 5-20R isolated ground receptacles
AC output 3	One 30A, 125/250 Volt, NEMA L14-30R, 3P, 4W, locking receptacle
Dead battery charge	Yes
Battery bank reserve power (Wh)	9.6 kW (9,600 Watts hours)
Battery Bank Amp Hours (Ah)	800 Amp Hours
Battery service life	12-16 years on float
Solar charge controller	40A-12/48V (~1,920 W per hour/sunlight)
General Specifications	
Transfer relay rating	30A Transfer time (AC to inverter and inverter to AC) <1 cycle (16.7ms)
Optimal operating temperature range	-20°C to 60°C (-4°F to 140°F)
Regulatory approval	
Safety	Components are (CSA) us mark CSA C22.2, No. 107.1-01 UL1741 Ed.2
EMC directive	FCC Part 15 Class B
General Specifications	
Product Dimensions (H x D x W) and weight	(36" x 18 x 36") & (820 Lbs.) 373 kg.
Shipping Dimensions (H x W x L) and weight	Standard Pallet 42" x 36" x 48" (990 lbs.) 450 kg.
Construction	Strong Steel, Four Casters, Color-Dove Grey
Warranty	2-year warranty on components; up to 3-years on batteries
Part Number	GEN-838H-120240-3800-16-SW
Price	\$10,979