



# WET4 LED SERIES

LED 4FT

ENCLOSED FIBERGLASS

**SOUTHEAST LIGHTING, INC.**

**704-372-5240 / 877-688-5240**



**SPECIFICATIONS :**

Width of fixture - 14.6"

Depth of fixture - 5.9"

Length of fixture - 51.9"

**SPECIFICATIONS :**

**HOUSING :** 5VA Flammability rating in accordance with UL94 and(f1) in accordance with UL746

**GEARTRAYS:** Pre-painted cold rolled steel with minimum 87% total reflectance. Stainless steel spring fittings.

**ELECTRICAL :** Utilizes high-efficiency LED's boards paired with high efficiency drivers rated from 120v-277v 50/60HZ. 0-10V dimming to 1%.

**MOUNTING :** Easy mounting with V-hooks or cables. Stainless steel V-hook requires no holes to be drilled through the housing. UL rated for 4X fixture weight.

**SHIELDING :** 100% Clear Impact Resistant Acrylic, Polycarbonate and Frosted options available

**LATCHES :** Stainless steel latches standard; provide durability and chemical resistance. Can easily be made tamper resistant.

**UL LISTED :** All fixtures are list by and bear label of Underwriters Laboratories, INC - Suitable for WET Locations.

**CERTIFICATIONS:** NEMA 4X, IP65, IP66, IP67, High Pressure Hose Test, RoHS Complaint, NSF Component

**MANUFACTURER:** All products made and assembled in the United States of America.

<i>WET4 LED</i>	<i>840</i>	<i>195L</i>	<i>UNV</i>	<i>CFR50</i>
Series	Color	Lumens Output	Voltage	Diffuser
WET4 LED	830 (3000K) 835 (3500K) 840 (4000K) 850 (5000K)	195L - 19,500 Lumens	UNV	CIRA - Clear IR Acrylic CFR50 - Clear IR Frosted Acrylic  <i>IR - Impact Resistant</i>

**Catalog Number**

**Type**

**CONTACT FACTORY FOR MORE OPTIONS**