



PRESENTS THE

SL-3750 Powder Vacuum System



S2700
Power Unit



DC-1240
Primary
Powder Canister



DC-500
Secondary
Powder Canister

The Performance of S2700

Motor: 8.4"
Voltage: 120 A.C.
Shipping Weight - Power Unit (Approx.): 55.0 lbs
Max Amperage (Approx.): 13.8 amps
Electrical Service to Unit: 120 volt
Pump:.....Tangential 2-Stage By-pass .
Airflow @ 2" Opening (Approx.):.....142 C.F.M.
Sealed Vacuum (Approx.):.....147" H₂O
Vacuum Pump Housing:
Diameter (Approx.): 13-5/8"
Height (Approx.): 15-3/4"

Primary Powder Canister - DC-1240:

Filtration: Cyclonic primary, standpipe secondary,
with convenient lift off inspection lid
Diameter:..... 16-1/8"
Height:.....40-1/4"

Powder Canister Capacity (Approx.):38 Qts.
Shipping Weight - Powder Canister (Approx.):..... 23.0 lbs.

Secondary Powder Canister - DC-500:

Filtration: Disposable Paper Bag
Inlet and Outlet Connections:.....2"
Diameter:..... 13-5/8"
Height: 25-3/4"
Capacity (Approx.):.....27 Qts.
Shipping Weight (Approx.):..... 10.0 lbs.
Replacement Filter: HPB-2H

Notes: Ambient Temperature must be below 100° F.
If unit over heats, you must unplug and replug the unit in to get it
to start again. **Unit must be kept well ventilated.**




www.eicgroupusa.com
Office: 214-477-1344 • Fax: 972-317-6889



Powder Vac Kit includes:

1	S-2700	POWER UNIT	110'	2VM1000UL	REMOTE CONTROL WIRE
1	DC-500	HEPA BAG FILTERED DIRT CANISTER	59	SS-200	HEAT SHRINK SLEEVE
1	DC-1240	14" CYCLONIC DIRT CANISTER	2	UA-221X	1-1/2" UTILITY VALVE W/ MICRO SWITCH
112'	SF-207	2" STEEL TUBING	1	CH-225	1-1/2" X 30' CONDUCTIVE HOSE
15	SF-213	2" STEEL 90 DEGREE ELL	1	IWA-24	48" DOUBLE CURVED INDUSTRIAL WAND
2	SF-216	2" STEEL 45 DEGREE ELL	1	IFB-635	14" METAL HEAVY DUTY FLOOR BRUSH
1	SF-215	2" STEEL 90 DEGREE TY	1	IW-224	METAL HEAVY HANDY TOOL
10	SF-202	2" STEEL COUPLING	1	IW-221-2	BRUSH FOR IW-224
1	PF-200SW	SQUARE MUFFLER	1	ICT-624A-1	24" LONG METAL CREVICE TOOL
19	PF-2051'W	TUBING STRAP	1	H-331	HOSE HANGER
			1	CB-180	CADDY BAG

Included Accessories



CH-225
1-1/2" Clear
Conducting Hose



IFB-635
14" Industrial
Floor Brush



IW-224 & IW-221-2
Handi Tool



ICT-624A-1
24" Crevice Tool



IWA-24
Aluminum Curved Wand



CWP332
Commercial
Stainless Steel
Wet Pickup Bucket



DC1633
33 Gallon
Interceptor

(DO NOT MOUNT OVER 8' HIGH IN WARM AREAS.)

NOTE: ALL METAL TUBING AND FITTINGS MUST BE GROUNDED.