

GLADIATOR

LUXURY VINYL PLANK



CLICK

SPECIFICATIONS

PHYSICAL CONSTRUCTION


COMPOSITION:	Stabilcor™ (Polymeric/Extruded Composite Core)
CONSTRUCTION:	Click Lock
WEAR LAYER THICKNESS:	12 Mil
OVERALL THICKNESS:	7.5mm (5.5mm + 2mm EVA Pad)
BACKING:	EVA (Ethylene-Vinyl Acetate) Pad
FINISH:	Polyguard/hp (UV Polyurethane)
EDGE PROFILE:	Bevel
ANTIMICROBIAL TREATMENT:	Yes
INSTALLATION:	Floating/Intermediate Level
RECOMMENDED ADHESIVE:	None Required
MEASUREMENTS:	7" x 48"
	8 planks per carton/18.65 sq ft per carton
	75 cartons per pallet/1,398.75 sq ft per pallet
WARRANTY:	30-Year Limited Residential Wear
ADDITIONAL BENEFITS:	100% Waterproof, Floor Score Certified, Antimicrobial, Scratch & Slip-Resistant



Stabilcor™



COLORWAYS




EUROPEAN OAK - HF551



WEATHERED OAK - HF552



COLONIAL PECAN - HF554



APPALACHIAN OAK - HF555



PLANTATION OAK - HF556



ASPEN OAK - HF557

HIGH SHADE VARIATION

NOTE: Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.