

CLAUSB USB TO RS485 CONVERTER



- Designed to make serial port expansion quick and simple
- External 4-pin DIP switch to set RS-232, RS-422 or RS-485 mode conveniently
- DIN-rail mountable bracket for industrial environment
- Both a 6-pin terminal block and a DB9 male connector are available for optimal flexibility for serial connection
- Provides instant connectivity to RS-232, RS-422 and RS-485 communication devices serial port by connecting to a PC's USB port by connecting to its USB port
- Speed up to 38.4 kbps
- Powered by USB port - No external power supply required
- Includes: USB cable & driver
- Supports SmartLock®, Hurricane and Maestro controllers
- Ports: 1 RS232/422/485 port
- Speed: up to 38.4 kbps
- RS232 signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
- RS422/485 signals: RS422 TxD+/-, RxD+/-, RTS+/-, CTS+/-, GND, RS485 Data+/-, GND
- Driver: Windows 98, ME, 2000, XP, 2003 Server, Vista and Windows 7
- Connectors: 1 DB9 male and terminal block
- Dimensions: 57 x 72 x 22 mm (W×L×H) 82 x 77 x 22 mm with DB9 connector and ears

C

| MFG # | DESCRIPTION | EZ # |
|-----------|---------------------------------|--------|
| CA CLAUSB | USB Serial Communication Device | 087108 |

ZODIAC® LINK FINGERPRINT READER KIT



- Enroll and manage up to 2,000 users (2 templates per user) right at the reader
- Use with a ZDCM door control module for a totally stand-alone solution
- Alternatively, allows existing proximity readers in a standard access control system to be upgraded to biometrics in under 5 minutes
- User templates can be copied from one unit to another - no need to re-enroll users should a unit need to be replaced
- Programmable via reader keypad
- Two line LCD display guides users easily through all programming functions
- No PC or software required
- No credentials required
- Includes: 1 Zodiac Link reader, 1 door control module, 1 enclosure, 1 power supply and 1 plug-in transformer

| MFG # | DESCRIPTION | EZ # |
|------------------|------------------------------|--------|
| CA ZODIACLINKKIT | Biometric Access Control Kit | 082969 |