



Monofilament fish line and tubing provided. User to determine tubing length and antenna exit location.

Technical Specifications

| | |
|------------------------|---------------------------------------------------------------------------|
| Transmitter type: | Crystal controlled 2-stage |
| Calibration tolerance: | ± 2.5kHz |
| Frequency stability: | ± 2.5kHz, -20°C to 40°C |
| Pulse rate and width: | Typical on time 15ms, off time 1.1-2.0sec (controlled by astable circuit) |
| Pulse rate variation: | 5%/volt, ± 20% for temperatures -20°C to +40°C |
| Battery: | Silver Oxide |
| Activation: | By removing magnet |
| Encapsulation: | Electrical resin, water-proof, specific gravity: 1.12 |

| MODEL | BATTERY | BATTERY CAPACITY (days) | | | DIMENSIONS (mm) | | | WEIGHT (grams) | PRICE GROUP |
|-------|---------|-------------------------|--------|--------|-----------------|----|---|----------------|-------------|
| | | 30 ppm | 35 ppm | 40 ppm | A | B | C | | |
| M1450 | 337 | 24 | 20 | 18 | 5 | 13 | 5 | 0.55 | B |
| M1410 | 379 | 42 | 36 | 32 | 6 | 15 | 5 | 0.75 | B |
| M1420 | 377 | 72 | 62 | 55 | 7 | 16 | 5 | 1.00 | B |

Above models only available in 48.00-50.66MHz, 144.06-151.98MHz, and 164.00-167.99MHz ranges.

Warranty life is 50% of battery capacity.