

aeroplus m

Mobile Oxygen Concentrator

- **Now with pulsed continuous flow!**
- universal mobile oxygen supply
- latest battery technology
- silent operation
- USB interface
- microprocessor controlled
- adjustable trigger sensitivity
- compliance memory
- easy-to-operate
- internal and external battery chargers



aeroplus m

Mobiler Sauerstoffkonzentrator

- **Jetzt mit gepulstem Dauerflow!**
- lange Betriebsdauer
- neueste Akku-Technologie
- geräuscharmer Betrieb
- USB Schnittstelle
- microprozessorgesteuert
- einstellbare Empfindlichkeit
- Speicher
- leicht zu bedienen
- interne und externe Ladegeräte

Zubehör

- Externes Ladegerät
- weiterer Akku



Mobile Oxygen Concentrator

- **Now with pulsed continuous flow!**
- superior operation time
- latest battery technology
- silent operation
- USB interface
- microprocessor controlled
- adjustable trigger sensitivity
- compliance memory
- easy-to-operate
- internal and external battery chargers

Accessories

- External charger
- Addtl. rechargeable battery

Technische Daten

MPG Geräteklasse	II a, CE 0197
Netzspannung	100-240 V / 50-60 Hz
Temperatur	Betrieb + 5° bis + 40°C Lagerung - 25° bis + 70°C
Gleichspannung	19 V
Schalldruckpegel	< 40 dB (A)
Akku-Betriebsdauer	> 4 Stunden (Stufe 2)
Wiederaufladedauer	< 90 Minuten (Stand-by)
O2-Abgabe	CMV ¹ 150 ml pro Stufe 10 Therapiestufen von 0,5 bis 5,0 (max. 750 ml auf Stufe 5,0)
O2-Konzentration	> 90 %
Atemfrequenz	< 30 bpm
Alarmer (akustisch/ optisch)	Temperatur, Netzausfall, O ₂ , Sensor, System
Schnittstelle	USB
Gewicht	Gerät 3,6 kg Batterie 0,7 kg
Maße (HxBxT)	248 x 230 x 155 mm
Herstellergarantie	2 Jahre (Akku: 1 Jahr)

Technical data

MDD classification	II a, CE 0197
Operating power	100-240 V / 50-60 Hz
Temperature	operation + 5° to + 40°C storage - 25° to + 70°C
DC supply	19 V
Sound level	< 40 dB (A)
Battery operation	> 4 h (@ setting 2)
Recharging duration	< 90 min (Stand-by)
O2 duty	CMV ¹ 150 ml per setting 10 therapy settings from 0.5 to 5.0 (750 ml max. @ setting 5.0)
O2 concentration	> 90 %
Breathing rate	< 30 bpm
Alarms (acoustic/ visual)	temperature, power, O ₂ , sensor, system
Interface	USB
Weight	Device 3.6 kg Battery 0.7 kg
Dimensions (HxLxW)	248 x 230 x 155 mm
Manufacturers warranty	2 years (Battery: 1 year)

¹(CMV = konstantes Minutenvolumen, constant minute volume)

Kröber Medizintechnik GmbH

Salzheck 4 • D-56332 Dieblich

Tel. +49 (0) 26 07 / 9 40 40 • Fax +49 (0) 26 07 / 9 40 422